



DELL P Series P2222H LED display 54.6 cm (21.5") 1920 x 1080 pixels Full HD LCD Black, Silver

Brand : DELL

Product family: P Series

Product code: P2222H

Product name : P2222H

- 54.61cm (21.5") Full HD 1920 x 1080 LED IPS
- 8ms, 16:9, 250cd/m², 1000:1
- USB, VGA, HDMI, DisplayPort
- 54.61cm (21.5") Full HD 1920 x 1080 LED IPS, 16:9, 250cd/m², 16.7M, 8ms, 1000:1

DELL P Series P2222H LED display 54.6 cm (21.5") 1920 x 1080 pixels Full HD LCD Black, Silver:

Stay productive no matter where you work. Reduce harmful blue light with this sleek 21.5-inch FHD monitor featuring ComfortView Plus technology. DELL P Series P2222H. Display diagonal: 54.6 cm (21.5"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black, Silver



Display		Ergonomics	
Display diagonal *	54.6 cm (21.5")	Pivot	✓
Display resolution *	1920 x 1080 pixels	Pivot angle	-90 - 90°
HD type *	Full HD	Swivelling	✓
Native aspect ratio *	16:9	Swivel angle range	-45 - 45°
Display technology *	LCD	Tilt adjustment	✓
Panel type *	IPS	Tilt angle range	-5 - 21°
Backlight type	LED	On Screen Display (OSD)	✓
Touchscreen *	✗	Plug and Play	✓
Display brightness (typical)	250 cd/m ²	LED indicators	Power
Response time	8 ms		
Anti-glare screen	✓	Power	
Screen shape *	Flat	Energy efficiency class (SDR) *	D
Supported graphics resolutions	1920 x 1080 (HD 1080)	Energy consumption (SDR) per 1000 hours *	12 kWh
Supported video modes	480p, 576p, 720p, 1080i, 1080p	Power consumption (standby) *	0.3 W
Aspect ratio	16:9	Power consumption (max)	46 W
Contrast ratio (typical) *	1000:1	Power consumption (off)	0.2 W
Maximum refresh rate *	60 Hz	AC input voltage	100 - 240 V
Viewing angle, horizontal	178°	AC input frequency	50 - 60 Hz
Viewing angle, vertical	178°	Energy efficiency scale	A to G
Display number of colours *	16.7 million colours	Operational conditions	
Response time (fast)	5 ms	Operating temperature (T-T)	0 - 40 °C
Pixel pitch	0.248 x 0.248 mm	Storage temperature (T-T)	-20 - 60 °C
Pixel density	102 ppi	Operating relative humidity (H-H)	10 - 80%
Horizontal scan range	30 - 83 kHz	Storage relative humidity (H-H)	5 - 90%
Vertical scan range	56 - 76 Hz	Operating altitude	0 - 5000 m
Viewable size, horizontal	47.6 cm	Non-operating altitude	0 - 12192 m
Viewable size, vertical	26.8 cm	Packaging content	
Viewable size diagonal	54.6 cm	Stand included	✓
Display diagonal (metric)	54.61 cm		

Display		Packaging content	
sRGB coverage (typical)	99%	Cables included	AC, DisplayPort, HDMI, USB, VGA
Performance		Quick start guide	✓
Flicker-free technology	✓	Weight & dimensions	
Low Blue Light technology	✓	Width (with stand)	487.3 mm
Multimedia		Depth (with stand)	179.6 mm
Built-in speaker(s) *	✗	Height (with stand)	482 mm
Built-in camera *	✗	Weight (with stand)	4.57 kg
Design		Width (without stand)	487.3 mm
Market positioning *	Home	Depth (without stand)	52.1 mm
Product colour *	Black, Silver	Height (without stand)	290 mm
Front bezel colour	Black	Weight (without stand)	2.82 kg
Detachable stand	✓	Bezel width (side)	5.6 mm
Feet colour	Silver	Bezel width (top)	5.6 mm
Heavy metals free	Hg (mercury)	Bezel width (bottom)	1.66 cm
Ports & interfaces		Packaging data	
Built-in USB hub *	✓	Package weight	6.37 kg
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Sustainability	
USB upstream port type	USB Type-B	Sustainability certificates	ENERGY STAR, EPEAT Gold, RoHS
Number of upstream ports	1	Doesn't contain	PVC/BFR
USB Type-A downstream ports quantity	4	European Product Registry for Energy Labelling (EPREL) code	549695
VGA (D-Sub) ports quantity	1	Carbon footprint	
HDMI *	✓	Total carbon footprint	481 kg of CO2e
HDMI ports quantity	1	Total carbon emissions (Standard deviation)	105 kg of CO2e
HDMI version	1.4	Carbon emissions (Manufacturing)	332 kg of CO2e
DisplayPorts quantity	1	Carbon emissions (Logistics)	33 kg of CO2e
DisplayPort version	1.2	Carbon emissions (Use)	114 kg of CO2e
Headphone out *	✗	Carbon emissions (End-of-Life)	2 kg of CO2e
HDCP	✓	Total carbon emissions (w/o Use phase)	366 kg of CO2e
AC (power) in	✓	PAIA version	1.2.15, 2021
Ergonomics		Logistics data	
VESA mounting *	✓	Harmonized System (HS) code	85285210
Panel mounting interface	100 x 100 mm		
Cable lock slot *	✓		
Height adjustment *	✓		
Height adjustment	15 cm		



0884116398004



884116398004

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 10-MAY-2024. Prints or copies of Information are only valid on the printed Publication date