

Product data sheet

Specifications

APC Smart-UPS Online 48V 2U Lithium-Ion External Battery Pack



XBP48RM2U-LI

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	DC
Number of rack unit	2U
Battery Type	Li-Ion (Lithium Ion)
Provided Equipment	4 post rail kit Communication Cable Grounding Cable Installation guide Rack Mounting brackets

Physical

Color	Black with silver front bezel
Height	3.37 in (85.5 mm)
Width	17.01 in (432 mm)
Depth	20.51 in (521 mm)
Net Weight	59.52 lb(US) (27 kg)
Mounting preference	No preference
Mounting Mode	Rack-mounted

Output

Battery Capacity	50 Ah
------------------	-------

Conformance

Standards	UL 1973
-----------	---------

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 % non-condensing

Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Storage Relative Humidity	0...95 % Non-condensing

Batteries & Runtime

Battery Placement	External Frame
Battery Slots Empty	0
Included Battery Modules	0
Device mounting	Rack mount
Battery voltage	48V

Ordering and shipping details

GTIN	731304448952
Package weight(Lbs)	72.75 lb(US) (33 kg)

Packing Units

Package 1 Height	9.17 in (233 mm)
Package 1 width	21.85 in (555 mm)
Package 1 Length	29.02 in (737 mm)

Contractual warranty

Warranty	5 year repair or replace
-----------------	--------------------------