Neomounts®

Videobar & multimedia kit

We are committed to making product choices that are sustainable and rely on the recyclability of our products. Investing in a circular economy where sustainability is at the heart of everything we do. A sustainable approach is essential in addressing global climate change.



Greenhouse gasses emitted into the environment during production of a product contribute directly to our planet's global warming.

Using LCA software¹ we are able to calculate² the (potential) environmental footprint, measured in kilograms CO₂-equivalent. This enables us to evaluate a product's footprint and support the design of sustainable products.

By recycling our products the impact on the environment can be reduced as the recycled material replace the need to produce virgin materials.



ANDE WITH RECY.

Steel

100,0%

Emitted carbon dioxide

To illustrate the effect of a kilogram carbon dioxide, we converted it to kilometres driven by a car.



Without recycling

11,02 kg CO₂ 33 km* With recycling

6,72 kg CO₂ 20 km*

| AFLS-825BL1 | | | | | | | |
|---|--------|--|--|--|--|--|--------|
| | Steel | | | | | | Total |
| Material weight (g) | 2951,5 | | | | | | 2951,5 |
| Kilograms CO ₂ -equivalent | | | | | | | |
| Without recycling | 11,02 | | | | | | 11,02 |
| Recycling reduction % | | | | | | | 39% |
| With recycling | 6,72 | | | | | | 6,72 |
| *8 litres of netral per 100 km ² | | | | | | | |

Sources: ¹ Mobius Ecochain - Ecoinvent v3.6, ² According to EN15804+A2, ³ Foundation myclimate; based on 8 litres of pertrol per 100 km

