



AOC V5 CU34V5C/BK LED display 86.4 cm (34") 3440 x 1440 pixels Wide Quad HD Black

Brand : AOC

Product family: V5

Product code: CU34V5C/BK

Product name : CU34V5C/BK

Screen size (inch) 34, Panel resolution 3440x1440, Refresh rate 100 Hz, Response time MPRT 1 ms, Panel type VA, USB-C connectivity USB-C 3.2 x 1 (DP alt mode, upstream, power delivery up to 65 W), HDMI HDMI 2.0 x 1, Display Port DisplayPort 1.2 x 1, D-SUB (VGA) 0x, DVI 0x, Sync technology (VRR) Freesync

AOC V5 CU34V5C/BK LED display 86.4 cm (34") 3440 x 1440 pixels Wide Quad HD Black:


34" VA WQHD panel for maximum productivity, with MultiView, USB-C and PD65W

The AOC CU34V5C is equipped with a 34" VA curved panel with Ultrawide QHD 21:9 resolution for an immersive viewing experience in a three-side frameless chassis that you can tilt and height adjust as needed. Ready to boost your productivity with USB-C with Power Delivery up to 65W, 4 USB ports & HDMI, it also offers Picture by Picture MultiView for the most complex multitasking.



Display		Ports & interfaces	
Display diagonal *	86.4 cm (34")	Headphone outputs	1
Display resolution *	3440 x 1440 pixels	Headphone connectivity	3.5 mm
HD type *	Wide Quad HD	HDCP	✓
Native aspect ratio *	21:9	HDCP version	2.2
Display technology *	LED	AC (power) in	✓
Panel type *	VA	Mobile High-Definition Link (MHL)	✗
Backlight type	W-LED	Ergonomics	
Touchscreen *	✗	VESA mounting *	✓
Display brightness (typical)	300 cd/m ²	Panel mounting interface	100 x 100 mm
Response time	1 ms	Wall mountable	✓
Anti-glare screen	✓	Cable lock slot *	✓
Screen shape *	Curved	Cable lock slot type	Kensington
Screen curvature rating	1500R	Height adjustment *	✓
Contrast ratio (typical) *	3000:1	Height adjustment	13 cm
Contrast ratio (dynamic)	20000000:1	Pivot	✗
Maximum refresh rate *	100 Hz	Swivelling	✓
Viewing angle, horizontal	178°	Tilt adjustment	✓
Viewing angle, vertical	178°	Tilt angle range	3 - 21°
Display number of colours *	16.7 million colours	Picture-in-Picture	✓
Pixel pitch	0.23175 x 0.23175 mm	On Screen Display (OSD)	✓
Pixel density	109.7 ppi	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Croatian, Czech, German, Dutch, English, Spanish, Finnish, French, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Display diagonal (metric)	86.4 cm	Number of OSD languages	19
Surface hardness	6H	LED indicators	✓
sRGB coverage (typical)	116%		
NTSC coverage (typical)	101%		
Adobe RGB coverage	100%		
Performance			
NVIDIA G-SYNC *	✗		
AMD FreeSync *	✓		

Performance		Power	
AMD FreeSync type	FreeSync	Energy efficiency class (SDR) *	G
Fast charging	✓	Energy efficiency class (HDR) *	G
Flicker-free technology	✓	Energy consumption (SDR) per 1000 hours *	34 kWh
Low Blue Light technology	✓	Energy consumption (HDR) per 1000 hours *	35 kWh
Brand-specific features	False	Power consumption (typical) *	60 W
Multimedia		Power consumption (standby) *	0.5 W
Built-in speaker(s) *	✓	Power consumption (off)	0.3 W
Built-in camera *	✗	AC input voltage	100 - 240 V
Number of speakers	2	AC input frequency	50 - 60 Hz
RMS rated power	10 W	Power supply type	Internal
Built-in microphone	✗	Energy efficiency scale	A to G
Design		Packaging content	
Market positioning *	Home	Stand included	✓
Product colour *	Black	Cables included	AC
Frameless design	✓	HDMI cable length	1.5 m
Front bezel colour	Black	Weight & dimensions	
Detachable stand	✓	Width (with stand)	808.1 mm
Feet colour	Black	Depth (with stand)	250 mm
Ports & interfaces		Height (with stand)	527.3 mm
Built-in USB hub *	✓	Weight (with stand)	9.34 kg
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Width (without stand)	808.1 mm
USB upstream port type	USB Type-C	Depth (without stand)	99.9 mm
Number of upstream ports	1	Height (without stand)	365.3 mm
Number of USB Type-C upstream ports quantity	1	Packaging data	
USB Type-A downstream ports quantity	4	Package width	189 mm
USB Type-C DisplayPort Alternate Mode	✓	Package depth	1071 mm
USB Power Delivery	✓	Package height	500 mm
USB Power Delivery up to	65 W	Package weight	11.8 kg
DVI port	✗	Package type	Box
HDMI *	✓	USB cable length	1.8 m
HDMI ports quantity	1	Other features	
HDMI version	2.0	DCI-P3 coverage	93%
DisplayPorts quantity	1	Picture-by-Picture (PbP)	✓
DisplayPort version	1.2	Exterior finish type	Matt
Headphone out *	✓	Mean time between failures (MTBF)	50000 h
		Light effects	✗



4038986110198

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 13-MAY-2024. Prints or copies of Information are only valid on the printed Publication date