/ISUS

ASUS ProArt OLED PA32DC computer monitor 80 cm (31.5") 3840 x 2160 pixels 4K Ultra HD Black

Brand : ASUS

Product family: ProArt OLED

Product code: 90LM06N0-B01I70

Product name : PA32DC

- 31.5-inch 4K (3840 x 2160) HDR OLED panel with RGB stripes and 99% DCI-P3 color gamut

- Built-in colorimeter and ASUS Auto Calibration complement ASUS ProArt Calibration software as well as Calman and Light Illusion ColourSpace CMS professional hardware calibration software

- True 10-bit color depth and 1,000,000:1 contrast ratio provide the deepest blacks and accurate highlights

- Supports multiple HDR formats, including HDR10 and HLG

- Includes two versatile stand options to suit any scenario or setup, along with an elegant metal handle for portability

- Monitor hood helps reduce reflections, and bundled clips allow for easy cable management

ProArt Display OLED PA32DC Professional Monitor – 31.5-inch, OLED, 4K UHD (3840 x 2160), 99% DCI-P3, Built-in Motorized Colorimeter, Auto Calibration, HDR-10, HLG, $\Delta E < 1$, USB-C, HDMI, Hardware Calibration, Calman Ready, ColourSpace Integration







Display diagonal *80 cm (31.5")HDMI *Display resolution *3840 x 2160 pixelsHDMI ports quantity3HD type *4K Ultra HDHDMI version2.0Native aspect ratio *16:9DisplayPorts quantity1Display technology *0LEDDisplayPort version1.4Panel type *0LEDHeadphone out *Touchscreen *XPC Audio inDisplay brightness (peak)500 cd/m²HDCP	
Display brightness (typical)250 cd/m²HDCP version2.2Response time0.1 msErgonomicsImsImsDisplay surfaceMattVESA mounting *Ims	
Anti-glare screenImage: Contrast ratioScreen shape *FlatPanel mounting interface100 x 100 mmContrast ratio (typical) *1000000:1Cable lock slot *Image: Cable lock slot ypeKensingtonMaximum refresh rate *60 HzCable lock slot typeKensingtonViewing angle, horizontal178°Height adjustment *Image: Cable lock slot ypeViewing angle, vertical178°Height adjustment *Image: Cable lock slot ypeDisplay number of colours *1.073 billion coloursPivotImage: Cable lock slot ypePixel pitch0.182 x 0.182 mmSwivel angle-90 - 90°Viewable size, horizontal69.8 cmSwivel angle range-30 - 30°Viewable size, vertical39.3 cmTilt adjustmentImage: Cable ca	
High Dynamic Range (HDR) Power supported Energy efficiency class (SDR) * G	
High Dynamic Range (HDR) technologyDolby Vision, High Dynamic Range 10 (HDR10), Hybrid Log-Gamma (HLG)Energy efficiency class (HDR) * Energy consumption (SDR) per 1000 hours *GColour depth10 bitEnergy consumption (MDR) per 1000 hours *46 kWhRGB colour spaceDCI-P3100 hours *75 kWh	

Display		Power	
Colour gamut Adobe RGB coverage	99% 99%	Power consumption (typical) * Power consumption (PowerSave)	38 W 0.5 W
Performance		AC input voltage	100 - 240 V
NVIDIA G-SYNC * AMD FreeSync *	× ×	AC input frequency Energy efficiency scale	50 - 60 Hz A to G
Flicker-free technology	1	Packaging content	
Low Blue Light technology	√	Stand included	✓
Multimedia		Cables included	AC, DisplayPort, HDMI, USB Type-C, USB Type-C to USB Type-A
Built-in speaker(s) * Built-in camera *	×	Sun hood included Quick start guide	4
Number of speakers	2 6 W	Weight & dimensions	
RMS rated power Design	6 W	Width (with stand) Depth (with stand)	735.4 mm 245 mm
Market positioning *	Graphics design	Height (with stand)	626.9 mm
Product colour *	Black	Weight (with stand)	12.1 kg
Detachable stand	1	Width (without stand)	735.4 mm
Feet colour	Black	Depth (without stand)	54.4 mm
Certification	Energy Star TÜV Flicker-free TÜV Low Blue Light VESA DisplayHDR 400 True Black Calman Ready	Height (without stand) Weight (without stand)	466.9 mm 7.6 kg
Ports & interfaces		Packaging data	
Built-in USB hub * ✓ USB hub version 3.2 Gen 2 (3.1 Gen 2) USB upstream port type USB Type-C Number of upstream ports 1 Number of USB Type-C upstream ports quantity 1	Package width Package depth Package height Package weight Package type	878 mm 298 mm 616 mm 19.9 kg Box	
USB Type-A downstream ports	4	Sustainability	
quantity USB Power Delivery USB Power Delivery up to	4 ✓ 65 W	European Product Registry for Energy Labelling (EPREL) code	1115602





4711081560883

0195553560931



195553560931

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.