Viewsonic IFP7532-2 interactive whiteboard 190.5 cm (75") 3840 x 2160 pixels Touchscreen HDMI

Brand : Viewsonic

Product name : IFP7532-2

Product code: IFP7532-2

- All-in-one myViewBoard™ suite with Whiteboard, Display, and Manager
- Pen-on-paper writing experience with Ultra Fine Touch Technology
- Front-facing dual speakers to deliver attention-grabbing sound
- Webcam bracket easily attached with camera for better engagement
- Quad Core CPU with upgraded storage powered by Android 9.0 OS
75" TFT LCD, Touch, DLED, UHD, 16:9, 1.07B, 350 cd/m², 4000:1, 8.5 ms, 178/178, 10W x2, RJ45, HDMI, VGA, RS232, USB, 100-240 VAC, VESA, 51.8 kg
Viewsonic IFP7532-2. Display diagonal: 190.5 cm (75"), Working area: 1650.24 x 928.26 mm, Display brightness: 350 cd/m². Operating system installed: Android 9, Processor architecture: ARM Cortex-A55, Maximum internal memory: 32 GB. Speaker power: 20 W. Ethernet LAN data rates: 10,100 Mbit/s. Interface: HDMI, USB connector type: USB Type-A, USB Type-B

Display

Display diagonal *	190.5 cm (75")
Display brightness	350 cd/m²
Display number of colours	1.07 billion colours
Display resolution	3840 x 2160 pixels
Anti-glare screen	✔
HD type	4K Ultra HD
Panel type	LCD
LED backlighting type	Direct-LED
Native aspect ratio	16:9
Contrast ratio (typical)	4000:1
Response time	8.5 ms
Touchscreen *	✔
Touch technology	Multi-touch
Number of simultaneous touchpoints	20
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Working area *	1650.24 x 928.26 mm
Hardness	9H
Technology	Ultrasonic

Computer system

Operating system installed	Android 9
Built-in processor	✔
Processor architecture	ARM Cortex-A55
Processor cores	4
Maximum internal memory	32 GB
RAM capacity	4 GB
RAM type	DDR4

Audio

Built-in speaker(s) *	✔
Number of built-in speakers	2
Speaker power	20 W

Projector

Built-in projector *	✘

Network

Ethernet LAN	✔
Ethernet LAN data rates	10,100 Mbit/s

Ports & interfaces

USB 2.0 Type-B Touch ports quantity	1
HDMI ports quantity	2
HDMI version	2.0
Ethernet LAN (RJ-45) ports	1
VGA (D-Sub) ports quantity	1
OPS slot	1
S/PDIF out port	✔
Audio output	1
RS-232 ports	1

Ergonomics

Panel mounting interface	800 x 400 mm
Mean time between failures (MTBF)	30000 h
Certification	EMC/CE , CB/LVD, GOST-R / EAC, FAC, RCM, BIS, ECAS, LBL (Low Blue Light Certification), RoHS, REACH, SCIP, WEEE, TPCH, Packing waste, CA65, Green BOM, ErP-Eco

Power

Power consumption (typical)	238 W
Power consumption (off)	0.5 W
AC input voltage	162 - 264 V
Battery type	AAA

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 90%

Weight & dimensions

Width *	1710 mm
Depth	87 mm
Height *	1020 mm
Weight	51.8 kg

Packaging data

Package width	1860 mm
Package depth	280 mm
Package height	1140 mm
Package weight	65.7 kg

Ports & interfaces		Packaging content	
Interface	HDMI	Cables included	AC, HDMI, USB
USB 2.0 ports quantity	5	Remote control included	✔
USB connector type	USB Type-A, USB Type-B	Mounting kit	✔
USB 2.0 Type-A hub ports quantity	4	Batteries included	✔
		Quick start guide	✔
		Stylus included	✔

0766907018936

766907018936

Publication date: 13-MAY-2024. Prints or copies of Information are only valid on the printed Publication date