




QNAP TVS-h674 NAS Tower Ethernet LAN Black i5-12400

Brand : QNAP

Product code: TVS-H674-I5-16G/24TB IW

Product name : TVS-h674

- Enable NVMe SSD caching or Edge TPU empowered AI image recognition
 - 2.5GbE ports provide higher transmission speeds with existing Cat 5e cables
 - PCIe slots allow for installing 2.5/5/10/25GbE adapters, QM2 cards, or entry-level graphics cards to increase application performance
 - Host multiple virtual machines and containers with optimized resource utilization
 - Directly view creative works on an HDMI display. Enjoy smooth full HD media playback and real-time transcoding
 - The built-in Intel® OpenVINO™ and Intel® UHD Graphics help boost AI image recognition and offload CPU workloads
- 24TB (Seagate IronWolf), Intel Core i5-12400 (2.5/4.4GHz), 16GB DDR4, 2.5 Gigabit LAN



| Storage | | Performance | |
|--------------------------------------|---|--------------------------------------|--|
| Storage drive interface * | Serial ATA | Type * | NAS |
| Supported storage drive interfaces | M.2, Serial ATA | Device class * | Small & Medium Business |
| Number of M.2 (M & B) slots | 2 | Backup function * | ✓ |
| RAID support * | ✓ | Backup features | Cloud, USB drive, iSCSI LUN |
| RAID levels | 0, 1, 5, 6, 10, 50, 60 | Buzzer | ✓ |
| Online RAID migration | ✓ | Snapshot | ✓ |
| Online RAID expansion | ✓ | Management protocols | SNMP |
| RAID rebuild | ✓ | Share folder access right management | ✓ |
| Hot-swap drive bays | ✓ | Security algorithms | FIPS 140-2, HTTPS, SNMPv2, SNMPv3, SSH |
| Supported file systems | FAT32, HFS+, NTFS, ZFS, exFAT, ext3, ext4 | Access Control List (ACL) | ✓ |
| Storage drives installed * | ✓ | Reset button | ✓ |
| Total installed storage capacity * | 24 TB | On/off switch | ✓ |
| Number of storage drives supported * | 6 | Built-in FTP server | ✓ |
| Installed storage drive type * | HDD | Browser supported | Apple Safari, Google Chrome, Microsoft Edge, Mozilla Firefox |
| Supported storage drive types * | HDD & SSD | System log | ✓ |
| Disk roaming | ✓ | Hot spare | ✓ |
| Processor | | S.M.A.R.T. support | ✓ |
| Processor manufacturer * | Intel | Backup button | ✓ |
| Processor generation | 12th gen Intel® Core™ i5 | USB copy function | ✓ |
| Processor family * | Intel® Core™ i5 | Software | |
| Processor model * | i5-12400 | Operating system installed * | QuTS hero |
| Processor frequency * | 2.5 GHz | Operating system version | h5.0.1 |
| Processor boost frequency | 4.4 GHz | | |
| Processor cores | 6 | | |
| Processor threads | 12 | | |
| Bus type | DMI4 | | |
| CPU configuration (max) | 1 | | |
| Number of processors supported | 1 | | |
| On-board graphics card model | Intel UHD Graphics 730 | | |
| Memory | | | |
| Internal memory type | DDR4 | | |
| Maximum RAM supported | 64 GB | | |
| Memory slots | 2x SODIMM | | |
| Internal memory * | 16 GB | | |

| Memory | | Software | |
|---|-------------------------|---|--|
| Memory form factor | SO-DIMM | | Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64 |
| Flash memory | 5120 MB | | |
| Network | | | |
| Ethernet LAN * | ✓ | | |
| Ethernet LAN data rates | 10,100,1000,2500 Mbit/s | | |
| DHCP server | ✓ | | |
| Jumbo frames support | ✓ | | |
| iSCSI support | ✓ | | |
| Wake-on-LAN ready | ✓ | | |
| Ports & interfaces | | | |
| USB port * | ✓ | | |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity | 2 | | |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity | 1 | | |
| HDMI ports quantity | 1 | | |
| HDMI version | 1.4b | | |
| Ethernet LAN (RJ-45) ports * | 2 | Linux operating systems supported | Ubuntu 14.04 |
| Design | | | |
| Chassis type * | Tower | Mac operating systems supported | Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina |
| Cooling type * | Active | | |
| Product colour | Black | | |
| Number of fans | 3 fan(s) | | |
| Fan diameter | 9.2 cm | Server operating systems supported | Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 |
| Fan diameter 2 | 6 cm | | |
| Drive bay locking | ✓ | Other operating systems supported | Solaris 10 |
| LED indicators | HDD, LAN, Status, USB | | |
| Built-in display | ✓ | | |
| Display type | LCD | | |
| Cable lock slot | ✓ | | |
| Cable lock slot type | Kensington | | |
| | | Power | |
| | | Power supply location | Built-in |
| | | Power supply unit (PSU) capacity | 250 W |
| | | Number of power supply units | 1 |
| | | Power consumption (typical) | 79.363 W |
| | | Power consumption (sleep) | 39.911 W |
| | | AC input voltage | 100 - 240 V |
| | | Fan voltage | 12 V |
| | | Weight & dimensions | |
| | | Width * | 264.3 mm |
| | | Depth * | 280.8 mm |
| | | Height * | 188 mm |
| | | Weight | 6.32 kg |
| | | Package weight | 7.89 kg |
| | | Packaging content | |
| | | Cables included | AC, LAN (RJ-45) |
| | | Number of screws | 42 |
| | | Drive tray key included | ✓ |
| | | Processor special features | |
| | | Embedded options available | ✗ |
| | | Enhanced Intel SpeedStep Technology | ✓ |
| | | Execute Disable Bit | ✓ |
| | | Idle States | ✓ |
| | | Intel 64 | ✓ |
| | | Intel Virtualization Technology (VT-x) | ✓ |
| | | Intel Virtualization Technology for Directed I/O (VT-d) | ✓ |
| | | Intel VT-x with Extended Page Tables (EPT) | ✓ |

Operational conditions

| | |
|-----------------------------------|-----------|
| Operating temperature (T-T) | 0 - 40 °C |
| Operating relative humidity (H-H) | -20 - 70% |
| Storage temperature (T-T) | 5 - 95 °C |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 13-MAY-2024. Prints or copies of Information are only valid on the printed Publication date