



## APC Smart-UPS X 2200VA uninterruptible power supply (UPS) Line-Interactive 2.2 kVA 1980 W 10 AC outlet(s)

Brand : APC

Product code: SMX2200HVNC

Product name : Smart-UPS X 2200VA

230 V, 1.98 KW / 2.2 kVA, 50/60 Hz, RJ-45, SmartSlot, USB, 178 x 483 x 432 mm, 38.56 kg  
 APC Smart-UPS X 2200VA. UPS topology: Line-Interactive, Output power capacity: 2.2 kVA, Output power: 1980 W. AC outlet types: C13 coupler, C19 coupler, C20 coupler, Power plug: C20 coupler, AC outlets quantity: 10 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 702 Ah, Battery recharge time: 3 h. Form factor: Rackmount/Tower, Product colour: Black, Rack capacity: 2U. Width: 178 mm, Depth: 483 mm, Height: 432 mm




Features		Design	
UPS topology *	Line-Interactive	Form factor *	Rackmount/Tower
Output power capacity *	2.2 kVA	Rack capacity	2U
Output power *	1980 W	Cable length	2 m
Waveform *	Sine	Product colour *	Black
Input operation voltage (min) *	140 V	Display type	LED
Input operation voltage (max) *	280 V	LED indicators	✓
Input frequency *	50/60 Hz	Certification	CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE
Output operation voltage (min)	208 V	<b>Operational conditions</b>	
Output operation voltage (max)	240 V	Operating temperature (T-T)	0 - 40 °C
Output frequency	50/60 Hz	Storage temperature (T-T)	-15 - 45 °C
Output frequency regulation	+/- 3 Hz	Operating relative humidity (H-H)	0 - 95%
Output voltage regulation	5%	Storage relative humidity (H-H)	0 - 95%
Response time	10 ms	Operating altitude	0 - 3000 m
Emergency Power Off (EPO)	✓	Non-operating altitude	0 - 15000 m
EMI/RFI noise filtering	✓	<b>Technical details</b>	
Noise level	55 dB	Sustainability certificates	RoHS
Surge protection	✓	<b>Weight &amp; dimensions</b>	
Audible alarm(s)	✓	Width	178 mm
Web-based management	✓	Depth	483 mm
Audible alarm modes	Battery replacement	Height	432 mm
Auto-restart	✓	Weight	38.6 kg
<b>Ports &amp; interfaces</b>		Package width	586 mm
AC outlet types	C13 coupler, C19 coupler, C20 coupler	Package depth	633 mm
Power plug	C20 coupler	Package height	330 mm
AC outlets quantity	10 AC outlet(s)	Package weight	47.6 kg
USB 2.0 ports quantity	1	<b>Packaging data</b>	
Ethernet LAN (RJ-45) ports	1	Rack mount kit	✓
<b>Battery</b>		Cables included	Input power cable, USB cable
Battery technology	Sealed Lead Acid (VRLA)	Quick installation guide	✓
Battery capacity	702 Ah		

Battery		Packaging data	
Battery recharge time	3 h	Resource CD	✓
Hot-swap battery	✓	<b>Logistics data</b>	
Automatic battery test	✓	Products per pallet	6 pc(s)
Cold start	✓	Harmonized System (HS) code	85078000
		Other features	
		Output voltage	230 V



0731304327158



731304327158

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 13-MAY-2024. Prints or copies of Information are only valid on the printed Publication date