

Manhattan USB-C Dock/Hub, Ports (x3): HDMI, USB-A and USB-C, 5 Gbps (USB 3.2 Gen1 aka USB 3.0), With Power Delivery (60W) to USB-C Port (Note additional USB-C wall charger and USB-C cable needed), Equivalent to CDP2HDUACP, Black, 3 Year Warranty, Blister



Brand: Manhattan Product code: 152037

Product name : USB-C Dock/Hub, Ports (x3): HDMI, USB-A and USB-C, 5 Gbps (USB 3.2 Gen1 aka USB 3.0), With Power Delivery (60W) to USB-C Port (Note additional USB-C wall charger and USB-C cable needed), Equivalent to CDP2HDUACP, Black, 3 Year Warranty, Blister

USB-C Hub/Dock/Converter, USB-C to HDMI, USB-C (including Power Delivery) and USB-A Ports, 5Gbps (USB 3.2 Gen 1), HDMI 4K video: 1080p@60Hz or 3840x2160p@30Hz, Male to Females, Cable 8cm, Black, Bilster

Manhattan USB-C Dock/Hub, Ports (x3): HDMI, USB-A and USB-C, 5 Gbps (USB 3.2 Gen1 aka USB 3.0), With Power Delivery (60W) to USB-C Port (Note additional USB-C wall charger and USB-C cable needed), Equivalent to CDP2HDUACP, Black, 3 Year Warranty, Blister. USB connector type: USB Type-A, USB Type-C. Product colour: Black, Housing material: Acrylonitrile butadiene styrene (ABS), Certification: HDCP 1.4 CE FCC RoHS2 WEEE. Maximum resolution: 3840 x 2160 pixels. Sustainability certificates: RoHS. Width: 43 mm, Depth: 45 mm, Height: 14.5 mm





| Ports & interfaces | | Software | |
|---|---------------------------------------|-----------------------------------|-------------|
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * | 1 | Mac operating systems supported | ✓ |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-C | - | Operational conditions | |
| ports quantity | 1 | Operating temperature (T-T) | 0 - 40 °C |
| USB connector type | USB Type-A, USB Type-C | Storage temperature (T-T) | -20 - 60 °C |
| HDCP | ✓ | Operating relative humidity (H-H) | 5 - 90% |
| Performance | | Sustainability | |
| Product colour * | Black | Sustainability certificates | RoHS |
| Housing material | Acrylonitrile butadiene styrene (ABS) | Weight & dimensions | |
| Certification | HDCP 1.4 CE FCC RoHS2 WEEE | Width | 43 mm |
| Graphics | | Depth | 45 mm |
| Maximum resolution | 3840 x 2160 pixels | Height | 14.5 mm |
| | 3040 X 2100 pixeis | Weight | 30 g |
| Software | | Packaging content | |
| Windows operating systems supported | ✓ | Manual | 1 |
| Mac compatibility | ✓ | Logistics data | |
| | | Harmonized System (HS) code | 84733020 |





766623152037

0766623152037

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.