Viewsonic PA503X data projector Standard throw projector 3600 ANSI lumens DLP XGA (1024x768) Grey, White

Brand : Viewsonic **Product code:** PA503X

Product name : PA503X

 $1024 \times 768, \, DLP, \, 3600 \, ANSI \, lum, \, 30\text{-}300", \, 190 \, W, \, 4\text{:}3, \, Mini \, USB \, B, \, RS\text{-}232, \, RCA, \, 3.5mm, \, HDMI \, 1.4, \, VGA, \, 2x \, RGB, \, 2 \, W \, RMS, \, 294x218x110 \, \, mm$

Viewsonic PA503X. Projector brightness: 3600 ANSI lumens, Projection technology: DLP, Projector native resolution: XGA (1024x768). Light source type: Lamp, Service life of light source: 4500 h, Service life of light source (economic mode): 15000 h. Focus: Manual, Zoom type: Manual, Optical zoom: 1.1x. Analog signal format system: NTSC, PAL, PAL 60, SECAM, Supported graphics resolutions: 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA),..., Supported video modes: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p. Serial interface type: RS-232, HDMI connector type: Full-size





| Projector | | Network | |
|---|--|-----------------------------------|--------------------------|
| Screen size compatibility * | 762 - 7620 mm (30 - 300") | Ethernet LAN * | × |
| Projection distance | 1.1 - 13 m | Wi-Fi * | × |
| Contrast ratio (dynamic) | 22000:1 | Storage | |
| Projector brightness * | 3600 ANSI lumens | Card reader integrated * | × |
| Projection technology * | DLP XGA (1024x768) 4:3 1.073 billion colours 15 - 102 kHz | Features | |
| Projector native resolution * Native aspect ratio * Number of colours | | Certification | FCC (ICES-003), cTUVus |
| | | | ree (iees-005), erovus |
| Horizontal scan range | | Multimedia | |
| Vertical scan range | 23 - 120 Hz | Built-in speaker(s) * | ✓ |
| Keystone correction, vertical | -40 - 40° | RMS rated power | 2 W |
| Matrix size | 1.4 cm (0.55") | Number of built-in speakers | 1 |
| Matrix type | DMD | Design | |
| Light source | | Product type * | Standard throw projector |
| Light source type * | Lamp | Product colour * | Grey, White |
| Service life of light source * | 4500 h | Placement | Desktop |
| Service life of light source | 4300 11 | Cable lock slot | ✓ |
| (economic mode) | 15000 h | Cable lock slot type | Kensington |
| Lamp power | 190 W | Display | |
| Lamps quantity | 1 lamp(s) | Built-in display * | × |
| Lens system | | Power | |
| Focus * | Manual | Power source * | AC |
| Zoom capability | ✓ | Power consumption (typical) * | 260 W |
| Zoom type | Manual | Power consumption (standby) * | 0.5 W |
| Optical zoom | 1.1x | AC input voltage | 100 - 240 V |
| Throw ratio | 1.96 - 2.15:1 | AC input frequency | 50 - 60 Hz |
| Video | | Operational conditions | |
| Analog signal format system * | NTSC, PAL, PAL 60, SECAM | Operating temperature (T-T) | 0 - 40 °C |
| 3D Ready | , | | |
| 55 | 640 x 480 (VGA), 720 x 480, 720 x | Operating relative humidity (H-H) | 10 - 90% |
| | 576, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 800 (WXGA), 1360 x 768 (WXGA), 1366 x 768, 1400 x 1050 (SXGA+), 1440 x 900 (WXGA+), 1920 x 1200 (WUXGA) | Operating altitude | 0 - 1499 m |
| Supported graphics resolutions | | Weight & dimensions | |
| | | Width | 294 mm |
| | | Depth | 218 mm |
| | | Height | 110 mm |
| Supported video modes | 480i, 480p, 576i, 576p, 720p, 1080i, | Weight * | 2.2 kg |
| | 1080p | Package width | 365 mm |
| Ports & interfaces | | Package depth | 188 mm |
| HDMI connector type | Full-size | Package height | 300 mm |

| Ports & interfaces | | Weight & dimensions | |
|---|-----------------|---|--------------|
| HDMI version | 1.4 | Package weight | 6.24 kg |
| Serial interface type * | RS-232 ✓ ✓ 3 | Packaging content | |
| PC Audio in PC Audio out VGA (D-Sub) ports quantity * | | Remote control included * Cables included Ouick start guide | ✓ AC, VGA |
| HDMI ports quantity * Composite video in * | 1 1 | Logistics data | , |
| DVI port * AC (power) in | X | Harmonized System (HS) code Other features | 85286200 |
| | | RS-232 ports | 1 |





766907905113

0766907905113

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.