



HP E24d G4 FHD USB-C Docking Monitor

Brand : HP

Product code: 6PA50A4

Product name : E24d G4 FHD USB-C Docking Monitor

E24d G4 FHD USB-C Docking Monitor

[HP E24d G4 FHD USB-C Docking Monitor:](#)

Create the perfect productivity hub

Inspire joy on your desk with the clean connectivity of the HP E24d G4 FHD USB-C Docking Monitor. Add your everyday accessories at the display, then add your PC with just one USB-C^[1] cable. Empower IT to remotely manage HP devices from anywhere on the network through RJ-45.^[2,3]

HP E24d G4 FHD USB-C Docking Monitor. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Response time: 5 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black



Display		Ergonomics	
Display diagonal *	60.5 cm (23.8")	Panel mounting interface	100 x 100 mm
Display resolution *	1920 x 1080 pixels	Cable lock slot *	✗
HD type *	Full HD	Height adjustment *	✓
Native aspect ratio *	16:9	Height adjustment	15 cm
Panel type *	IPS	Pivot	✓
Touchscreen *	✗	Swivelling	✓
Display brightness (typical)	250 cd/m ²	Swivel angle range	0 - 30°
Response time	5 ms	Tilt angle range	-5 - 20°
Screen shape *	Flat	On Screen Display (OSD)	✓
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 768 (WXGA), 1280 x 800 (WXGA), 1440 x 900, 1600 x 900, 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080)	Plug and Play	✓
		Power	
Contrast ratio (typical) *	1000:1	Energy efficiency class (SDR) *	E
Contrast ratio (dynamic)	5000000:1	Energy efficiency class (HDR) *	Not available
Maximum refresh rate *	60 Hz	Energy consumption (SDR) per 1000 hours *	18 kWh
Viewing angle, horizontal	178°	Power consumption (typical) *	70 W
Viewing angle, vertical	178°	Power consumption (standby) *	0.5 W
Pixel pitch	0.274 x 0.274 mm	Power consumption (max)	175 W
Digital horizontal frequency	30 - 80 kHz	AC input voltage	100 - 240 V
Digital vertical frequency	50 - 60 Hz	Operational conditions	
RGB colour space	NTSC	Operating temperature (T-T)	5 - 35 °C
Colour gamut	72%	Operating relative humidity (H-H)	20 - 80%
Performance		Packaging content	
HP segment	Business	Cables included	DisplayPort, HDMI, USB Type-C
Multimedia		Weight & dimensions	
Built-in camera *	✓	Width (with stand)	539.4 mm
Built-in microphone	✓	Depth (with stand)	206.8 mm
Design		Height (with stand)	486.4 mm
Market positioning *	Business	Weight (with stand)	6.86 kg
Product colour *	Black	Width (without stand)	539.4 mm
Country of origin	China	Depth (without stand)	48.5 mm
		Height (without stand)	323.3 mm
		Packaging data	
		Package width	646 mm

Ports & interfaces		Packaging data	
Built-in USB hub *	✓	Package depth	269 mm
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Package height	438 mm
USB upstream port type	USB Type-C	Package weight	11 kg
Number of upstream ports	1	Sustainability	
Number of USB Type-C upstream ports quantity	1	Sustainable technologies and materials	Arsenic-free display glass; Low halogen; Mercury-free display backlights
USB Type-A downstream ports quantity	4	European Product Registry for Energy Labelling (EPREL) code	298044
USB Type-C downstream ports quantity	1	Logistics data	
USB Type-C DisplayPort Alternate Mode	✓	Harmonized System (HS) code	85285210
USB Power Delivery	✓	Brand-specific features	
USB Power Delivery up to	100 W	HP GTIN (EAN/UPC)	195697978920
HDMI *	✓	Other features	
HDMI ports quantity	1	Weight	6.86 kg
HDMI version	1.4	Height	323.3 mm
DisplayPorts quantity	1	Width	539.4 mm
DisplayPort version	1.2	Depth	48.5 mm
Headphone out *	✓		
Ergonomics			
VESA mounting *	✓		



0195697978883



195697978883



0195697978838



195697978838



0195697978845



195697978845



0195697978852



195697978852



0195697978869



195697978869




0195697978876



195697978876



0195697978906



195697978906




0195697978913



195697978913



0195697978920



195697978920



0195697978937



195697978937



0195697978944



195697978944



0195697978951



195697978951



0195697978968



195697978968




0195697978975



195697978975



0195697978982



195697978982



0195697978999



195697978999



0195697979002



195697979002



0195697978821



195697978821



4573595618128



0195697978890



195697978890

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.