

Philips S Line 272S1MH/00 LED display 68.6 cm (27") 1920 x 1080 pixels Full HD Black

Brand : Philips

Product family: S Line

Product code: 272S1MH/00

Product name : 272S1MH/00

Business Monitor 272S1MH LCD monitor with Windows Hello Webcam

Philips S Line 272S1MH/00 LED display 68.6 cm (27") 1920 x 1080 pixels Full HD Black:

The Philips S Line monitor provides features that guarantee comfortable working and daily productivity. 3 sided frameless bezel with crisp FHD gives a clearer and wider view. Pop-up webcam with Windows Hello delivers performance and convenience.

Philips S Line 272S1MH/00. Display diagonal: 68.6 cm (27"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LED, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black



| Display | | Ergonomics | |
|---------------------------------------|-----------------------|---|---|
| Display diagonal * | 68.6 cm (27") | Cable lock slot type | Kensington |
| Display resolution * | 1920 x 1080 pixels | Height adjustment * | ✓ |
| HD type * | Full HD | Height adjustment | 13 cm |
| Native aspect ratio * | 16:9 | Pivot | ✓ |
| Display technology * | LED | Pivot angle | -90 - 90° |
| Panel type * | IPS | Swivelling | ✓ |
| Backlight type | W-LED | Swivel angle range | -180 - 180° |
| Touchscreen * | ✗ | Tilt adjustment | ✓ |
| Display brightness (typical) | 300 cd/m ² | Tilt angle range | -5 - 25° |
| Response time | 4 ms | On Screen Display (OSD) | ✓ |
| Anti-glare screen | ✓ | On Screen Display (OSD) languages | Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian |
| Screen shape * | Flat | Number of OSD languages | 21 |
| Aspect ratio | 16:9 | Plug and Play | ✓ |
| Contrast ratio (typical) * | 1000:1 | LED indicators | Operation, Stand-by |
| Contrast ratio (dynamic) | 50000000:1 | | |
| Dynamic contrast ratio marketing name | SmartContrast | | |
| Maximum refresh rate * | 75 Hz | | |
| Viewing angle, horizontal | 178° | | |
| Viewing angle, vertical | 178° | | |
| Display number of colours * | 16.7 million colours | | |
| Pixel pitch | 0.3114 x 0.3114 mm | | |
| Pixel density | 82 ppi | | |
| Horizontal scan range | 30 - 85 kHz | | |
| Vertical scan range | 48 - 75 Hz | | |
| Viewable size, horizontal | 59.8 cm | | |
| Viewable size, vertical | 33.6 cm | | |
| Display diagonal (metric) | 68.6 cm | | |
| DDC/CI | ✓ | | |
| Haze rate | 25% | | |
| | | Power | |
| | | Energy efficiency class (SDR) * | E |
| | | Energy consumption (SDR) per 1000 hours * | 21 kWh |
| | | Power consumption (typical) * | 16.23 W |
| | | Power consumption (standby) * | 0.3 W |
| | | Power consumption (off) | 0.3 W |
| | | Power consumption (PowerSave) | 11.6 W |
| | | AC input voltage | 100 - 240 V |
| | | AC input frequency | 50 - 60 Hz |
| | | Power supply type | Internal |

| | | | |
|--------------------------------------|---|---|--|
| Display | | Operational conditions | |
| Surface hardness | 3H | Operating temperature (T-T) | 0 - 40 °C |
| sRGB coverage (typical) | 102% | Storage temperature (T-T) | -20 - 60 °C |
| NTSC coverage (typical) | 81% | Operating relative humidity (H-H) | 20 - 80% |
| Display sRGB | ✓ | Operating altitude | 0 - 3658 m |
| Performance | | Non-operating altitude | 0 - 12192 m |
| NVIDIA G-SYNC * | ✗ | Packaging content | |
| AMD FreeSync * | ✗ | Stand included | ✓ |
| Fast charging | ✓ | Cables included | VGA, HDMI, DisplayPort, USB Type-A to USB Type-B, Audio (3.5mm), AC |
| VESA Adaptive Sync support | ✓ | Quick start guide | ✓ |
| Component video sync | Separate sync, Sync-on-green (SOG) | Manual | ✓ |
| Flicker-free technology | ✓ | Bundled software | SmartControl |
| Low Blue Light technology | ✓ | Weight & dimensions | |
| Compatible operating systems | Mac OS X, Windows 10 / 8.1 / 8 / 7 | Width (with stand) | 613 mm |
| Multimedia | | Depth (with stand) | 205 mm |
| Built-in speaker(s) * | ✓ | Height (with stand) | 537 mm |
| Built-in camera * | ✓ | Weight (with stand) | 6.22 kg |
| Number of speakers | 2 | Width (without stand) | 613 mm |
| RMS rated power | 2 W | Depth (without stand) | 51 mm |
| Megapixel (approx.) | 2 MP | Height (without stand) | 366 mm |
| Built-in microphone | ✓ | Weight (without stand) | 4.35 kg |
| Design | | Packaging data | |
| Market positioning * | Home | Package width | 700 mm |
| Product colour * | Black | Package depth | 215 mm |
| Front bezel colour | Black | Package height | 456 mm |
| Feet colour | Black | Package weight | 9.62 kg |
| Heavy metals free | Hg (mercury) | Sustainability | |
| Certification | CB, FCC Class B, ICES-003, CE Mark, TUV/GS, TUV Ergo, SEMKO, CU-EAC, EAEU RoHS, TUV Eye Comfort certified | Sustainability certificates | ENERGY STAR, TCO, RoHS |
| Ports & interfaces | | Doesn't contain | PVC/BFR, Mercury |
| Built-in USB hub * | ✓ | European Product Registry for Energy Labelling (EPREL) code | 1187990 |
| USB hub version | 3.2 Gen 1 (3.1 Gen 1) | Recycling data | |
| USB upstream port type | USB Type-B | Post-consumer recycled plastic | 85% |
| USB Type-A downstream ports quantity | 3 | Logistics data | |
| VGA (D-Sub) ports quantity | 1 | Harmonized System (HS) code | 85285210 |
| DVI-D ports quantity | 1 | Other features | |
| HDMI * | ✓ | Exterior finish type | Textured |
| HDMI ports quantity | 1 | Picture enhancement | SmartImage |
| HDMI version | 1.4 | Recyclable packaging material | 100% |
| DisplayPorts quantity | 1.2 | Regulatory Approvals | CB; FCC Class B; ICES-003; CE Mark; TUV/GS; TUV Ergo; CU-EAC; EAEU RoHS; TUV Eye Comfort certified |
| DisplayPort version | 1.2 | EasyRead mode | ✓ |
| Audio output | ✓ | LowBlue mode | ✓ |
| PC Audio in | ✓ | Energy efficiency class (old) | E |
| HDCP | ✓ | Weight | 4.35 kg |
| HDCP version | 1.4 | Height | 366 mm |
| Ergonomics | | Width | 613 mm |
| VESA mounting * | ✓ | Depth | 51 mm |
| Panel mounting interface | 100 x 100 mm | Mean time between failures (MTBF) | 70000 h |
| Cable lock slot * | ✓ | | |



8712581794989

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 13-MAY-2024. Prints or copies of Information are only valid on the printed Publication date