

AXIS M3077-PLVE Network Camera

6 MP outdoor-ready with 360° panoramic view and audio capture

With its 6 MP sensor, AXIS M3077-PLVE offers excellent image quality and a complete 180° or 360° overview, indoors or out, around the clock. It features two built-in microphones allowing for audio surveillance and detection. This compact mini dome offers dewarped views such as panorama, quad, corner, and corridor views directly from the camera. It includes Axis Lightfinder and Axis Forensic WDR for true colors and great details in challenging light or near darkness. And, Axis OptimizedIR for surveillance in pitch darkness.

- > [Complete 180° and 360° overview](#)
- > [Lightfinder, Forensic WDR and Optimized IR](#)
- > [Digital PTZ and dewarped views](#)
- > [Built-in microphones](#)
- > [Enhanced security features](#)



AXIS M3077-PLVE Network Camera

DHCPv4/v6, ARP, SSH, SIP, LLDP, CDP, MQTT v3.1.1, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)

Camera

Image sensor	1/1.8" progressive scan RGB CMOS
Lens	1.56 mm, F2.0 Horizontal field of view: 183° Vertical field of view: 183° Fixed iris, fixed focus, IR corrected
Day and night	Automatically removable infrared-cut filter
Minimum illumination	Color: 0.16 lux at 50 IRE, F2.0 B/W: 0.03 lux at 50 IRE, F2.0 0 lux with IR illumination on
Shutter speed	1/16000 s to 1 s
Camera angle adjustment	Digital roll: ± 180°

System on chip (SoC)

Model	ARTPEC-7
Memory	1024 MB RAM, 512 MB Flash

Video

Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG
Resolution	Overview: 2016x2016 to 160x160 Panorama: 2560x1440 to 192x72 Double Panorama: 2560x1920 to 384x288 Quad view: 2560x1920 to 384x288 View area 1-4: 1920x1440 to 256x144 Corner right/left: 2368x1184 to 384x288 Double corner: 2016x2016 to 384x288 Corridor: 2560x1920 to 256x144
Frame rate	360° overview only, up to 2016x2016 without WDR: 50/60 fps @ 50/60 Hz 360° overview and dewarped views up to max resolution with WDR: up to 25/30 fps @ 50/60 Hz
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Low latency mode
Multi-view streaming	360° overview, dewarped panorama, corridor, corner left/right and quad views. Up to 4 individually cropped out and dewarped view areas. All different views can be streamed simultaneously. When streaming 4 dewarped view areas and one 360° overview in max resolution: up to 19 fps per stream.
Image settings	Compression, color saturation, brightness, sharpness, contrast, local contrast, white balance, day/night threshold, tone mapping, exposure control (including automatic gain control), exposure zones, Forensic WDR: up to 120 dB depending on scene, fine tuning of low-light behavior, dynamic text and image overlay, mirroring, digital roll, polygon privacy masks
Pan/Tilt/Zoom	Digital PTZ of view areas, digital PT of panorama, corner, corridor and quad views, preset positions, guard tours

Audio

Audio streaming	One-way, simplex, mono or stereo.
Audio encoding	LPCM 48 kHz, AAC-LC 8/16/32/44.1/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate
Audio input/output	Built-in microphone (can be disabled) Two-way audio connectivity via the optional AXIS T61 Audio and I/O interfaces with portcast technology

Network

Security	IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, user access log, centralized certificate management, signed video, secure keystore (CC EAL4 certified)
Network protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS ^a , HTTP/2, TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SRTP/RTSPS, TCP, UDP, IGMP, RTCP, ICMP,

System integration

Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com AXIS Guardian with One-Click Connection ONVIF [®] Profile G, ONVIF [®] Profile M, ONVIF [®] Profile S, ONVIF [®] Profile T specification at onvif.org Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX
Onscreen controls	Day/night shift Wide dynamic range Video streaming indicator IR illumination
Event conditions	Analytics, edge storage events, virtual inputs through API, supervised external inputs, open casing, audio detection MQTT subscribe
Event actions	Record video/audio: SD card and network share MQTT publish Upload of images or video/audio clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset, start/stop guard tour Overlay text, external output activation, play audio clip, zoom preset, day/night mode
Built-in installation aids	Pixel counter, digital roll, repositioning of quad views, digital PTZ of view areas, digital PT of panorama, corner, corridor and quad views

Analytics

Applications	Included AXIS Video Motion Detection, AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard, active tampering alarm, audio detection Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap
---------------------	---

Cybersecurity

Edge security	Software: Signed firmware, brute force delay protection, digest authentication, password protection, AES-XTS-Plain64 256bit SD card encryption Hardware: Secure boot, Axis Edge Vault with Axis device ID
Network security	IEEE 802.1X (EAP-TLS) ^a , IEEE 802.1AR, HTTPS/HSTS ^a , TLS v1.2/v1.3 ^a , Network Time Security (NTS), X.509 Certificate PKI, IP address filtering
Documentation	<i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM) To download documents, go to axis.com/support/cybersecurity/resources To read more about Axis cybersecurity support, go to axis.com/cybersecurity

General

Casing	IP66-, NEMA 4X- and IK10-rated Polycarbonate hard coated dome Aluminum Color: white NCS S 1002-B For repainting instructions of skin cover or casing and impact on warranty, contact your Axis partner.
Sustainability	PVC free
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 8.0 W, max 11.9 W
Connectors	Shielded RJ45 10BASE-T/100BASE-TX PoE Terminal block for 1 supervised alarm input and 1 output (12 V DC output, max. load 25 mA)
IR illumination	Optimized IR with power-efficient, long-life 850 nm IR LEDs Range of reach 20 m (66 ft) or more depending on scene

Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Operating conditions	-40 °C to 50 °C (-40 °F to 122 °F) Start-up temperature: -30 °C to 50 °C (-22 °F to 122 °F) Maximum temperature (intermittent): 55 °C (131 °F) Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F) Humidity 10–100% RH (condensing)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Approvals	EMC EN 55032 Class A, EN 55035, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZS CISPR 32 Class A, KC KN32 Class A, KC KN35 Safety IEC/EN/UL 60950-22, IEC/EN/UL 62368-1, IEC/EN 62471, IS 13252 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, 60068-2-78, IEC/EN 60529 IP66, IEC/EN 62262 IK10, IEC 60721-3-5 Class 5M3 (vibration and shock), NEMA 250 Type 4X, NEMA TS 2 (2.2.7-2.2.9) Network

	NIST SP500-267
Dimensions	Height: 66 mm (2.5 in) ø 149 mm (5.8 in)
Weight	700 g (1.5 lb)
Included accessories	Installation guide, Windows® decoder 1-user license, drill hole template, cable gaskets, connector guard, I/O connector, RESISTORX® TR20 bit, mounting bracket, cable hole lid, view protector
Optional accessories	AXIS T94T02D Pendant kit with weathershield AXIS Surveillance Cards AXIS TM3808-E Skin Cover Black AXIS Mounts & Cabinets AXIS T6101 Audio and I/O Interface AXIS T6112 Audio and I/O Interface For more accessories, see axis.com
Video management software	AXIS Device Manager, AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese
Warranty	5-year warranty, see axis.com/warranty

- a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*