


BenQ ST6502S Digital signage flat panel 165.1 cm (65") LED 400 cd/m² 4K Ultra HD Black Built-in processor Android 8.0 18/7

Brand : BenQ Product code: 9H.F88PT.DA2

Product name: ST6502S









Display		Design	
Panel type	ADS Direct-LED	Panel mounting interface	600 x 400 mm
LED backlighting type		Performance	
Display diagonal *	165.1 cm (65")	Purpose *	Universal
Display technology *	LED 3840 x 2160 pixels 400 cd/m ² 4K Ultra HD	Operating hours (hours/days)	18/7
Display resolution *		Power	
Display brightness * HD type *		Power consumption (typical) *	155 W
Touchscreen *	4K UILIA ND	Power consumption (typical) *	0.5 W
Native aspect ratio	16:9	Energy efficiency class (SDR)	G G
Response time	8 ms	Energy consumption (SDR) per 1000	1
Active display area (W x H)	1428.5 x 803.5 mm	hours	['] 155 kWh
Display diagonal (metric)	164 cm	AC input voltage	100-240 V
Panel life	30000 h	AC input frequency	50 - 60 Hz
RGB colour space	NTSC	Computer system	
Ports & interfaces		Computer system *	✓
HDMI ports quantity *	3	Built-in processor *	1
HDMI version	2.0	Internal memory	3 GB
DVI port *	✓	Internal storage capacity	16 GB
DVI-D ports quantity	1	Operating system installed	Android 8.0
VGA (D-Sub) input ports	1	Weight & dimensions	
USB port *	1	Display width	1462.3 mm
USB ports quantity	2	Display depth	68.9 mm
USB version	2.0	Display height	837.3 mm
Ethernet LAN *	✓	Display weight	29 kg
Ethernet LAN (RJ-45) ports	1	Packaging data	
Ethernet LAN data rates	10,100,1000 Mbit/s	Package width	1605 mm
Wi-Fi *		Package depth	220 mm
PC Audio in	✓	Package height	965 mm

Audio		Packaging data	
Built-in speaker(s) *		Package weight	37.4 kg
Number of built-in speakers RMS rated power		Packaging content	
Design		Remote control included Cables included	√ HDMI
Product design *	Digital signage flat panel Indoor Black Flat √	Operational conditions	
Placement supported * Product colour *		Operating temperature (T-T)	0 - 40 °C
Screen shape		Operating relative humidity (H-H)	10 - 80%
VESA mounting *		Storage temperature (T-T)	-20 - 60 °C
		Storage relative humidity (H-H)	10 - 80%



4718755089039

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.