DELL S Series 27 Video Conferencing Monitor - S2722DZ

Brand : DELL

Product family: S Series

Product code: DELL-S2722DZ

Product name : 27 Video Conferencing Monitor - S2722DZ

- 68.6cm (27") Quad HD 2560 x 1440 LED IPS
- 8ms, 16:9, 350cd/m², 1000:1
- HDMI, DisplayPort

68.6cm (27") Quad HD 2560 x 1440 LED IPS, 16:9, 350cd/m², 16.7M, 8ms, 178°/178°, 1000:1

DELL S Series 27 Video Conferencing Monitor - S2722DZ:

An easy-to-use 27″ QHD monitor made to fit your busy lifestyle with a built-in camera, noise-cancelling microphones and dual 5W speakers
DELL S Series 27 Video Conferencing Monitor - S2722DZ. Display diagonal: 68.6 cm (27"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LCD, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). VESA mounting, Height adjustment. Product colour: Silver

Display

Display diagonal *	68.6 cm (27")
Display resolution *	2560 x 1440 pixels
HD type *	Quad HD
Native aspect ratio *	16:9
Display technology *	LCD
Panel type *	IPS
Backlight type	LED
Touchscreen *	✘
Display brightness (typical)	350 cd/m²
Response time	4 ms
Anti-glare screen	✔
Screen shape *	Flat
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1400 x 1050 (SXGA+), 1600 x 1200 (UXGA), 1600 x 900, 1920 x 1080 (HD 1080), 2560 x 1440
Supported video modes	480i, 480p, 720p, 1080i, 1080p
Contrast ratio (typical) *	1000:1
Maximum refresh rate *	75 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	16.7 million colours
Response time (fast)	5 ms
Pixel pitch	0.2331 x 0.2331 mm
Pixel density	108.79 ppi
Horizontal scan range	30 - 120 kHz
Vertical scan range	48 - 75 Hz
Viewable size, horizontal	59.7 cm

Ergonomics

Cable lock slot *	✔
Height adjustment *	✔
Height adjustment	11 cm
Pivot	✔
Pivot angle	-90 - 90°
Swivelling	✔
Swivel angle range	-30 - 30°
Tilt adjustment	✔
Tilt angle range	-5 - 21°
On Screen Display (OSD)	✔
Plug and Play	✔

Power

Energy efficiency class (SDR) *	F
Energy efficiency class (HDR) *	Not available
Energy consumption (SDR) per 1000 hours *	24 kWh
Power consumption (typical) *	24 W
Power consumption (standby) *	0.3 W
Power consumption (max)	149 W
Power consumption (off)	0.2 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power supply type	Internal
Energy efficiency scale	A to G

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 80%

Display

Viewable size, vertical	33.6 cm
Display diagonal (metric)	68.47 cm
High Dynamic Range (HDR) supported	✘
DDC/CI	✔
Surface hardness	3H
Colour depth	8 bit
RGB colour space	sRGB
sRGB coverage (typical)	99%

Performance

NVIDIA G-SYNC *	✘
AMD FreeSync *	✔
Flicker-free technology	✔
Low Blue Light technology	✔
Repairability index	6.2

Multimedia

Built-in speaker(s) *	✔
Built-in camera *	✔
Number of speakers	2
RMS rated power	5 W
Megapixel (approx.)	5 MP
Built-in microphone	✔

Design

Market positioning *	Business
Product colour *	Silver
Front bezel colour	Black
Detachable stand	✔
Feet colour	Silver
Heavy metals free	Hg (mercury)
Country of origin	China

Ports & interfaces

Built-in USB hub *	✘
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	2
USB Type-C DisplayPort Alternate Mode	✔
USB Power Delivery up to	65 W
HDMI *	✔
HDMI ports quantity	1
HDMI version	1.4
DisplayPorts quantity	1
DisplayPort version	1.2
Headphone out *	✔
Headphone connectivity	3.5 mm

Network

Wi-Fi	✘

Ergonomics

VESA mounting *	✔
Panel mounting interface	100 x 100 mm

Operational conditions

Storage relative humidity (H-H)	5 - 90%
Operating altitude	0 - 5000 m
Non-operating altitude	0 - 12192 m

Packaging content

Stand included	✔
Cables included	AC, USB Type-C to USB Type-C
Quick start guide	✔

Weight & dimensions

Width (with stand)	611.6 mm
Depth (with stand)	174.7 mm
Height (with stand)	510 mm
Weight (with stand)	6.86 kg
Width (without stand)	611.6 mm
Depth (without stand)	56.7 mm
Height (without stand)	365.8 mm
Weight (without stand)	5.18 kg
Bezel width (side)	7.43 mm
Bezel width (top)	7.37 mm
Bezel width (bottom)	2.28 cm

Packaging data

Package width	139.9 mm
Package depth	819.9 mm
Package height	447 mm
Package weight	9.46 kg

Sustainability

Sustainability certificates	ENERGY STAR
European Product Registry for Energy Labelling (EPREL) code	755450

Carbon footprint

Total carbon footprint	622 kg of CO2e
Total carbon emissions (Standard deviation)	148 kg of CO2e
Carbon emissions (Manufacturing)	398 kg of CO2e
Carbon emissions (Logistics)	46 kg of CO2e
Carbon emissions (Use)	173 kg of CO2e
Carbon emissions (End-of-Life)	5 kg of CO2e
Total carbon emissions (w/o Use phase)	449 kg of CO2e
PAIA version	1.3.2

Logistics data

Commodity Classification Automated Tracking System (CCATS)	85285931
Harmonized System (HS) code	85285210

5397184641309

5397184567630

Publication date: 14-MAY-2024. Prints or copies of Information are only valid on the printed Publication date