

ZX350ST

Ultra-compact high brightness laser projector



- **Bright XGA DuraCore laser projector - 3300 lumens and IP6X certified**
- **Ultra compact and short throw lens for easy installation - 360-degree and portrait projection**
- **DuraCore laser technology - 30,000 hours maintenance-free laser light source**
- **Designed with the environment in mind - DuraCore laser technology cuts power consumption and ensures a long product lifespan**



The ZX350ST is one of Optoma's most compact, hassle free XGA DuraCore laser projectors to date. This 3300-lumen projector is built for maintenance-free continuous operation up to 30,000 hours, while its small and lightweight footprint makes it smaller than the previous generation, offering flexible installation in virtually any orientation and location.

Specifications

EAN: 5055387666771, Colour: White

UPC: 796435 44 640 6, Colour: White

Display/image	
Display technology	DLP™
Resolution	XGA (1024x768)
Brightness	3,300 lumens
Contrast ratio	300,000:1
Native aspect ratio	4:3
Aspect ratio - compatible	4:3,16:9
Keystone correction - vertical	+/-40°
Has vertical auto keystone correction	Yes
Displayable colours (millions)	1073.4
Horizontal scan rate	15 ~ 140Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	75%
Screen size	0.81m ~ 7.62m (32" ~ 300") diagonal
Lamp info	
Light source type	Laser
LASER life	30,000 hours
Optical	
Throw ratio	0.617:1
Projection distance (m)	0.4m - 3.76m
Zoom type	Manual
Focal length (mm)	21.85 ~ 24.01
Native offset	115%
Connectivity	
Connections	Inputs 2 x HDMI 1.4a 3D support Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A Control 1 x RS232, 1 x RJ45
General	
Noise level (typical)	32dB
Noise level (max)	34dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D)
3D	3D ready
Security	Security bar, Kensington Lock, Password protected interface
IP rating	IP6X
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Operating conditions	0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m
Remote control	Card style
Speaker count	1
Watts per speaker	15W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual
Optional wireless models	UHDCast Pro
Power	
Power supply	100V ~ 240V, 50-60Hz
Power consumption (standby)	<0.5W
Power consumption (min)	98W
Power consumption (max)	139W
Weight and dimensions	
Dimensions (W x D x H) mm	274 x 216 x 114
Gross weight	4.2 kg
Net weight	3 kg

