



Printing: High Speed Cable 20276 80°C 30V VW-1..

- NOTE:
- TESTING CONDITIONS:
 - 100% TEST FOR OPEN AND SHORT
 - CONDUCTOR RESISTANCE: 3Ω
 - INSULATION RESISTANCE: 10MΩ/DC300/0.01S
 - REAL MACHINE USE DATA:
 - BY QUANTUM DATA 980 HANDHOLD TEST INSTRUMENT FOR DP1.4(32.4G)
 - SUPPORT 7680*4320 30Hz 4:4:4
 - SUPPORT 7680*4320 60Hz 4:2:0 OR DSC
 - BY PC: 3840*2160 120Hz 4:4:4 8Bit HDR OFF
 - BY PC: 3840*2160 120Hz 4:2:2 12Bit HDR ON
 - BY PC: 3840*2160 60Hz 4:4:4 12Bit HDR ON
 - SHIELD: COPPER FOIL TAPE COVER PREMOLD
 - PACKING: EACH CABLE IN A PE BAG
 - ALL COMPONENTS ARE RoHS/REACH COMPLIANT.

PIN OUT	
P1	P2
1	12
3	10
2	11
4	9
6	7
5	8
7	6
9	4
8	5
10	3
12	1
11	2
13	13
14	14
15	15
17	17
16	16
18	18
19	19
SHELL	BRAID
SHELL	SHELL

NO.	MATERIAL	DESCRIPTION	QTY.	UNIT
⑤	MOLDED	OVER MOLDING: BLACK PVC	AR	G
④	MOLDED	INNER MOLDING: PE	AR	G
③	HOOD	DP HOOD: ASSEMBLY TYPE, BLACK ABS	2	SET
②	CONNECTOR	DP1.4 MALE: GOLD PLATED CONTACTS, GOLD PLATED SHELL, RED INSULATION	2	SET
①	CABLE	DP 1.4 CABLE: (30AWG<1/0.25BC>*1P+1C<1/0.25BC>+AL+MY)*5C+30AWG(1/0.25BC)*4C+ADB(16/8/0.12AL-Mg), BLACK PVC JACKET, OD=∅6.0±0.3MM	1	PCS

Ltemref	Quantity	Title/Name, designation, material, dimension etc			Article No./Reference	
Designed by	Checked by	Approved by - date	File name	Date	Scale	FREE
ANGLE:					DP1.4 CABLE 8K 60Hz, 2M	
UNIT:MM		26-6020/8K			Edition	Sheet
					1	1/1