



DELL E Series E2723H computer monitor 68.6 cm (27") 1920 x 1080 pixels Full HD LCD Black

Brand : DELL

Product family: E Series

Product code: DELL-E2723H

Product name : E2723H

- 68.6cm (27") Full HD 1920 x 1080 LED VA
- 8ms, 16:9, 300cd/m², 3000:1
- VGA, DisplayPort

68.6cm (27") Full HD 1920 x 1080 LED VA, 16:9, 300cd/m², 16.7M, 8ms, 178°/178°, 3000:1

DELL E Series E2723H computer monitor 68.6 cm (27") 1920 x 1080 pixels Full HD LCD Black:

Get outstanding value with this 27-inch FHD monitor featuring a wide viewing angle, DP and VGA, and an eco-conscious design.

DELL E Series E2723H. Display diagonal: 68.6 cm (27"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. VESA mounting. Product colour: Black



Display		Ergonomics	
Display diagonal *	68.6 cm (27")	Swivelling	✗
Display resolution *	1920 x 1080 pixels	Tilt adjustment	✓
HD type *	Full HD	Tilt angle range	-5 - 21°
Native aspect ratio *	16:9	On Screen Display (OSD)	✓
Display technology *	LCD	LED indicators	Power, Stand-by
Panel type *	VA	Power	
Backlight type	LED	Energy efficiency class (SDR) *	D
Touchscreen *	✗	Energy efficiency class (HDR) *	Not available
Display brightness (typical)	300 cd/m ²	Energy consumption (SDR) per 1000 hours *	17 kWh
Response time	8 ms	Power consumption (typical) *	17 W
Anti-glare screen	✓	Power consumption (standby) *	0.3 W
Screen shape *	Flat	Power consumption (max)	30 W
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1600 x 900, 1920 x 1080 (HD 1080)	Power consumption (off)	0.25 W
		AC input voltage	100 - 240 V
		AC input frequency	50 - 60 Hz
		Input current	1.5 A
Contrast ratio (typical) *	3000:1	Power supply type	Internal
Maximum refresh rate *	60 Hz	Energy efficiency scale	A to G
Viewing angle, horizontal	178°	Operational conditions	
Viewing angle, vertical	178°	Operating temperature (T-T)	0 - 40 °C
Display number of colours *	16.7 million colours	Storage temperature (T-T)	-20 - 60 °C
Response time (fast)	5 ms	Operating relative humidity (H-H)	10 - 80%
Pixel pitch	0.3114 x 0.3114 mm	Storage relative humidity (H-H)	5 - 90%
Pixel density	81.57 ppi	Operating altitude	0 - 5000 m
Horizontal scan range	30 - 85 kHz	Non-operating altitude	0 - 12192 m
Vertical scan range	48 - 75 Hz	Packaging content	
Viewable size, horizontal	59.8 cm	Stand included	✓
Viewable size, vertical	33.6 cm		
Viewable size diagonal	68.6 cm		

Display		Packaging content	
Display diagonal (metric)	68.6 cm	Cables included	DisplayPort
High Dynamic Range (HDR) supported	✗	Weight & dimensions	
DDC/CI	✓	Width (with stand)	623.3 mm
Surface hardness	3H	Depth (with stand)	188.3 mm
NTSC coverage (typical)	72%	Height (with stand)	458.9 mm
Heat dissipation	102.39 BTU/h	Weight (with stand)	4.5 kg
Heat dissipation (typical)	58.02 BTU/h	Width (without stand)	623.3 mm
Performance		Depth (without stand)	50.4 mm
NVIDIA G-SYNC *	✗	Height (without stand)	370.9 mm
AMD FreeSync *	✗	Weight (without stand)	3.78 kg
Flicker-free technology	✓	Bezel width (side)	1.27 cm
Low Blue Light technology	✓	Bezel width (top)	1.29 cm
Multimedia		Bezel width (bottom)	1.57 cm
Built-in speaker(s) *	✗	Packaging data	
Built-in camera *	✗	Package weight	6.77 kg
Design		Sustainability	
Market positioning *	Business	Sustainability certificates	ENERGY STAR
Product colour *	Black	Doesn't contain	PVC/BFR
Front bezel colour	Black	European Product Registry for Energy Labelling (EPREL) code	1140053
Detachable stand	✓	Carbon footprint	
Feet colour	Black	Total carbon footprint	476 kg of CO2e
Heavy metals free	Hg (mercury)	Total carbon emissions (Standard deviation)	126 kg of CO2e
Ports & interfaces		Carbon emissions (Manufacturing)	301 kg of CO2e
Built-in USB hub *	✗	Carbon emissions (Logistics)	33 kg of CO2e
VGA (D-Sub) ports quantity	1	Carbon emissions (Use)	139 kg of CO2e
HDMI *	✗	Carbon emissions (End-of-Life)	4 kg of CO2e
DisplayPorts quantity	1	Total carbon emissions (w/o Use phase)	338 kg of CO2e
DisplayPort version	1.2	PAIA version	1.3.1
Headphone out *	✗	Brand-specific features	
DC-in jack	✓	Dell Display Manager (DDM) compatibility	✓
Network			
Wi-Fi	✗		
Ergonomics			
VESA mounting *	✓		
Panel mounting interface	100 x 100 mm		
Cable management	✓		
Cable lock slot *	✓		
Cable lock slot type	Kensington		
Height adjustment *	✗		
Pivot	✗		



5397184656921

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-MAY-2024. Prints or copies of Information are only valid on the printed Publication date