

## Epson GP-C831 label printer Inkjet Colour 5760 x 1440 DPI 92 mm/sec Wired Ethernet LAN



**Brand :** Epson

**Product code:** C11CC68132

**Product name :** GP-C831

360 Nozzles, 92 mm/sec, 5.760 x 1.440 dpi, 203 mm, USB 2.0 A, Ethernet (100 Base-TX / 10 Base-T)

Epson GP-C831 label printer Inkjet Colour 5760 x 1440 DPI 92 mm/sec Wired Ethernet LAN:

It combines all the benefits of a rugged colour inkjet printer with the accuracy of an 8-pin tractor feeder and is the first inkjet solution that has been BS5609 certified (complies with the latest GHS standards for chemical labeling).

It features print speeds of up to 91.7mm/sec, printable areas of up to 203.2mm width, precise label feeding to reduce jamming and high-density barcode printing, all at a fraction of the cost of thermal transfer label printers.

Our newly developed printhead protection system protects the ink head from dust to ensure reliable, continuous printing. In addition, Epson's advanced DURABrite pigment inks deliver outstanding stability and resistance to water, chemicals, fading and smudges.

The GP-C831 comes with parallel, USB and LAN 100/10BASE interfaces as standard to make integration easy.

<b>Printing</b>		<b>Operational conditions</b>	
Print technology *	Inkjet	Storage relative humidity (H-H)	-20 - 40%
Colour *	✓	Operating temperature (T-T)	20 - 80 °C
Maximum resolution *	5760 x 1440 DPI	Storage temperature (T-T)	5 - 85 °C
Print speed *	92 mm/sec	<b>Weight &amp; dimensions</b>	
Printing colours	Black, Cyan, Magenta, Yellow	Width	464 mm
Maximum printing width *	20.3 cm	Depth	465 mm
<b>Ports &amp; interfaces</b>		Height	224 mm
Connectivity technology *	Wired	Weight	12.7 kg
Ethernet LAN *	✓	<b>Packaging data</b>	
USB port *	✓	Quantity per pack	1 pc(s)
USB 2.0 ports quantity	1	Package width	590 mm
<b>Design</b>		Package depth	680 mm
Product colour *	Grey	Package height	430 mm
<b>Power</b>		Package weight	16 kg
Power consumption (printing)	33 W	<b>Packaging content</b>	
Power consumption (standby)	8 W	Drivers included	✓
AC input voltage	100 - 240 V	Quick start guide	✓
AC input frequency	50 - 60 Hz	AC adapter included	✓
<b>Operational conditions</b>		<b>Logistics data</b>	
Operating relative humidity (H-H)	10 - 35%	Harmonized System (HS) code	84433210
		Products per pallet	8 pc(s)
		<b>Other features</b>	
		Country of origin	China



8715946530345

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-MAY-2024. Prints or copies of Information are only valid on the printed Publication date