## Epson WorkForce WF-7830DTWF Inkjet A3 4800 x 2400 DPI Wi-Fi

Brand: Epson Product family: WorkForce Product code: C11CH68401

Product name: WF-7830DTWF

A3, Print, Scan, Copy, Fax, 4800 x 2400 DPI, USB, LAN, WLAN, Touchscreen, 18.2 kg
Epson WorkForce WF-7830DTWF. Print technology: Inkjet, Printing: Colour printing, Maximum resolution: 4800 x 2400 DPI. Scanning: Colour scanning, Optical scanning resolution: 1200 x 2400 DPI. Faxing: Colour faxing. Maximum ISO A-series paper size: A3. Wi-Fi. Product colour: Black





Printing		Paper handling	
Duplex printing mode	Auto	Paper tray media weight	64 - 255 g/m²
Print technology *	Inkjet	Ports & interfaces	
Printing *	Colour printing	USB port	1
Duplex printing *	<b>V</b>	Network	•
Maximum resolution *	4800 x 2400 DPI		
Print speed (ISO/IEC 24734) black	25 ppm	Wi-Fi *	✓
Print speed (ISO/IEC 24734) colour	12 ppm	Ethernet LAN *	<b>✓</b>
Duplex print speed (black, normal quality, A4/US Letter)	16 ppm	Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n) 64-bit WEP, 128-bit WEP, WPA-PSK,
Duplex print speed (colour, normal quality, A4/US Letter)	9 ppm	Security algorithms	WPA-TKIP, WPA-AES
Duplex print speed (ISO/IEC 24734, A4) black	16 ppm	Management protocols	SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, SLP, WSD, LLTD, Ping
Duplex print speed (ISO/IEC 24734, A4) colour	9 ppm	Mobile printing technologies	Epson Connect, Epson iPrint, Epson Email Print, Epson Remote Print,
Borderless printing	✓		Apple AirPrint, Mopria Print Service
Scanning		Performance	
Duplex scanning *	✓	Card reader integrated	×
Scanning *	Colour scanning	Design	
Optical scanning resolution *	1200 x 2400 DPI	Product colour *	Black
Scan technology	CIS	Market positioning *	Home & office
Scan to	Cloud	Built-in display *	✓
Image formats supported	BMP, JPEG, TIFF, PNG	Display	LCD
Document formats supported	PDF	Display diagonal	6.86 cm (2.7")
Fax		Touchscreen	✓
Faxing *	Colour faxing	Colour display	✓
Fax transmission speed	3 sec/page	Power	
Modem speed	33.6 Kbit/s	Power consumption (copying)	20 W
Fax memory	180 pages	Power consumption (ready)	8.8 W
Auto-redialing	✓	Power consumption (off)	0.2 W
Speed dialling	✓	, , ,	<u>-</u>
Fax speed dialing (max numbers)	100	System requirements	
Fax forwarding	✓	Windows operating systems supported	✓
Fax forwarding to	PC	Mac operating systems supported	<b>√</b>
Error Correction Mode (ECM)	✓	mac operating systems supported	•

Features		Weight & dimensions	
Recommended duty cycle  Maximum duty cycle *  Number of print cartridges *	200 - 2500 pages per month 50000 pages per month 4	Width Depth Height	515 mm 400 mm 350 mm
Printing colours *	Black, Cyan, Magenta, Yellow	Weight	18.2 kg
Page description languages Country of origin	ESC/P-R Indonesia	Packaging data	
Input & output capacity		Package width Package depth	475 mm 590 mm
Total number of input trays * Total output capacity * Multi-Purpose tray Multi-Purpose tray input capacity Auto document feeder (ADF) Auto document feeder (ADF) input capacity Maximum input capacity	2 125 sheets  ✓ 500 sheets  ✓ 50 sheets  500 sheets	Package depth Package height Package weight Quantity per pack	465 mm 21.6 kg 1 pc(s)
		Packaging content	
		Cartridge(s) included Cables included Drivers included Warranty card	AC
Paper handling		Logistics data	
Maximum ISO A-series paper size * Paper tray media types * ISO A-series sizes (A0A9) * ISO B-series sizes (B0B9) Non-ISO print media sizes Envelopes sizes Photo paper sizes	A3 Thick paper A3, A4, A5, A6 B4, B5 Legal, Letter C4, C6, DL 9x13,10x15,13x18	Harmonized System (HS) code Products per pallet layer Products per pallet Products per pallet layer (UK) Products per pallet (UK)	84433100 2 pc(s) 8 pc(s) 4 pc(s) 16 pc(s)
		Other features	
		Printing method Number of users  Compatible operating systems	Epson PrecisionCore 5 user(s) Mac OS 10.5.8 oder höher, Windows 10, Windows 7, Windows 8, Windows Server 2003 (32/64 Bit), Windows Server 2008 (32/64 Bit), Windows Server 2008 R2, Windows Server 2012 (64bit), Windows Vista, Windows XP, Windows Server 2003 R2
		Ink drop	3.8
		Fax polling	√ 800 nozzles black, 256 nozzles per
		Print head nozzles	colour
		Supported network protocols	TCP/IPv4, TCP/IPv6



8715946668406

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.