## Philips B Line 243B1JH/00 computer monitor 60.5 cm (23.8") 1920 x 1080 pixels Full HD LCD Black

Brand : Philips

Product family: B Line

Product code: 243B1JH/00

Product name : 243B1JH/00

Business Monitor 243B1JH LCD monitor with USB docking

## Philips B Line 243B1JH/00 computer monitor 60.5 cm (23.8") 1920 x 1080 pixels Full HD LCD Black:

This Philips monitor offers 100 W power delivery and a simple laptop docking solution. One USB dual mesh cable with Type C and A connectors delivers video, Ethernet, power charge and DisplayLink functions. Windows Hello webcam offers greater security.

Philips B Line 243B1JH/00. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Display surface: Matt, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black









Display		Ports & interfaces	
Display diagonal *	60.5 cm (23.8")	HDCP version	1.4
Display resolution *	1920 x 1080 pixels	DC-in jack	1
HD type *	Full HD	DisplayPort output	1
Native aspect ratio *	16:9	Network	
Display technology *	LCD	Ethernet LAN	1
Panel type *	IPS		•
Backlight type	W-LED	Ergonomics	
Touchscreen *	×	VESA mounting *	1
Display brightness (typical)	300 cd/m <sup>2</sup>	Panel mounting interface	100 x 100 mm
Response time	4 ms	Cable lock slot *	1
Display surface	Matt	Cable lock slot type	Kensington
Anti-glare screen	<	Height adjustment *	1
Screen shape *	Flat	Height adjustment	15 cm
Aspect ratio	16:9	Pivot	1
Contrast ratio (typical) *	1000:1	Pivot angle	-90 - 90°
Contrast ratio (dynamic)	5000000:1	Swivel angle range	-180 - 180°
Dynamic contrast ratio marketing name	SmartContrast	Tilt adjustment Tilt angle range	✓ -5 - 30°
Maximum refresh rate *	75 Hz	On Screen Display (OSD)	1
Viewing angle, horizontal	178°		Simplified Chinese, Traditional
Viewing angle, vertical	178°		Chinese, Czech, German, Dutch,
Display number of colours *	16.7 million colours	On Screen Display (OSD) languages	English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese,
Pixel pitch	0.2745 x 0.2745 mm		Korean, Polish, Portuguese, Russian,
Pixel density	93 ppi		Swedish, Turkish, Ukrainian
Horizontal scan range	30 - 85 kHz	Number of OSD languages	21
Vertical scan range	48 - 75 Hz	Plug and Play	1
Viewable size, horizontal	57.8 cm	LED indicators	Operation, Stand-by
Viewable size, vertical	29.6 cm	Power	
Digital horizontal frequency	30 - 85 kHz	Energy efficiency class (SDR) *	E
Digital vertical frequency	48 - 75 Hz	Energy enteriney class (SDN)	-

		_	
Display		Power	
Display diagonal (metric)	60.5 cm	Energy consumption (SDR) per 1000 hours *	<sup>0</sup> 15 kWh
DDC/CI Haze rate	<b>√</b> 25%	Power consumption (typical) *	14.2 W
Surface hardness	3H	Power consumption (standby) *	0.5 W
sRGB coverage (typical)	105%	Power consumption (off)	0.3 W
NTSC coverage (typical)	88%	Power consumption (PowerSave)	13.5 W
Display sRGB	✓	AC input voltage	100 - 240 V
Performance		AC input frequency AC adapter output voltage	50 - 60 Hz 19 V
NVIDIA G-SYNC *	×	Power supply type	External
AMD FreeSync *	×	Operational conditions	
Component video sync	Separate sync	Operating temperature (T-T)	0 - 40 °C
Flicker-free technology		Storage temperature (T-T)	-20 - 60 °C
Low Blue Light technology HBR3 support		Operating relative humidity (H-H)	20 - 80%
Windows operating systems	Windows 10, Windows 7, Windows	Operating altitude	0 - 3658 m
supported	8, Windows 8.1	Non-operating altitude	0 - 12192 m
	Mac OS X 10.0 Cheetah, Mac OS X 10.1 Puma, Mac OS X 10.10	Packaging content	
	Yosemite, Mac OS X 10.11 El	Stand included	✓
	Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS	Cables included	HDMI, DisplayPort, USB Type-C, DC,
	X 10.14 Mojave, Mac OS X 10.15	Manual	AC
Mac operating systems supported	Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.2 Jaguar, Mac		SmartControl
	OS X 10.3 Panther, Mac OS X 10.4	Weight & dimensions	
	Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X	Width (with stand)	540 mm
	10.7 Lion, Mac OS X 10.8 Mountain	Depth (with stand)	205 mm
	Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur	Height (with stand)	501 mm
Multimedia	-	Weight (with stand)	4.88 kg
Built-in speaker(s) *	1	Width (without stand)	540 mm
Built-in camera *		Depth (without stand)	51 mm
Number of speakers	2	Height (without stand)	323 mm
RMS rated power	3 W	Weight (without stand)	3.27 kg
Megapixel (approx.)	2 MP	Packaging data	
Built-in microphone	4	Package width	730 mm
Design		Package depth	198 mm
Product colour *	Black	Package height Package weight	465 mm 7.56 kg
Front bezel colour	Black		7.50 kg
Feet colour	Black	Sustainability	
Heavy metals free	Hg (mercury) UKRAINIAN, CB, TUV/GS, TUV Ergo,	Sustainability certificates Doesn't contain	ENERGY STAR, RoHS, TCO PVC/BFR, Mercury
Certification	SEMKO, CU-EAC, EAEU RoHS, CE	European Product Registry for	
Certification	Mark, FCC Class B, ICES-003, TUV Eye Comfort certified	Energy Labelling (EPREL) code	398405
Ports & interfaces		Recycling data	
Built-in USB hub *	4	Post-consumer recycled plastic	85%
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Logistics data	
USB upstream port type	USB Type-C	Harmonized System (HS) code	85285210
Number of upstream ports	1	Other features	
Number of USB Type-C upstream	1	USB Power Delivery revision	3.0
ports quantity USB Type-A downstream ports		Exterior finish type	Textured
quantity	4	Picture enhancement	SmartImage
USB Type-C downstream ports	1	Recyclable packaging material	100%
quantity USB Type-C DisplayPort Alternate			UKRAINIAN; CB; TUV/GS; TUV Ergo; CU-EAC; EAEU RoHS; CE Mark; FCC
Mode	4	Regulatory Approvals	Class B; ICES-003; TUV Eye Comfort
USB Power Delivery	<	500 1	certified
USB Power Delivery up to	100 W	ECO mode	4
DVI port	×	Light sensor EasyRead mode	4
HDMI *	<b>√</b>	LowBlue mode	,
HDMI ports quantity	1		•

Ports & interfaces		Other features
HDMI version	1.4	Mean time between failures (MTBF) 70000 h
DisplayPorts quantity	1	Ethernet LAN data rates 10,100,1000 Mbit/s
DisplayPort version	1.4	Ethernet LAN (RJ-45) ports 1
Audio input	×	Wake-on-LAN 🗸
Audio output	1	
Headphone out *	×	
HDCP	1	



8712581771096

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.