

## ASUS ProArt PA279CV computer monitor 68.6 cm (27") 3840 x 2160 pixels 4K Ultra HD LED Black, Silver

**Brand :** ASUS

**Product family:** ProArt

**Product code:** 90LM06M1-B01170

**Product name :** PA279CV

- 27-inch 4K UHD (3840 x 2160) LED backlight display with IPS 178° wide viewing angle panel
  - International color standard 100% sRGB and 100% Rec. 709 wide color gamut
  - Calman Verified with factory calibrated for excellent Delta E < 2 color accuracy
  - Extensive connectivity including DP over USB-C™ with 65W Power Delivery, DisplayPort, HDMI, USB 3.0 hub
  - Adaptive-Sync technology (40~60Hz) to animated content with fast action and eliminate screen tearing
  - ASUS-exclusive ProArt Preset and ProArt Palette provide numerous adjustable color parameters
  - Ergonomic design with +35° ~ -5° tilt, ±45° swivel, ±90° pivot and 150mm height adjustments for a comfortable viewing experience
- 27", IPS, 4K UHD, 3840 x 2160, 5ms, 16:9, HDCP, 2 x HDMI, DisplayPort, USB Type-C, 4 x USB Type-A, 3.5mm, Flicker free, HDR-10, VESA, Frameless, 614 x 370 x 60 mm, 5.7 Kg




Display		Ports & interfaces	
Display diagonal *	68.6 cm (27")	HDMI version	2.0
Display resolution *	3840 x 2160 pixels	DisplayPorts quantity	1
HD type *	4K Ultra HD	DisplayPort version	1.2
Native aspect ratio *	16:9	Audio input	✗
Display technology *	LED	Headphone out *	✓
Panel type *	IPS	Headphone outputs	1
Touchscreen *	✗	Headphone connectivity	3.5 mm
Display brightness (typical)	350 cd/m <sup>2</sup>	HDCP	✓
Response time	5 ms	AC (power) in	✓
Screen shape *	Flat	Ergonomics	
Supported graphics resolutions	3840 x 2160	VESA mounting *	✓
Aspect ratio	16:9	Panel mounting interface	100 x 100 mm
Contrast ratio (typical) *	1000:1	Cable lock slot *	✓
Contrast ratio (dynamic)	100000000:1	Cable lock slot type	Kensington
Dynamic contrast ratio marketing name	SmartContrast	Height adjustment *	✓
Maximum refresh rate *	60 Hz	Height adjustment	15 cm
Viewing angle, horizontal	178°	Pivot	✓
Viewing angle, vertical	178°	Pivot angle	-90 - 90°
Display number of colours *	1.073 billion colours	Swivelling	✓
Pixel pitch	0.155 x 0.155 mm	Swivel angle range	-45 - 45°
Viewable size, horizontal	59.7 cm	Tilt adjustment	✓
Viewable size, vertical	33.6 cm	Tilt angle range	-5 - 35°
Viewable size diagonal	68.5 cm	Power	
Digital horizontal frequency	29 - 160 kHz	Energy efficiency class (SDR) *	G
Digital vertical frequency	40 - 60 Hz	Energy efficiency class (HDR) *	G
High Dynamic Range (HDR) supported	✓	Energy consumption (SDR) per 1000 hours *	32 kWh
High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10)	Energy consumption (HDR) per 1000 hours *	54 kWh
sRGB coverage (typical)	100%	Power consumption (typical) *	32.1 W
Performance		Power consumption (standby) *	0.5 W
VESA Adaptive Sync support	✓	Power consumption (off)	0.2 W
		AC input voltage	100 - 240 V

<b>Performance</b>		<b>Power</b>	
Flicker-free technology	✓	AC input frequency	50 - 60 Hz
Low Blue Light technology	✓	Energy efficiency scale	A to G
<b>Multimedia</b>		<b>Packaging content</b>	
Built-in speaker(s) *	✓	Stand included	✓
Built-in camera *	✗	Cables included	AC
Number of speakers	2	Quick start guide	✓
RMS rated power	2 W	<b>Weight &amp; dimensions</b>	
<b>Design</b>		Width (with stand)	614 mm
Market positioning *	Photo editing	Depth (with stand)	227.8 mm
Product colour *	Black, Silver	Height (with stand)	523.4 mm
Frameless design	✓	Weight (with stand)	8.6 kg
Front bezel colour	Black	Width (without stand)	614 mm
Detachable stand	✓	Depth (without stand)	60 mm
Feet colour	Silver	Height (without stand)	370 mm
Country of origin	China	Weight (without stand)	5.7 kg
Certification	TUV Flicker-free , TUV Low Blue Light, Calman Verified	<b>Packaging data</b>	
<b>Ports &amp; interfaces</b>		Package width	516 mm
Built-in USB hub *	✓	Package depth	161 mm
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Package height	680 mm
Number of upstream ports	4	Package weight	11.2 kg
USB Type-A downstream ports quantity	4	Package type	Box
USB Type-C downstream ports quantity	1	<b>Sustainability</b>	
DVI port	✗	European Product Registry for Energy Labelling (EPREL) code	403921
HDMI *	✓	<b>Logistics data</b>	
HDMI ports quantity	2	Commodity Classification Automated Tracking System (CCATS)	8528521000
		Harmonized System (HS) code	85285210



4718017853200




0192876853207



192876853207



4718017853170



0192876853214



192876853214

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.