PHILIPS

Philips S Line 243S1/00 computer monitor 60.5 cm (23.8") 1920 x 1080 pixels Full HD LCD Black

Brand : Philips   **Product family:** S Line   **Product code:** 243S1/00

Product name : 243S1/00

Business Monitor 243S1 LCD monitor with USB-C docking

Philips S Line 243S1/00 computer monitor 60.5 cm (23.8") 1920 x 1080 pixels Full HD LCD Black:

The Philips USB-C monitor replaces cable clutter. View FHD image and recharge a laptop, all at the same time with a single USB-C cable. Features like Daisy chain for multi-display setup, Eye comfort with TUV certified to reduce eye fatigue

Philips S Line 243S1/00. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Display surface: Matt, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 2 (3.1 Gen 2). VESA mounting, Height adjustment. Product colour: Black

Display

|	
Display diagonal *	60.5 cm (23.8")
Display resolution *	1920 x 1080 pixels
HD type *	Full HD
Native aspect ratio *	16:9
Display technology *	LCD
Panel type *	IPS
Backlight type	W-LED
Touchscreen *	✖
Display brightness (typical)	300 cd/m²
Response time	4 ms
Display surface	Matt
Anti-glare screen	✔
Screen shape *	Flat
Aspect ratio	16:9
Contrast ratio (typical) *	1000:1
Contrast ratio (dynamic)	50000000:1
Dynamic contrast ratio marketing name	SmartContrast
Maximum refresh rate *	75 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	16.7 million colours
Pixel pitch	0.2745 x 0.2745 mm
Pixel density	93 ppi
Horizontal scan range	30 - 85 kHz
Vertical scan range	48 - 75 Hz
Viewable size, horizontal	52.7 cm
Viewable size, vertical	29.6 cm
Display diagonal (metric)	60.5 cm
DDC/CI	✔

Ergonomics

Panel mounting interface	100 x 100 mm
Cable lock slot *	✔
Cable lock slot type	Kensington
Height adjustment *	✔
Height adjustment	13 cm
Pivot	✔
Pivot angle	-90 - 90°
Swivelling	✔
Swivel angle range	-180 - 180°
Tilt angle range	-5 - 25°
On Screen Display (OSD)	✔
On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Number of OSD languages	21
Plug and Play	✔
LED indicators	Operation, Stand-by

Power

Energy efficiency class (SDR) *	D
Energy efficiency class (HDR) *	Not available
Energy consumption (SDR) per 1000 hours *	14 kWh
Power consumption (typical) *	14 W
Power consumption (standby) *	0.3 W
Power consumption (off)	0.3 W
Power consumption (PowerSave)	12.9 W
AC input voltage	100 - 240 V

Display

Haze rate	25%
Surface hardness	3H
RGB colour space	sRGB
sRGB coverage (typical)	107%
NTSC coverage (typical)	91%
Display sRGB	✔

Performance

NVIDIA G-SYNC *	✘
AMD FreeSync *	✘
Fast charging	✔
Fast charging technology	Power Delivery
Component video sync	Separate sync
Flicker-free technology	✔
Low Blue Light technology	✔
Compatible operating systems	Mac OS X Windows 10 / 8.1 / 8 / 7

Multimedia

Built-in speaker(s) *	✔
Built-in camera *	✘
Number of speakers	2
RMS rated power	4 W

Design

Market positioning *	Office
Product colour *	Black
Front bezel colour	Black
Feet colour	Black
Heavy metals free	Hg (mercury)
Certification	CB, FCC Class B, ICES-003, CE Mark, TUV/GS, TUV Ergo, SEMKO, CU-EAC, EAEU RoHS, TUV Eye Comfort certified

Ports & interfaces

Built-in USB hub *	✔
USB hub version	3.2 Gen 2 (3.1 Gen 2)
USB upstream port type	USB Type-C
Number of upstream ports	1
USB Type-A downstream ports quantity	4
USB Type-C DisplayPort Alternate Mode	✔
USB Power Delivery	✔
USB Power Delivery up to	65 W
HDMI *	✔
HDMI ports quantity	1
HDMI version	1.4
DisplayPorts quantity	1
DisplayPort version	1.2
Audio output	✔
HDCP	✔
HDCP version	1.4
DisplayPort output	✔

Network

Ethernet LAN	✔

Ergonomics

VESA mounting *	✔

Power

AC input frequency	50 - 60 Hz
Power supply type	Internal
Energy efficiency scale	A to G

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Operating altitude	0 - 3658 m
Non-operating altitude	3658 - 12192 m

Packaging content

Stand included	✔
Cables included	HDMI, DisplayPort, USB Type-C, AC
Manual	✔
Bundled software	SmartControl

Weight & dimensions

Width (with stand)	540 mm
Depth (with stand)	205 mm
Height (with stand)	482 mm
Weight (with stand)	5.28 kg
Width (without stand)	540 mm
Depth (without stand)	51 mm
Height (without stand)	323 mm
Weight (without stand)	3.42 kg

Packaging data

Package width	625 mm
Package depth	180 mm
Package height	435 mm
Package weight	8.46 kg

Sustainability

Sustainability compliance	✔
Sustainability certificates	ENERGY STAR, TCO, RoHS
Doesn't contain	PVC/BFR, Mercury
European Product Registry for Energy Labelling (EPREL) code	1014111

Recycling data

Post-consumer recycled plastic	85%

Logistics data

Harmonized System (HS) code	85285210

Other features

USB Power Delivery revision	3.0
Exterior finish type	Textured
Picture enhancement	SmartImage
Recyclable packaging material	100%
Regulatory Approvals	CB; FCC Class B; ICES-003; CE Mark; TUV/GS; TUV Ergo; CU-EAC; EAEU RoHS; TUV Eye Comfort certified
EasyRead mode	✔
LowBlue mode	✔
Energy efficiency class (old)	D
Mean time between failures (MTBF)	70000 h
Ethernet LAN data rates	10,100,1000 Mbit/s
Wake-on-LAN	✔

8712581784744

0609585254886

609585254886