

PHILIPS

Philips P Line 329P1H/00 LED display 80 cm (31.5") 3840 x 2160 pixels 4K Ultra HD Black

Brand : Philips

Product family: P Line

Product code: 329P1H/00

Product name : 329P1H/00



Brilliance 329P1H LCD monitor with USB-C docking

Philips P Line 329P1H/00 LED display 80 cm (31.5") 3840 x 2160 pixels 4K Ultra HD Black:


The Philips USB-C docking display for a comprehensive solution. View UltraClear 4K UHD and re-charge a laptop up to 90 W, all at the same time with a single USB-C cable. Pop-up webcam with Windows Hello delivers performance and convenience.

Philips P Line 329P1H/00. Display diagonal: 80 cm (31.5"), Display resolution: 3840 x 2160 pixels, HD type: 4K Ultra HD, Display technology: LED, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 2 (3.1 Gen 2). VESA mounting, Height adjustment. Product colour: Black



| Display | | Network | |
|---------------------------------------|-----------------------|---|---|
| Display diagonal * | 80 cm (31.5") | Ethernet LAN | ✓ |
| Display resolution * | 3840 x 2160 pixels | Ergonomics | |
| HD type * | 4K Ultra HD | VESA mounting * | ✓ |
| Native aspect ratio * | 16:9 | Panel mounting interface | 100 x 100 mm |
| Display technology * | LED | Cable lock slot * | ✓ |
| Panel type * | IPS | Cable lock slot type | Kensington |
| Backlight type | W-LED | Height adjustment * | ✓ |
| Touchscreen * | ✗ | Height adjustment | 18 cm |
| Display brightness (typical) | 350 cd/m ² | Pivot | ✓ |
| Response time | 4 ms | Pivot angle | -90 - 90° |
| Anti-glare screen | ✓ | Swivelling | ✓ |
| Screen shape * | Flat | Swivel angle range | -180 - 180° |
| Aspect ratio | 16:9 | Tilt adjustment | ✓ |
| Contrast ratio (typical) * | 1000:1 | Tilt angle range | -5 - 25° |
| Contrast ratio (dynamic) | 50000000:1 | On Screen Display (OSD) | ✓ |
| Dynamic contrast ratio marketing name | SmartContrast | On Screen Display (OSD) languages | Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian |
| Maximum refresh rate * | 60 Hz | Plug and Play | ✓ |
| Viewing angle, horizontal | 178° | LED indicators | Operation, Stand-by |
| Viewing angle, vertical | 178° | Power | |
| Display number of colours * | 1.07 billion colours | Energy efficiency class (SDR) * | G |
| Pixel pitch | 0.18159 x 0.18159 mm | Energy consumption (SDR) per 1000 hours * | 40 kWh |
| Pixel density | 140 ppi | Power consumption (typical) * | 31.8 W |
| Horizontal scan range | 30 - 140 kHz | Power consumption (standby) * | 0.3 W |
| Vertical scan range | 23 - 75 Hz | Power consumption (PowerSave) | 26.8 W |
| Viewable size, horizontal | 69.7 cm | | |
| Viewable size, vertical | 39.2 cm | | |
| Digital horizontal frequency | 30 - 140 kHz | | |
| Digital vertical frequency | 23 - 75 Hz | | |
| Display diagonal (metric) | 80 cm | | |

| | | | |
|---------------------------------------|---|---|---|
| Display | | Power | |
| DDC/CI | ✓ | AC input voltage | 100 - 240 V |
| Haze rate | 25% | AC input frequency | 50 - 60 Hz |
| Surface hardness | 3H | Power supply type | Internal |
| RGB colour space | sRGB | Energy efficiency scale | A to G |
| Colour gamut | 117% | Operational conditions | |
| sRGB coverage (typical) | 128% | Operating temperature (T-T) | 0 - 40 °C |
| NTSC coverage (typical) | 117% | Storage temperature (T-T) | -20 - 60 °C |
| Adobe RGB coverage | 89% | Operating relative humidity (H-H) | 20 - 80% |
| Display sRGB | ✓ | Operating altitude | 0 - 3658 m |
| Performance | | Non-operating altitude | 0 - 12192 m |
| NVIDIA G-SYNC * | ✗ | Packaging content | |
| AMD FreeSync * | ✗ | Stand included | ✓ |
| VESA Adaptive Sync support | ✓ | Cables included | HDMI, DisplayPort, USB Type-C, AC |
| Component video sync | Separate sync | Manual | ✓ |
| Flicker-free technology | ✓ | Bundled software | SmartControl |
| Low Blue Light technology | ✓ | Weight & dimensions | |
| HBR3 support | ✓ | Width (with stand) | 714 mm |
| Multimedia | | Depth (with stand) | 280 mm |
| Built-in speaker(s) * | ✓ | Height (with stand) | 649 mm |
| Built-in camera * | ✓ | Weight (with stand) | 12.2 kg |
| Number of speakers | 2 | Width (without stand) | 714 mm |
| RMS rated power | 10 W | Depth (without stand) | 62 mm |
| Megapixel (approx.) | 2 MP | Height (without stand) | 422 mm |
| Built-in microphone | ✓ | Weight (without stand) | 8.19 kg |
| Design | | Packaging data | |
| Market positioning * | Home | Package width | 930 mm |
| Product colour * | Black | Package depth | 186 mm |
| Front bezel colour | Black | Package height | 563 mm |
| Feet colour | Black | Package weight | 15.5 kg |
| Heavy metals free | Hg (mercury) | Package type | Box |
| Certification | UKRAINIAN, EPA, cETLus, CB, TUV/GS, TUV Ergo, SEMKO, CU-EAC, EAEU RoHS, CE Mark, FCC Class B, ICES-003, TUV Eye Comfort certified | Sustainability | |
| Ports & interfaces | | Sustainability certificates | ENERGY STAR, TCO, RoHS |
| Built-in USB hub * | ✓ | Doesn't contain | PVC/BFR, Mercury |
| USB hub version | 3.2 Gen 2 (3.1 Gen 2) | European Product Registry for Energy Labelling (EPREL) code | 399162 |
| USB upstream port type | USB Type-C | Recycling data | |
| Number of upstream ports | 1 | Post-consumer recycled plastic | 85% |
| USB Type-A downstream ports quantity | 4 | Logistics data | |
| USB Type-C DisplayPort Alternate Mode | ✓ | Harmonized System (HS) code | 85285210 |
| USB Power Delivery | ✓ | Other features | |
| USB Power Delivery up to | 90 W | USB Power Delivery revision | 3.0 |
| DVI port | ✗ | Exterior finish type | Textured |
| HDMI * | ✓ | Picture enhancement | SmartImage |
| HDMI ports quantity | 2 | Recyclable packaging material | 100% |
| HDMI version | 2.0 | Regulatory Approvals | UKRAINIAN; cETLus; CB; TUV/GS; TUV Ergo; CU-EAC; EAEU RoHS; CE Mark; FCC Class B; ICES-003; TUV Eye Comfort certified |
| DisplayPorts quantity | 1 | Delta E | 2 |
| DisplayPort version | 1.4 | Light sensor | ✓ |
| Audio output | ✓ | EasyRead mode | ✓ |
| HDCP | ✓ | LowBlue mode | ✓ |
| HDCP version | 2.2 | Philips SmartUniformity | 93 - 105% |
| | | Mean time between failures (MTBF) | 70000 h |
| | | Ethernet LAN data rates | 10,100,1000 Mbit/s |
| | | Wake-on-LAN | ✓ |



8712581768058



0609585253902



609585253902

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.