iiyama

iiyama ProLite X3270QSU-B1 computer monitor 81.3 cm (32") 2560 x 1440 pixels Wide Quad HD LED Black

Brand : iiyama   **Product family:** ProLite   **Product code:** X3270QSU-B1

Product name : X3270QSU-B1

iiyama ProLite X3270QSU-B1. Display diagonal: 81.3 cm (32"), Display resolution: 2560 x 1440 pixels, HD type: Wide Quad HD, Display technology: LED, Response time: 3 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting. Product colour: Black

Display

Display diagonal *	81.3 cm (32")
Display resolution *	2560 x 1440 pixels
HD type *	Wide Quad HD
Native aspect ratio *	16:9
Display technology *	LED
Panel type *	IPS
Touchscreen *	✖
Display brightness (typical)	250 cd/m²
Response time	3 ms
Screen shape *	Flat
Aspect ratio	16:9
Contrast ratio (typical) *	1200:1
Maximum refresh rate *	100 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.272 x 0.272 mm
Horizontal scan range	30 - 90 kHz
Viewable size, horizontal	69.8 cm
Viewable size, vertical	39.3 cm
Display diagonal (metric)	80 cm

Performance

NVIDIA G-SYNC *	✖
AMD FreeSync *	✖
VESA Adaptive Sync support	✔
Flicker-free technology	✔

Multimedia

Built-in speaker(s) *	✔
Built-in camera *	✖
Number of speakers	2
RMS rated power	4 W

Design

Market positioning *	Business

Ports & interfaces

HDMI version	2.0
DisplayPorts quantity	1
DisplayPort version	1.4
Headphone out *	✔
Headphone connectivity	3.5 mm
HDCP	✔

Ergonomics

VESA mounting *	✔
Panel mounting interface	100 x 100 mm
Cable management	✔
Tilt adjustment	✔
Tilt angle range	4 - 20°
On Screen Display (OSD)	✔
On Screen Display (OSD) languages	Czech, German, English, French, Italian, Japanese, Polish, Russian

Power

Energy efficiency class (SDR) *	E
Energy efficiency class (HDR) *	Not available
Energy consumption (SDR) per 1000 hours *	27 kWh
Power consumption (typical) *	35 W
Power consumption (standby) *	0.3 W
Power consumption (off)	0.5 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Energy efficiency scale	A to G

Packaging content

Cables included	HDMI, Power, USB
Quick start guide	✔

Weight & dimensions

Width (with stand)	726 mm
Depth (with stand)	221.5 mm

Design

Product colour *	Black
Certification	CE, TÜV-Bauart, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA

Ports & interfaces

Built-in USB hub *	✔
USB hub version	3.2 Gen 1 (3.1 Gen 1)
Number of upstream ports	3
HDMI *	✔
HDMI ports quantity	2

Weight & dimensions

Height (with stand)	503.5 mm
Weight (with stand)	6.9 kg

Packaging data

Package width	810 mm
Package depth	125 mm
Package height	505 mm
Package weight	8.5 kg

4948570123643