Lindy DST-Mini Plus, USB-C Laptop Mini Docking Station with 4K HDMI, VGA Support and 100W Pass-Through Charging

Brand : Lindy

Product code: 43278

Product name : DST-Mini Plus, USB-C Laptop Mini Docking Station with 4K HDMI, VGA Support and 100W Pass-Through Charging

- Adds 3 USB 3.2 / 3.1 Gen 1 / USB 3.0 Type A ports, an HDMI and VGA port as well as a Gigabit Ethernet port to a laptop
- Supports 4K UHD 3840x2160@30Hz for HDMI displays and Full HD 1920x1080@60Hz for VGA displays
- Features DisplayPort Alternate Mode
- USB Power Delivery 3.0 capable up to 100W
- 2 year warranty

DST-Mini Plus, USB-C Laptop Mini Docking Station with 4K HDMI, VGA Support and 100W Pass-Through Charging

Lindy DST-Mini Plus, USB-C Laptop Mini Docking Station with 4K HDMI, VGA Support and 100W Pass-Through Charging. Host interface: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, USB Power Delivery up to: 100 W. Ethernet LAN data rates: 10,100,1000 Mbit/s. Product colour: Grey, Compatible memory cards: MicroSD (TransFlash), SD, Hub interfaces: HDMI, RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A, USB 3.2 Gen 1 (3.1 Gen 1) Type-C, VGA. Power supply type: USB. Width: 180 mm, Depth: 17 mm, Height: 49 mm

Ports & interfaces

Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	3
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1
USB Power Delivery	✔
USB Power Delivery revision	3.0
USB Power Delivery up to	100 W
HDMI ports quantity *	1
VGA (D-Sub) ports quantity	1
HDCP	✔
HDCP version	2.2
USB Type-C DisplayPort Alternate Mode	✔

Network

Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	10,100,1000 Mbit/s

Performance

Card reader integrated *	✔
Compatible memory cards	MicroSD (TransFlash), SD
Product colour *	Grey
Hub interfaces	HDMI, RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A, USB 3.2 Gen 1 (3.1 Gen 1) Type-C, VGA
Housing material	Aluminium
Certification	CE, UKCA, FCC, REACH, RoHS, CP65

Power

Power supply type	USB

Operational conditions

Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	20 - 80%

Weight & dimensions

Width	180 mm
Depth	17 mm
Height	49 mm
Weight	90 g

Packaging data

Quantity per pack	1 pc(s)
Package width	174 mm
Package depth	194 mm
Package weight	100 g

Packaging content

Manual	✔

Logistics data

Harmonized System (HS) code	84719000

Other features

Chipset	RTL8153B, EP9632G, GL3510
Maximum operating temperature	45 °C

4002888432788