

Gigabyte P750GM power supply unit 750 W 20+4 pin ATX ATX Black

Brand : Gigabyte

Product code: GP-P750GM

Product name : P750GM

- 80 PLUS Gold certified
- Fully modular design
- 120mm Smart Hydraulic Bearing (HYB) Fan
- Main Japanese capacitors
- Powerful single +12V rail
- OVP/OPP/SCP/UV/PC/OTP protection
- 5 years warranty (Adjusted according to different regions)

P750GM, 80 PLUS Gold, 750W, Active PFC, 120mm

Gigabyte P750GM. Total power: 750 W, AC input voltage: 100 - 240 V, AC input frequency: 50 - 60 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 61 cm, SATA power cable length: 150,600 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Cables included: CPU, PCIe, Peripheral (Molex), SATA



Power		Ports & interfaces	
Total power *	750 W	ATX power connector (20+4 pin)	✓
AC input voltage *	100 - 240 V	Floppy drive power connector	1
AC input frequency	50 - 60 Hz	Floppy disk drive cable length	12 cm
Input current	12-6 A	PCI Express connector	✓
Power Factor Correction (PFC) type	Active	Cabling type	Fully-Modular
Hold time	16 ms		
Efficiency	90%		
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage		
Ports & interfaces		Performance	
Motherboard power connector *	20+4 pin ATX	80 PLUS certification *	80 PLUS Gold
Motherboard power cable length	61 cm	Purpose *	PC
Number of SATA power connectors	8	Power supply unit (PSU) form factor *	ATX
SATA power cable length	150,600 mm	ATX version	2.31
Peripheral (Molex) power connectors (4-pin) *	4	Mean time between failures (MTBF)	100000 h
Peripheral (Molex) power cable length	120,500 mm		
EPS power connector (4+4 pin)	✓	Design	
PCI Express power connectors (6+2 pin)	4	Product colour	Black
PCI Express power cable length	60 cm	Cooling type	Active
CPU power connector (4+4 pin)	✓	Fan diameter	12 cm
CPU power cable length	60 cm	Number of fans	1 fan(s)
		Fan location	Top
		Packaging content	
		Cables included	CPU, PCIe, Peripheral (Molex), SATA
		Weight & dimensions	
		Width	150 mm
		Depth	140 mm
		Height	86 mm
		Logistics data	
		Harmonized System (HS) code	84733020



0813567028710



813567028710



4719331551759

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.