



## DELL P Series P2422H\_WOST LED display 60.5 cm (23.8") 1920 x 1080 pixels Full HD LCD Black

**Brand :** DELL

**Product family:** P Series

**Product code:** DELL-P2422HWOS



**Product name :** P2422H\_WOST

- 60.5cm (23.8") Full HD 1920 x 1080 LED IPS
- 8ms, 16:9, 250cd/m<sup>2</sup>, 1000:1
- USB, VGA, HDMI, DisplayPort
- 60.5cm (23.8") Full HD 1920 x 1080 LED IPS, 16:9, 250cd/m<sup>2</sup>, 16.7M, 8ms, 178°/178°, 1000:1

DELL P Series P2422H\_WOST LED display 60.5 cm (23.8") 1920 x 1080 pixels Full HD LCD Black:

Stay productive, no matter where you work. Reduce harmful blue light with this sleek 23.8" FHD monitor featuring ComfortView Plus technology.

DELL P Series P2422H\_WOST. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 2.0 / 3.2 Gen 1 (3.1 Gen 1). VESA mounting. Product colour: Black



Display		Ports & interfaces	
Display diagonal *	60.5 cm (23.8")	HDCP	✓
Display resolution *	1920 x 1080 pixels	AC (power) in	✓
HD type *	Full HD	<b>Network</b>	
Native aspect ratio *	16:9	Wi-Fi	✗
Display technology *	LCD	<b>Ergonomics</b>	
Panel type *	IPS	VESA mounting *	✓
Backlight type	LED	Panel mounting interface	100 x 100 mm
Touchscreen *	✗	Cable lock slot *	✗
Display brightness (typical)	250 cd/m <sup>2</sup>	Height adjustment *	✗
Response time	8 ms	Pivot	✗
Anti-glare screen	✓	Swivelling	✗
Screen shape *	Flat	Tilt adjustment	✗
Supported graphics resolutions	1920 x 1080 (HD 1080)	Tilt angle range	0 - 0°
Supported video modes	480p, 576p, 720p, 1080i, 1080p	On Screen Display (OSD)	✓
Aspect ratio	16:9	Plug and Play	✓
Contrast ratio (typical) *	1000:1	LED indicators	Power
Maximum refresh rate *	60 Hz	<b>Power</b>	
Viewing angle, horizontal	178°	Energy efficiency class (SDR) *	C
Viewing angle, vertical	178°	Energy efficiency class (HDR) *	Not available
Display number of colours *	16.7 million colours	Energy consumption (SDR) per 1000 hours *	12 kWh
Response time (fast)	5 ms	Power consumption (typical) *	12 W
Pixel pitch	0.2745 x 0.2745 mm	Power consumption (standby) *	0.3 W
Pixel density	93 ppi	Power consumption (max)	48 W
Horizontal scan range	30 - 83 kHz	Power consumption (off)	0.2 W
Vertical scan range	50 - 76 Hz	AC input voltage	100 - 240 V
Viewable size, horizontal	52.7 cm	AC input frequency	50 - 60 Hz
Viewable size, vertical	29.6 cm	Power supply type	Internal
Viewable size diagonal	60.5 cm		
Display diagonal (metric)	60.47 cm		

<b>Display</b>		<b>Power</b>	
High Dynamic Range (HDR) supported	✘	Energy efficiency scale	A to G
Colour depth	6 bit	<b>Operational conditions</b>	
sRGB coverage (typical)	99%	Operating temperature (T-T)	0 - 40 °C
<b>Performance</b>		Storage temperature (T-T)	-20 - 60 °C
Flicker-free technology	✓	Operating relative humidity (H-H)	10 - 80%
Low Blue Light technology	✓	Storage relative humidity (H-H)	5 - 90%
<b>Multimedia</b>		Operating altitude	0 - 5000 m
Built-in speaker(s) *	✘	Non-operating altitude	0 - 12192 m
Built-in camera *	✘	<b>Packaging content</b>	
<b>Design</b>		Cables included	AC, DisplayPort, HDMI, USB, VGA
Market positioning *	Business	Quick start guide	✓
Product colour *	Black	<b>Weight &amp; dimensions</b>	
Front bezel colour	Black	Width (with stand)	537.8 mm
Heavy metals free	Hg (mercury)	Width (without stand)	537.8 mm
<b>Ports &amp; interfaces</b>		Depth (without stand)	52.1 mm
Built-in USB hub *	✓	Height (without stand)	318.5 mm
USB hub version	2.0 / 3.2 Gen 1 (3.1 Gen 1)	Weight (without stand)	3.39 kg
USB upstream port type	USB Type-B	Bezel width (side)	5.38 mm
Number of upstream ports	1	Bezel width (top)	5.38 mm
USB Type-A downstream ports quantity	4	Bezel width (bottom)	1.67 cm
VGA (D-Sub) ports quantity	1	<b>Sustainability</b>	
HDMI *	✓	Sustainability certificates	ENERGY STAR, EPEAT Gold, RoHS
HDMI ports quantity	1	Doesn't contain	PVC/BFR
HDMI version	1.4	European Product Registry for Energy Labelling (EPREL) code	550826
DisplayPorts quantity	1	<b>Logistics data</b>	
DisplayPort version	1.2	Harmonized System (HS) code	85285210
Headphone out *	✘		



5397184505182



3523210099437

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.