

# QNAP QSW-M804-4C network switch Managed 10G Ethernet (100/1000/10000) Black

**Brand :** QNAP

**Product code:** QSW-M804-4C



**Product name :** QSW-M804-4C

8x 10GbE SFP+/RJ45, 4x 10GbE SFP+, 160Gbps, 46.65 x 285 x 236.6 mm  
 QNAP QSW-M804-4C. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000), Console port: RS-232. Full duplex. MAC address table: 16000 entries, Switching capacity: 160 Gbit/s. Networking standards: IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE.... Rack mounting



<b>Management features</b>		<b>Design</b>	
Switch type *	Managed	Product colour	Black
Quality of Service (QoS) support	✓	Reset button	✓
Web-based management	✓	LED indicators	Activity, Link, Power, Speed, Status
<b>Ports &amp; interfaces</b>		Number of fans	4 fan(s)
Basic switching RJ-45 Ethernet ports type *	10G Ethernet (100/1000/10000)	Electromagnetic compatibility	CLASS A
Combo SFP ports quantity	4	Certification	FCC, CE, VCCI, BSMI, RCM, WEEE
SFP+ module slots quantity	4	<b>Performance</b>	
Console port	RS-232	Firmware upgradeable	✓
<b>Network</b>		<b>Power</b>	
Networking standards *	IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Power source *	AC
10G support *	✓	Power supply included *	✓
Full duplex	✓	AC input voltage	100 - 240 V
Flow control support	✓	AC input frequency	50 - 60 Hz
Spanning tree protocol	✓	Power consumption (max)	70 W
Auto-negotiation	✓	<b>Power over Ethernet (PoE)</b>	
VLAN support	✓	Power over Ethernet (PoE) *	✗
Virtual LAN features	Port-based VLAN	<b>Operational conditions</b>	
<b>Data transmission</b>		Operating temperature (T-T)	0 - 40 °C
Switching capacity *	160 Gbit/s	Operating relative humidity (H-H)	5 - 95%
Throughput	80 Gbit/s	<b>Weight &amp; dimensions</b>	
MAC address table *	16000 entries	Width	285 mm
Jumbo frames support	✓	Depth	236.6 mm
Jumbo frames	9000	Height	46.6 mm
<b>Security</b>		Weight	2.12 kg
DHCP features	DHCP client	<b>Packaging data</b>	
Access Control List (ACL)	✓	Cables included	AC
IGMP snooping	✓	User guide	✓
<b>Design</b>		<b>Logistics data</b>	
Rack mounting *	✓	Harmonized System (HS) code	85176990



4713213517819

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-MAY-2024. Prints or copies of Information are only valid on the printed Publication date