Epson EB-L570U data projector 5200 ANSI lumens 3LCD WUXGA (1920x1200) Black, White

Brand : Epson **Product code:** V11HA98080

Product name: EB-L570U

3LCD, 0.67", WUXGA, 5200 lumens, 16:10, speaker 10 W, 8.3 kg

Epson EB-L570U. Projector brightness: 5200 ANSI lumens, Projection technology: 3LCD, Projector native resolution: WUXGA (1920x1200). Light source type: Laser, Service life of light source: 20000 h, Service life of light source (economic mode): 30000 h. Focus: Manual, Focal length range: 20 - 31.8 mm, Aperture range (F-F): 1.5 - 1.7. Serial interface type: RS-232C. Noise level: 31 dB, Noise level (economic mode): 23 dB, High Dynamic Range (HDR) technology: High Dynamic Range 10 (HDR10)





Projector		Network	
Screen size compatibility *	1270 - 12700 mm (50 - 500")	Ethernet LAN *	×
Projection distance (wide) 1.4 Projection distance (tele) 2.4 Projector brightness * 520	1.44 - 23.84 m	Wi-Fi *	✓
	1.4 - 14.8 m 2.4 - 23.8 m 5200 ANSI lumens 3LCD	Storage	
		Card reader integrated *	×
		Features	
Projector native resolution *	WUXGA (1920x1200)	Interactive *	×
Contrast ratio (typical) *	2500000:1	Noise level (economic mode)	23 dB
Native aspect ratio *	16:10	Noise level *	31 dB
Number of colours Keystone correction, horizontal	1.07 billion colours -30 - 30°	High Dynamic Range (HDR) supported	✓
Keystone correction, vertical	-30 - 30°	High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10)
Matrix size	1.7 cm (0.67")	Multimedia	
Light source		Built-in speaker(s) *	√
Light source type *	Laser	RMS rated power	10 W
Service life of light source * Service life of light source	20000 h	Design	
(economic mode)	30000 h	Market positioning *	Business
Lens system		Product colour *	Black, White
Focus *	Manual	Power	
. 0000		. •	
Focal length range	20 - 31.8 mm	Power source *	AC
Focal length range Aperture range (F-F)	20 - 31.8 mm 1.5 - 1.7		AC 201 W
Focal length range Aperture range (F-F) Zoom capability	20 - 31.8 mm 1.5 - 1.7	Power source * Power consumption (typical) * Power consumption (standby) *	201 W 2 W
Focal length range Aperture range (F-F) Zoom capability Zoom type	20 - 31.8 mm 1.5 - 1.7 ✓ Manual	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max)	201 W
Focal length range Aperture range (F-F) Zoom capability	20 - 31.8 mm 1.5 - 1.7	Power source * Power consumption (typical) * Power consumption (standby) *	201 W 2 W
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio	20 - 31.8 mm 1.5 - 1.7 ✓ Manual 1.35 - 2.20:1	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy	201 W 2 W 260 W
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio Horizontal lens shift range	20 - 31.8 mm 1.5 - 1.7 ✓ Manual 1.35 - 2.20:1 -20 - 20%	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode)	201 W 2 W 260 W 199 W
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio Horizontal lens shift range Vertical lens shift range	20 - 31.8 mm 1.5 - 1.7 ✓ Manual 1.35 - 2.20:1 -20 - 20%	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode) AC input frequency	201 W 2 W 260 W 199 W 50/60 Hz
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio Horizontal lens shift range Vertical lens shift range	20 - 31.8 mm 1.5 - 1.7 Manual 1.35 - 2.20:1 -20 - 20% -50 - 50%	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode) AC input frequency AC adapter output voltage	201 W 2 W 260 W 199 W 50/60 Hz
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio Horizontal lens shift range Vertical lens shift range Video Analog signal format system *	20 - 31.8 mm 1.5 - 1.7 ✓ Manual 1.35 - 2.20:1 -20 - 20% -50 - 50% Not supported	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode) AC input frequency AC adapter output voltage Operational conditions	201 W 2 W 260 W 199 W 50/60 Hz 100 - 240 V
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio Horizontal lens shift range Vertical lens shift range Video Analog signal format system * Full HD *	20 - 31.8 mm 1.5 - 1.7 Manual 1.35 - 2.20:1 -20 - 20% -50 - 50% Not supported	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode) AC input frequency AC adapter output voltage Operational conditions Storage temperature (T-T)	201 W 2 W 260 W 199 W 50/60 Hz 100 - 240 V
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio Horizontal lens shift range Vertical lens shift range Video Analog signal format system * Full HD * 3D *	20 - 31.8 mm 1.5 - 1.7 Manual 1.35 - 2.20:1 -20 - 20% -50 - 50% Not supported	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode) AC input frequency AC adapter output voltage Operational conditions Storage temperature (T-T) Operating relative humidity (H-H)	201 W 2 W 260 W 199 W 50/60 Hz 100 - 240 V -10 - 60 °C 20 - 80%
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio Horizontal lens shift range Vertical lens shift range Video Analog signal format system * Full HD * 3D * Ports & interfaces	20 - 31.8 mm 1.5 - 1.7 Manual 1.35 - 2.20:1 -20 - 20% -50 - 50% Not supported X	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode) AC input frequency AC adapter output voltage Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	201 W 2 W 260 W 199 W 50/60 Hz 100 - 240 V -10 - 60 °C 20 - 80%
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio Horizontal lens shift range Vertical lens shift range Video Analog signal format system * Full HD * 3D * Ports & interfaces HDBaseT port USB 2.0 ports quantity * USB 2.0 Type-A ports quantity	20 - 31.8 mm 1.5 - 1.7 Manual 1.35 - 2.20:1 -20 - 20% -50 - 50% Not supported	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode) AC input frequency AC adapter output voltage Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth	201 W 2 W 260 W 199 W 50/60 Hz 100 - 240 V -10 - 60 °C 20 - 80% 10 - 90% 440 mm 304 mm
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio Horizontal lens shift range Vertical lens shift range Video Analog signal format system * Full HD * 3D * Ports & interfaces HDBaseT port USB 2.0 ports quantity * USB 2.0 Type-A ports quantity USB 2.0 Type-B ports quantity	20 - 31.8 mm 1.5 - 1.7 Manual 1.35 - 2.20:1 -20 - 20% -50 - 50% Not supported X 2 1 1	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode) AC input frequency AC adapter output voltage Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth Height	201 W 2 W 260 W 199 W 50/60 Hz 100 - 240 V -10 - 60 °C 20 - 80% 10 - 90% 440 mm 304 mm 122 mm
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio Horizontal lens shift range Vertical lens shift range Video Analog signal format system * Full HD * 3D * Ports & interfaces HDBaseT port USB 2.0 ports quantity * USB 2.0 Type-A ports quantity USB 2.0 Type-B ports quantity Serial interface type *	20 - 31.8 mm 1.5 - 1.7 Manual 1.35 - 2.20:1 -20 - 20% -50 - 50% Not supported X 2 1 1 RS-232C	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode) AC input frequency AC adapter output voltage Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth Height Weight *	201 W 2 W 260 W 199 W 50/60 Hz 100 - 240 V -10 - 60 °C 20 - 80% 10 - 90% 440 mm 304 mm
Focal length range Aperture range (F-F) Zoom capability Zoom type Throw ratio Horizontal lens shift range Vertical lens shift range Video Analog signal format system * Full HD * 3D * Ports & interfaces HDBaseT port USB 2.0 ports quantity * USB 2.0 Type-A ports quantity USB 2.0 Type-B ports quantity	20 - 31.8 mm 1.5 - 1.7 Manual 1.35 - 2.20:1 -20 - 20% -50 - 50% Not supported X 2 1 1	Power source * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (economy mode) AC input frequency AC adapter output voltage Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth Height	201 W 2 W 260 W 199 W 50/60 Hz 100 - 240 V -10 - 60 °C 20 - 80% 10 - 90% 440 mm 304 mm 122 mm

Packaging content

Batteries included
Cables included
AC



8715946714912

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.