

TP-Link Archer AX3000 Dual-Band Wi-Fi 6 Air Router

Brand : TP-Link Product family: Archer Product code: ARCHER AIR R5

Product name : AX3000 Dual-Band Wi-Fi 6 Air Router

- Next-Gen Gigabit Wi-Fi 6 Speed—2402 Mbps on 5 GHz and 574 Mbps on 2.4 GHz band ensure smoother streaming and faster downloads
- Smart Antennas Uses intelligent algorithms to auto-detect your devices' locations and adjust antennas' direction for all-round stable signals
- Ultra-Low Latency—Enables more responsive gaming and video chatting
- TP-Link HomeShield Enhanced security defends against the latest cyber threats
- $\hbox{-} \ Easy Mesh-Compatible Works with Easy Mesh-compatible routers to create a whole home seamless mesh network$
- Flexible Installation Easy to stick or mount on the wall with 3M adhesives and the attached plastic bracket

AX3000, Wi-Fi 6, 2.4/5 GHz, 574 + 2402 Mbps, 1x Gigabit WAN, 1x Gigabit, 210 x 148 x 10.8 mm





WAN connection		Management features	
Ethernet WAN *	✓	WPS push button	✓
DSL WAN *	X	Security	
SIM card slot * 3G/4G USB modem compatibility *	×	Security algorithms	WPA, WPA-PSK, WPA2, WPA2-PSK, WPA3
WAN connection type	RJ-45	Guest access	✓
Wireless LAN features		Protocols	
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	DHCP server	✓
Top Wi-Fi standard *	Wi-Fi 6 (802.11ax)	Supported network protocols	IPv4, IPv6
,	2976 Mbit/s 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Design	
Wi-Fi standards		Product colour Wall mountable	White
WLAN data transfer rate (first band)	574 Mbit/s	Product type *	Tabletop router
WLAN data transfer rate (second band)	2402 Mbit/s	Packaging content	
Network		Manual	✓
Ethernet LAN *	✓	Antenna	
Ethernet LAN interface type *	Gigabit Ethernet	Antenna design *	Internal
Ethernet LAN data rates	10,100,1000 Mbit/s	Features	
Number of guest networks (2.4 GHz)	1	Certification	FCC, CE, RoHS
Number of guest networks (5 GHz)	1	Power	
Ports & interfaces		Power source type *	USB
Ethernet LAN (RJ-45) ports *	1	Operational conditions	
USB port * USB charging port	1	Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -40 - 60 °C
Management features		Operating relative humidity (H-H)	10 - 90%
Quality of Service (QoS) support	✓	Storage relative humidity (H-H)	5 - 90%
Reset button	✓	Weight & dimensions	
		Width Depth Height	148 mm 10.8 mm 210 mm

Packaging data	
Package type	Box





4895252500653

4895252500660

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.