*ii*yama

iiyama ProLite T1931SR-B1S computer monitor 48.3 cm (19") 1280 x 1024 pixels SXGA LCD Touchscreen Black

Brand : iiyama   **Product family:** ProLite   **Product code:** T1931SR-B1S

Product name : T1931SR-B1S

- IPS
- serial resistive
- VGA x1
- HDMI x1
- DisplayPort x1
PROLITE T1931SR-B1S 19" Touchscreen with 5-Wire Resistive Touch Technology

iiyama ProLite T1931SR-B1S computer monitor 48.3 cm (19") 1280 x 1024 pixels SXGA LCD Touchscreen Black:

The T1931SR-B1S is based on 5-wire resistive touch technology. The price / performance ratio is ideal for the budget conscious user while quality and performance are certainly not compromised. The display includes both analogue (VGA) and digital inputs (HDMI and DisplayPort) with touchscreen connectivity via USB offering great flexibility. The flexible stand can be positioned at several angels creating a comfortable and ergonomic user experience and the integrated cable management system hides all the cables and electrical wires giving a neat and cable-free workspace. The T1931SR-B1S can be used in a variety of environments, especially recommended for shops, restaurants and industrial purposes.

Display

Display diagonal *	48.3 cm (19")
Display resolution *	1280 x 1024 pixels
HD type *	SXGA
Native aspect ratio *	5:4
Display technology *	LCD
Panel type *	IPS
Touchscreen *	✔
Touchscreen technology	Resistive
Display brightness (typical)	250 cd/m²
Response time	14 ms
Screen shape *	Flat
Contrast ratio (typical) *	1000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	16.7 million colours
Pixel pitch	0.293 x 0.293 mm
Horizontal scan range	31.5 - 80 kHz
Viewable size, horizontal	37.5 cm
Viewable size, vertical	30 cm

Performance

NVIDIA G-SYNC *	✘
AMD FreeSync *	✘

Multimedia

Built-in speaker(s) *	✔
Built-in camera *	✘
Number of speakers	2
RMS rated power	2 W

Design

Market positioning *	Business
Product colour *	Black
International Protection (IP) code	IP54
Certification	CE, EAC, RoHS, ErP, WEEE, cULus, VCCI, REACH, UKCA

Ports & interfaces

HDCP	✔

Ergonomics

VESA mounting *	✔
Panel mounting interface	100 x 100 mm
Cable management	✔
Cable lock slot *	✔
Cable lock slot type	Kensington
Height adjustment *	✘
Tilt angle range	90 - 5°
On Screen Display (OSD)	✔
On Screen Display (OSD) languages	Traditional Chinese, German, English, Estonian, French, Italian, Japanese
Number of OSD languages	7

Power

Energy efficiency class (SDR) *	E
Energy consumption (SDR) per 1000 hours *	13 kWh
Power consumption (typical) *	20 W
Power consumption (standby) *	1.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G

Packaging content

Cables included	AC, Audio, DisplayPort, HDMI, USB
Quick start guide	✔

Weight & dimensions

Width (with stand)	432 mm
Depth (with stand)	239.5 mm
Height (with stand)	431.5 mm
Weight (with stand)	6 kg

Ports & interfaces			Packaging data	
Built-in USB hub *	✘		Package width	530 mm
USB Touch port	✔		Package depth	190 mm
USB Touch ports quantity	1		Package height	495 mm
VGA (D-Sub) ports quantity	1		Package weight	8 kg
HDMI *	✔		Package type	Box
HDMI ports quantity	1		**Sustainability**	
DisplayPorts quantity	1		European Product Registry for Energy Labelling (EPREL) code	1554894

4948570122172