

Gigabyte Z790 AORUS PRO X Motherboard - Supports Intel 14th Gen CPUs, 18+1+2 phases VRM, up to 8266MHz DDR5 (OC), 1xPCIe 5.0 + 4xPCIe 4.0 M.2, Wi-Fi 7, 5GbE LAN, USB 3.2 Gen 2x2

Brand : Gigabyte

Product code: Z790 AORUS PRO X

Product name : Z790 AORUS PRO X Motherboard - Supports Intel 14th Gen CPUs, 18+1+2 phases VRM, up to 8266MHz DDR5 (OC), 1xPCIe 5.0 + 4xPCIe 4.0 M.2, Wi-Fi 7, 5GbE LAN, USB 3.2 Gen 2x2



- LGA 1700: Supports Intel Core 13th and next-gen processors
 - Digital direct 18+1+2 phases VRM solution
 - Full support up to DDR5-8266
 - 1*PCIe 5.0 x4 and 4*PCIe 4.0 x4 M.2 Connectors
 - VRM Thermal Armor Advanced & M.2 Thermal Guard XL
 - DIY-Friendly Design: Quick Release & Screwless Design for M.2 modules and graphics card
- Intel Z790, 4 x DDR5, 8266 MHz, Wi-Fi 7, 1 x RJ-45, 1 x HDMI, ATX, Bluetooth 5.3

Gigabyte Z790 AORUS PRO X Motherboard - Supports Intel 14th Gen CPUs, 18+1+2 phases VRM, up to 8266MHz DDR5 (OC), 1xPCIe 5.0 + 4xPCIe 4.0 M.2, Wi-Fi 7, 5GbE LAN, USB 3.2 Gen 2x2:

Elevate your computing experience with GIGABYTE's renowned motherboard series: AORUS, AERO, and GIGABYTE. Featuring innovative designs and advanced features, these boards offer exceptional performance and reliability. Whether you're a gamer, content creator, or professional, our series cater to your needs, ensuring uncompromising quality and cutting-edge technology.



Processor		Rear panel I/O ports	
Processor manufacturer *	Intel	DisplayPort version	1.2
Processor socket *	LGA 1700	Headphone outputs	1
Compatible processor series *	Intel® Celeron®, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9, Intel® Pentium® Gold	Microphone in	✓
Maximum number of SMP processors	1	S/PDIF out port	✓
Supported processor sockets	LGA 1700	Digital audio optical out	1
Maximum internal memory supported by processor	192 GB	Thunderbolt ports quantity	2
Memory		WiFi-AP antenna jack	2
Supported memory types *	DDR5-SDRAM	Network	
Number of memory slots *	4	Ethernet LAN	✓
Memory slots type	DIMM	Ethernet interface type	2.5 Gigabit Ethernet
Memory channels	Dual-channel	LAN controller	Realtek RTL8126
ECC	✓	Wi-Fi *	✓
Non-ECC	✓	Top Wi-Fi standard	Wi-Fi 7 (802.11be)
Supported memory clock speeds MHz	4000,4800,5200,5400,5600,5800,6000,6200,6400,6600,6800,7000,7200,7400,7600,7800,7900,7950,8000,8200,8266	Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax), Wi-Fi 6E (802.11ax), Wi-Fi 7 (802.11be)
Supported memory clock speed (max)	8266 MHz	Bluetooth	✓
Maximum internal memory *	192 GB	Bluetooth version	5.3
Unbuffered memory	✓	Features	
Storage controllers		Motherboard chipset *	Intel Z790
Supported storage drive types	HDD & SSD	Audio chip	Realtek ALC1220-VB
Supported storage drive interfaces *	M.2, SATA III	Audio output channels *	7.1 channels
Number of HDDs supported	4	Product colour	White
Number of storage drives supported	9	PC health monitoring	Fan, Noise, Temperature, Voltage, Water cooling
RAID support	✓	Component for *	PC
RAID levels	0, 1, 5, 10	Motherboard form factor *	ATX
Graphics		Motherboard chipset family *	Intel
Parallel processing technology support *	Not supported	Windows operating systems supported	Windows 11 x64
Maximum resolution	4096 x 2304 pixels	Expansion slots	
HDCP	✓	PCI Express x16 (Gen 3.x) slots	1
DirectX version	12.0		
Discrete graphics support	✓		
Internal I/O			
USB 2.0 connectors *	2		

Internal I/O		Expansion slots	
USB 3.2 Gen 1 (3.1 Gen 1) connectors *	1	PCI Express x16 (Gen 4.x) slots	1
USB 3.2 Gen 2x2 connectors	1	PCI Express x16 (Gen 5.x) slots	1
Number of SATA III connectors *	4	Number of M.2 (M) slots	5
Front panel audio connector	✓	BIOS	
Front panel connector	✓	BIOS type *	UEFI AMI
ATX Power connector (24-pin)	✓	BIOS memory size	256 Mbit
Number of EATX power connectors	2	ACPI version	5.0
CPU fan connector	✓	Clear CMOS jumper	✓
Number of chassis fan connectors	6	Clear CMOS button	✓
EPS power connector (8-pin)	✓	Desktop Management Interface (DMI) version	2.7
TPM connector	✓	System Management BIOS (SMBIOS) version	2.7
Thunderbolt headers	2	Logistics data	
12V power connector	✓	Country of origin	Taiwan
RGB LED pin header	✓	Products per shipping (inner) case	1 pc(s)
Rear panel I/O ports		Battery	
USB 2.0 ports quantity *	2	Battery weight	3 g
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	4	Lithium weight per battery	0.07 g
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity *	2	Number of battery cells	1
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity *	1	Battery technology	Lithium-Manganese Dioxide (LiMnO2)
USB 3.2 Gen 2x2 Type-C ports quantity	1	Battery type	CR2032
Ethernet LAN (RJ-45) ports *	1	Packaging data	
HDMI ports quantity *	1	Package width	335 mm
HDMI version	2.0	Package depth	270 mm
DisplayPorts quantity	1	Package height	80 mm
		Package weight	2.59 kg
		Weight & dimensions	
		Width	305 mm
		Depth	244 mm
		Height	35 mm
		Packaging content	
		Cables included	SATA
		Batteries included	✓
		Antenna included	✓
		Bundled software	Norton Internet Security LAN bandwidth management software
		Technical details	
		Warranty period	3 year(s)



4719331857608

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 08-MAY-2024. Prints or copies of Information are only valid on the printed Publication date