



## TP-Link 5-Port Gigabit Easy Smart Switch with 4-Port PoE+


**Brand :** TP-Link

**Product code:** TL-SG105MPE

**Product name :** 5-Port Gigabit Easy Smart Switch with 4-Port PoE+



- Five 10/100/1000Mbps RJ45 ports
  - Equipped with four 802.3af/at PoE+ ports with up to 30W for each port, data, and power can be transferred on one single cable
  - Supports PoE power up to 120 W for all PoE ports
  - Provides network monitoring, traffic prioritization, VLAN features, and PoE Auto Recovery
  - Simple network set-up on top of plug-and-play connectivity
  - Web-based user interface and Easy Smart Configuration Utility simplify configuration
  - Fanless design lowers energy consumption and eliminates operating noise
- 5 x 10/100/1000Mbps RJ45, 10 Gbps, 7.44 Mpps, 2K MAC, 16 KB Jumbo, 99.8 x 98 x 25 mm



Management features		Design	
Switch layer	L2	Product colour	Black
Web-based management	✓	<b>Power</b>	
<b>Ports &amp; interfaces</b>		Power source *	DC/PoE
Basic switching RJ-45 Ethernet ports quantity *	5	Power supply included *	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	AC input voltage	100 - 240 V
<b>Network</b>		AC input frequency	50 - 60 Hz
Networking standards *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x	DC input voltage	53.5 V
10G support *	✗	Power consumption (max)	137.01 W
Port mirroring	✓	<b>Power over Ethernet (PoE)</b>	
Broadcast storm control	✓	Power over Ethernet (PoE) *	✓
Rate limiting	✓	Total Power over Ethernet (PoE) budget	120 W
<b>Data transmission</b>		<b>Operational conditions</b>	
Switching capacity *	10 Gbit/s	Operating temperature (T-T)	0 - 40 °C
Forwarding rate	7.44 Mpps	Storage temperature (T-T)	-40 - 70 °C
MAC address table *	2000 entries	Operating relative humidity (H-H)	10 - 90%
Static route	✓	Storage relative humidity (H-H)	5 - 95%
Jumbo frames support	✓	<b>Weight &amp; dimensions</b>	
Jumbo frames	16	Width	99.8 mm
<b>Security</b>		Depth	98 mm
IGMP snooping	✓	Height	25 mm
Loop protection	✓	<b>Packaging data</b>	
<b>Design</b>		Cables included	LAN (RJ-45)
Rack mounting *	✗		




4895252500271



0840030708527



840030708527



4895252500264

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.