

Lindy 2m Active DisplayPort 1.4 to HDMI 8K60 Cable

Brand: Lindy Product code: 40931

Product name : 2m Active DisplayPort 1.4 to HDMI 8K60

Cable

- Connect a DisplayPort equipped device to a 8K HDMI display or projector
- Supports high quality resolutions up to 8K@60Hz or 4K@120Hz
- High Dynamic Range support provides deeper blacks, brighter whites and a wider colour gamut
- Active chipset for enhanced compatibility with various graphic cards
- 2 year warranty

2m Active DisplayPort 1.4 to HDMI 8K60 Cable

Lindy 2m Active DisplayPort 1.4 to HDMI 8K60 Cable. Cable length: 2 m, Connector 1: HDMI Type A (Standard), Connector 2: DisplayPort. Cable diameter: 5.5 mm, Connector 1 dimensions (WxDxH): $60 \times 20 \times 8 \text{ mm}$, Connector 2 dimensions (WxDxH): $50 \times 20 \times 8 \text{ mm}$. Package type: Polybag





| _ | | | |
|------------------------------------|------------------------|--------------------------------|------------------------------------------------------------|
| Features | | Features | |
| Connector 1 form factor | Straight | Bend radius (min) | 3.3 cm |
| Connector 2 form factor | Straight | Product colour | Black |
| Connector contacts plating | Gold | Conductor material | Tinned copper |
| Cable length * | 2 m | Nominal attenuation | 100MHz-10GHz ≤ 24dB |
| Connector 1 * | HDMI Type A (Standard) | Chipset | VM7100 |
| Connector 2 * | DisplayPort | Jacket material | Nylon/Polyvinyl Chloride (PVC) |
| Connector 1 gender * | Male | Cable type | Round cable |
| Connector 2 gender * | Male | Certification | CE, UKCA, FCC, RoHS, REACH, UL & California Proposition 65 |
| HDMI version | 2.1 | | |
| DisplayPort version | 1.4 | Operational conditions | |
| High Dynamic Range (HDR) | √ | Operating temperature (T-T) | -20 - 40 °C |
| supported | | Storage temperature (T-T) | -40 - 80 °C |
| Maximum resolution | 7680 x 4320 pixels | | |
| Supported graphics resolutions | 7680 x 4320 | Weight & dimensions | |
| Supported video modes | 4320p | Cable diameter | 5.5 mm |
| Data transfer rate | 48 Gbit/s | Connector 1 dimensions (WxDxH) | 60 x 20 x 8 mm |
| Maximum refresh rate | 60 Hz | Connector 2 dimensions (WxDxH) | 50 x 20 x 8 mm |
| Refresh rate at maximum resolution | 60 Hz | Packaging data | |
| | | Package type | Polybag |



4002888409315

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.