



## ASUS ROG STRIX 1200W Gold Aura Edition power supply unit 20+4 pin ATX Black

**Brand :** ASUS

**Product family:** ROG

**Product code:** 90YE00P0-B0NA00

**Product name :** ROG STRIX 1200W Gold Aura Edition



ROG STRIX 1200W Gold Aura Edition RGB power supply (1200 Watt, Aura Sync RGB lighting, 80+ Gold certification, Axial-Tech fan, ATX 3.0 compatible, PCIe 5.0 ready)

ASUS ROG STRIX 1200W Gold Aura Edition. Total power: 1200 W, AC input voltage: 100 - 240 V, Combined power (+3.3V): 120 W. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 60 cm, SATA power cable length: 400,520,640 mm. Purpose: PC, 80 PLUS certification: 80 PLUS Gold, Bearing technology: Ball bearing. Product colour: Black, Cooling type: Active, Fan diameter: 13.5 cm. Cables included: AC, CPU, PCIe, Peripheral (Molex), SATA



Power		Ports & interfaces	
Total power *	1200 W	CPU power connector (4+4 pin)	✓
AC input voltage *	100 - 240 V	CPU power cable length	65 cm
Combined power (+3.3V)	120 W	ATX power connector (20+4 pin)	✓
Combined power (+12V)	1200 W	Cabling type	Fully-Modular
Combined power (+5V)	120 W	<b>Performance</b>	
Combined power (-12V)	3.6 W	80 PLUS certification *	80 PLUS Gold
Combined power (+5Vsb)	15 W	Purpose *	PC
Max output current (+3.3V)	22 A	ATX version	3.0
Max output current (+12V)	100 A	Silent mode	✓
Max output current (+5V)	22 A	Bearing technology	Ball bearing
Max output current (-12V)	0.3 A	<b>Design</b>	
Max output current (+5Vsb)	3 A	Product colour	Black
Efficiency	80%	Cooling type	Active
Power protection features	Over power, Over voltage, Overcharge, Overheating, Short circuit, Under voltage	Fan diameter	13.5 cm
<b>Ports &amp; interfaces</b>		Number of fans	1 fan(s)
Motherboard power connector *	20+4 pin ATX	Illumination	✓
Motherboard power cable length	60 cm	On/off switch	✓
Number of SATA power connectors	5	<b>Packaging content</b>	
SATA power cable length	400,520,640 mm	Cables included	AC, CPU, PCIe, Peripheral (Molex), SATA
Peripheral (Molex) power connectors (4-pin) *	4	<b>Weight &amp; dimensions</b>	
Peripheral (Molex) power cable length	150,300,400,550 mm	Width	180 mm
PCI Express power connectors (8-pin)	4	Depth	150 mm
PCI Express power connectors (16-pin)	1	Height	86 mm
PCI Express power cable length	70 cm	Weight	3.23 kg
<b>Packaging data</b>		Manual	✓
		Package width	386 mm
		Package depth	242 mm
		Package height	129 mm
		Package weight	3.73 kg
		Package type	Box



4711081721475

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 09-MAY-2024. Prints or copies of Information are only valid on the printed Publication date