

Samsung QH50C Digital signage flat panel 127 cm (50") LED Wi-Fi 700 cd/m² 4K Ultra HD Black Built-in processor Tizen 24/7

Brand : Samsung

Product code: LH50QHCEBGXEN

Product name : QH50C



Samsung QH50C. Product design: Digital signage flat panel. Display diagonal: 127 cm (50"), Display technology: LED, Display resolution: 3840 x 2160 pixels, Display brightness: 700 cd/m², HD type: 4K Ultra HD. Wi-Fi. Operating hours (hours/days): 24/7. Operating system installed: Tizen. Product colour: Black



Display		Design	
LED backlighting type	Edge-LED	Panel mounting interface	200 x 200 mm
Display diagonal *	127 cm (50")	Performance	
Display technology *	LED	Operating hours (hours/days)	24/7
Display resolution *	3840 x 2160 pixels	Power	
Display brightness *	700 cd/m ²	Power consumption (typical) *	108 W
HD type *	4K Ultra HD	Power consumption (standby) *	0.5 W
Native aspect ratio	16:9	Energy efficiency class (SDR)	G
Response time	8 ms	Energy consumption (SDR) per 1000 hours	108 kWh
Contrast ratio (typical)	4000:1	Energy efficiency scale	A to G
Viewing angle, horizontal	178°	Computer system	
Viewing angle, vertical	178°	Computer system *	✓
Display number of colours	16.7 million colours	Computer system type	System on Chip (SoC)
Pixel pitch	0.285 x 0.285 mm	Built-in processor *	✓
Active display area (W x H)	1095.5 x 616.4 mm	Processor manufacturer	ARM
Display diagonal (metric)	125 cm	Processor family	ARM Cortex
Frame width	11.5 mm	Processor model	A73
Haze rate	25%	Processor frequency	1.6 GHz
Ports & interfaces		Processor cores	4
HDMI ports quantity *	3	Internal memory	16 GB
HDMI version	2.2	Operating system installed	Tizen
DisplayPorts quantity *	1	Operating system version	Tizen 7.0
DisplayPorts in	1	Weight & dimensions	
USB port *	✓	Display width	1124.1 mm
USB ports quantity	2	Display depth	28.5 mm
USB version	2.0	Display height	644.8 mm
Ethernet LAN *	✓	Display weight	12.4 kg
Ethernet LAN (RJ-45) ports	1	Packaging data	
Wi-Fi *	✓	Package width	1246 mm
RS-232C	✓	Package depth	131 mm
Audio		Package height	761 mm
Built-in speaker(s) *	✓		
Number of built-in speakers	2		

Audio		Packaging data	
RMS rated power	10 W	Package weight	15.5 kg
Design		Operational conditions	
Product design *	Digital signage flat panel	Operating temperature (T-T)	0 - 40 °C
Product colour *	Black	Operating relative humidity (H-H)	10 - 80%
VESA mounting *	✓		



8806094977974

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 09-MAY-2024. Prints or copies of Information are only valid on the printed Publication date