

PHILIPS

Philips 27M1N3200ZS/00 computer monitor 68.6 cm (27") 1920 x 1080 pixels Full HD LED Black

Brand : Philips

Product code: 27M1N3200ZS/00

Product name : 27M1N3200ZS/00



Gaming Monitor 27M1N3200ZS Full HD gaming monitor

Philips 27M1N3200ZS/00 computer monitor 68.6 cm (27") 1920 x 1080 pixels Full HD LED Black:

This gaming monitor is an all-around display for intense PC games. FreeSync, a rapid 165 Hz refresh rate and 1 ms response time deliver smooth gameplay. The virtually frameless display with Ultra Wide-Color enhances the immersive visual experience.

Philips 27M1N3200ZS/00. Display diagonal: 68.6 cm (27"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LED, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. VESA mounting. Product colour: Black



Display

Display diagonal *	68.6 cm (27")
Display resolution *	1920 x 1080 pixels
HD type *	Full HD
Native aspect ratio *	16:9
Display technology *	LED
Panel type *	IPS
Backlight type	W-LED
Display brightness (typical)	250 cd/m ²
Response time	4 ms
Anti-glare screen	✓
Screen shape *	Flat
Supported graphics resolutions	1920 x 1080 (HD 1080)
Supported video modes	1080p
Aspect ratio	16:9
Contrast ratio (typical) *	1100:1
Dynamic contrast ratio marketing name	Mega Infinity DCR
Maximum refresh rate *	165 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	16.7 million colours
Response time (fast)	1 ms
Pixel pitch	0.3114 x 0.3114 mm
Pixel density	81.59 ppi
Vertical scan range	48 - 165 Hz
Viewable size, horizontal	59.8 cm
Viewable size, vertical	33.6 cm
Display diagonal (metric)	68.5 cm
DDC/CI	✓
Haze rate	25%
Surface hardness	3H
sRGB coverage (typical)	122%

Ergonomics

Cable lock slot *	✓
Cable lock slot type	Kensington
Tilt adjustment	✓
Tilt angle range	-5 - 20°
On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Number of OSD languages	21
Plug and Play	✓
LED indicators	Operation, Stand-by

Power

Energy efficiency class (SDR) *	E
Energy consumption (SDR) per 1000 hours *	21 kWh
Power consumption (typical) *	28.2 W
Power consumption (standby) *	0.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power supply type	Internal
Energy efficiency scale	A to G

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Operating altitude	0 - 3658 m
Non-operating altitude	0 - 12192 m

Packaging content

Stand included	✓
----------------	---

Display		Packaging content	
NTSC coverage (typical)	107%	Cables included	DisplayPort, HDMI, Power
Adobe RGB coverage	90.4%	Manual	✓
Display sRGB	✓	Weight & dimensions	
Performance		Width (with stand)	612 mm
AMD FreeSync *	✓	Depth (with stand)	193 mm
AMD FreeSync type	FreeSync Premium	Height (with stand)	449 mm
Component video sync	Separate sync	Weight (with stand)	5.15 kg
Flicker-free technology	✓	Width (without stand)	612 mm
Low input lag	✓	Depth (without stand)	55 mm
Design		Height (without stand)	365 mm
Market positioning *	Gaming	Weight (without stand)	3.7 kg
Product colour *	Black	Packaging data	
Detachable stand	✓	Package width	780 mm
Ports & interfaces		Package depth	186 mm
HDMI *	✓	Package height	525 mm
HDMI ports quantity	2	Package weight	9.28 kg
HDMI version	2.0	Sustainability	
DisplayPorts quantity	1	Sustainability compliance	✓
DisplayPort version	1.2	Sustainability certificates	CB, Federal Communications Commission (FCC), ICES, RoHS, TUV
Audio output	✓	Doesn't contain	Mercury, PVC/BFR
HDCP	✓	Other features	
HDCP version	1.4/2.2	Exterior finish type	Textured
Ergonomics		Picture enhancement	SmartImage game
VESA mounting *	✓	Recyclable packaging material	100%
Panel mounting interface	100 x 100 mm	Regulatory Approvals	CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV/ISO9241-307; TUV-BAUART
Wall mountable	✓	EasyRead mode	✓
		LowBlue mode	✓
		Mean time between failures (MTBF)	50000 h



8712581802738

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 09-MAY-2024. Prints or copies of Information are only valid on the printed Publication date