

## Biamp Desono DX-S5 Two-Way High Output Coaxial 5-inch Surface Mount Loudspeaker ClickMount Black

**Brand :** Biamp

**Product family:** Desono

**Product code:** 910.0107.900

**Product name :** DX-S5 Two-Way High Output Coaxial 5-inch Surface Mount Loudspeaker ClickMount Black



DX-S5 Two-Way High Output Coaxial 5-inch Surface Mount Loudspeaker ClickMount Black

[Biamp Desono DX-S5 Two-Way High Output Coaxial 5-inch Surface Mount Loudspeaker ClickMount Black:](#)

The Desono™ DX surface mount loudspeakers provide high efficiency, high output, high intelligibility and low distortion in an attractive design. These loudspeakers install quickly and have the same components and voicing as the DX ceiling loudspeakers. The DX surface mount loudspeakers are equipped with a built-in 70 V/100 V autotransformer and low impedance input.

Easily outperforming loudspeakers of a larger size format, the DX-S5 is ideal for installations where space is a premium. With a modern appearance that merges well in most environments, combined with weather-resistant capability suitable for direct outdoor use, the DX-S5 can be used in a wide variety of speech and music applications.

Certified for use with Zoom software.

Loudspeakers		Amplifier	
Speaker type *	2-way	Amplifier *	✗
Speaker placement *	Surface-mountable	Recommended amplifier power (max)	200 W
Tweeter	✓	Recommended amplifier power (min)	100 W
Number of tweeter drivers	1	<b>Ports &amp; interfaces</b>	
Tweeter diameter	2.5 cm	Connectivity technology *	Wired
Tweeter diameter (imperial)	2.54 cm (1")	Bluetooth *	✗
Woofers	✓	<b>Weight &amp; dimensions</b>	
Number of woofer drivers	1	Width	180 mm
Woofer diameter	12.7 cm	Depth	185 mm
Woofer diameter (imperial)	12.7 cm (5")	Height	280 mm
<b>Audio</b>		Weight	4.7 kg
RMS rated power *	100 W	<b>Packaging data</b>	
Frequency range	75 - 20000 Hz	Package width	629.9 mm
Impedance	6 Ω	Package depth	340.4 mm
Sensitivity	92 dB	Package height	259.1 mm
Crossover frequency	1500 Hz	Package weight	9.3 kg
Sound pressure level (max)	109 dB	<b>Packaging content</b>	
Input sensitivity	2830 mV	Mounting brackets included	✓
<b>Performance</b>		<b>Logistics data</b>	
Recommended usage *	Universal	Export Control Classification Number (ECCN)	EAR99
Product colour *	Black	Harmonized System (HS) code	8518210000
International Protection (IP) code	IP54	<b>Other features</b>	
Suitable for outdoor use	✓	Country of origin	China

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-JUN-2024. Prints or copies of Information are only valid on the printed Publication date