## DeepCool PK750D power supply unit 750 W 20+4 pin ATX Black

**Brand**: DeepCool **Product code**: R-PK750D-FA0B-UK

**Product name:** PK750D

750 W, 80 PLUS Bronze, 120 mm, ATX12V 2.4

DeepCool PK750D. Total power: 750 W, AC input voltage: 100 - 240 V, Combined power (+3.3V): 120 W. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 50 cm, SATA power cable length: 400,500,600,700 mm. Purpose: PC, 80 PLUS certification: 80 PLUS Bronze, Bearing technology: HDB. Product colour: Black, Fan diameter: 12 cm, Number of fans: 1 fan(s). Cables included:





Power		Ports & interfaces	
Total power * AC input voltage *	750 W 100 - 240 V	PCI Express power connectors (6+2 pin)	2
Combined power (+3.3V) Combined power (+12V) Combined power (+5V)	120 W 750 W 120 W	PCI Express power cable length ATX power connector (20+4 pin) Cabling type	62 cm ✓ Non-Modular
Combined power (-12V)	3.6 W	Performance	
Combined power (+5Vsb)  Max output current (+3.3V)  Max output current (+12V)  Max output current (+5V)  Max output current (-12V)	12.5 W 20 A 62.5 A 20 A 0.3 A	80 PLUS certification * Purpose * ATX version Bearing technology Mean time between failures (MTBF)	80 PLUS Bronze PC 2.4 HDB 100000 h
Max output current (+5Vsb) Hold time	2.5 A 16 ms	Design	
Efficiency  Power protection features	85% Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage	Product colour Fan diameter Number of fans On/off switch	Black 12 cm 1 fan(s) ✓
Ports & interfaces		Operational conditions	
Motherboard power connector * Motherboard power cable length	nerboard power cable length 50 cm	Operating temperature (T-T)	0 - 40 °C
Number of SATA power connectors		Packaging content	
SATA power cable length	400,500,600,700 mm	Cables included	AC
Peripheral (Molex) power connectors (4-pin) *	1	Weight & dimensions	150
Peripheral (Molex) power cable length	400,500,600,700 mm	Width Depth	150 mm 140 mm
EPS power connector (4+4 pin)	✓	Height	86 mm

Packaging data	
Package type	Box

