

Epson TM-m10 203 x 203 DPI Wired & Wireless Thermal POS printer

Brand : Epson

Product code: C31CE74112AO

Product name : TM-m10



2" receipt printer, thermal, 203 dpi, bluetooth, black, UK, 900g

[Epson TM-m10 203 x 203 DPI Wired & Wireless Thermal POS printer:](#)



POS printing reimagined with a compact, sleek, 2" receipt printer

The industry's smallest POS 2" receipt printer in its class, the TM-m10 saves valuable counter space, while offering the freedom to print receipts from virtually any mobile device and/or desktop PC. Ideal for most environments, its modular casing can be easily switched from a top-load to front-load configuration. This versatile printer ensures simple integration with existing mobile POS environments, intuitive functionality and advanced connectivity. The TM-m10 is the first of its kind designed exclusively for small businesses. Featuring ePOS™ print technology, it works with iOS®, Android™ and Windows® mobile devices and desktop PCs, and offers fast, easy setup.

Printing		Design	
Colour	✗	Product colour *	Black
Maximum resolution	203 x 203 DPI	Power	
Print speed	150 mm/sec	Power consumption (printing)	15.9 W
Print technology *	Thermal	Input current	1.5 A
Type *	POS printer	Power supply type	DC
Paper handling		Operational conditions	
Maximum roll diameter	6 cm	Operating temperature (T-T)	5 - 45 °C
Supported paper width	57.5 mm	Storage temperature (T-T)	-20 - 60 °C
Maximum printing width	5.25 cm	Operating relative humidity (H-H)	10 - 90%
		Storage relative humidity (H-H)	10 - 90%
Ports & interfaces		System requirements	
USB port *	✓	Mobile operating systems supported	Android, Windows Mobile, iOS
USB 2.0 ports quantity	1	Weight & dimensions	
Bluetooth	✓	Width	102 mm
Bluetooth version	3.0+HS	Depth	102 mm
Connectivity technology *	Wired & Wireless	Height	102 mm
Standard interfaces	Bluetooth, USB 2.0	Weight	900 g
Network		Packaging data	
Ethernet LAN *	✗	Cables included	USB
Wi-Fi *	✗	Packaging content	
Features		Drivers included	✓
Built-in barcodes *	CODABAR (NW-7), Code 39, Code 93, EAN13, EAN8, GS1 DataBar, GS1-128, ITF, UPC-A, UPC-E	Quick start guide	✓
Sound pressure level (printing)	55 dB	AC adapter included	✓
Mean time between failures (MTBF)	360000 h	Other features	
Cutter	✓	Buffer size	4 KB
Autocutter durability	1 million cuts	LED indicators	✓
Built-in sensors details	PaperEnd, CoverOpen		
Safety	EMI FCC Class A, CAN ICES-3(A)/NMB-3(A), UL60950-1/CSA C22.2 No.60950-1		



8715946609126

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 10-JUN-2024. Prints or copies of Information are only valid on the printed Publication date