

Gigabyte GP-AP750GM power supply unit 750 W 20+4 pin ATX ATX Black

Brand : Gigabyte

Product code: 28200-AP75GM-1EUR

Product name : GP-AP750GM

- Fully Modular Design
- High quality 100% Japanese Capacitors
- 135mm 2 ball bearing smart fan with fan stop function
- 80 PLUS Gold certified: above 90% efficiency at 50% load
- Single +12V rail
- OCP/OTP/OVP/OPP/UVP/SCP protection
- 10 years warranty (Adjusted according to different regions)

Fully Modular, 750 W, ATX 12V v2.31, Active PFC, 100 - 240 V, 47 - 63 Hz, 10 A, 150 x 160 x 86 mm
 Gigabyte GP-AP750GM. Total power: 750 W, AC input voltage: 100 - 240 V, AC input frequency: 47 - 63 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 65 cm, SATA power cable length: 450,550,650,750 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Fan diameter: 13.5 cm, Number of fans: 1 fan(s). Width: 150 mm, Depth: 160 mm, Height: 86 mm



Power		Ports & interfaces	
Total power *	750 W	EPS power connector (8-pin)	✓
AC input voltage *	100 - 240 V	PCI Express power connectors (6+2 pin)	6
AC input frequency	47 - 63 Hz	CPU power connector (4+4 pin)	✓
Input current	10 A	ATX power connector (20+4 pin)	✓
Power factor	0.9	Floppy drive power connector	2
Power Factor Correction (PFC) type	Active	Floppy disk drive connector	✓
Combined power (+3.3V)	120 W	PCI Express connector	✓
Combined power (+12V)	744 W	Cabling type	Fully-Modular
Combined power (+5V)	120 W	Performance	
Combined power (-12V)	3.6 W	80 PLUS certification *	80 PLUS Gold
Combined power (+5Vsb)	15 W	Purpose *	PC
Max output current (+3.3V)	20 A	Power supply unit (PSU) form factor *	ATX
Max output current (+12V)	62 A	ATX version	2.31
Max output current (+5V)	20 A	Mean time between failures (MTBF)	100000 h
Max output current (-12V)	0.3 A	Design	
Max output current (+5Vsb)	3 A	Product colour	Black
Hold time	16 ms	Fan diameter	13.5 cm
Efficiency	90%	Number of fans	1 fan(s)
Power Good signal delay range	100 - 150 ms	Fan location	Top
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage	On/off switch	✓
Ports & interfaces		Weight & dimensions	
Motherboard power connector *	20+4 pin ATX	Width	150 mm
Motherboard power cable length	65 cm	Depth	160 mm
Number of SATA power connectors	6	Height	86 mm
SATA power cable length	450,550,650,750 mm	Logistics data	
Peripheral (Molex) power connectors (4-pin) *	6	Harmonized System (HS) code	84733020



4719331551025

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 10-JUN-2024. Prints or copies of Information are only valid on the printed Publication date