
Getac

Getac recommends Windows 11 Pro for business



S410 SEMI RUGGED Notebook

- 13th Generation Intel[®] Core™ i7 / i5 Processor
- 14" HD / FHD display with Getac sunlight readable technology (1,000 nits) and capacitive touchscreen
- Enhanced enterprise security with Intel[®] vPro[®], Windows Hello face-authentication camera, TPM 2.0, and many more multi-factor authentication options
- Versatile I/O options including Thunderbolt™ 4 and docking solutions
- Wider range of operating temperatures of -29°C ~ 63°C (-20°F ~ 145°F)



SPECIFICATIONS

Generation

Operating System Windows 11 Pro

Mobile Computing Platform

Intel[®] Core™ i5-1340P Processor Max. 4.6GHz with Intel[®] Turbo Boost Technology - 12 MB Intel[®] Smart Cache

Platform options: Intel[®] Core™ i5-1350P vPro[®] Processor Max. 4.7GHz with Intel[®] Turbo Boost Technology - 12 MB Intel[®] Smart Cache

Intel[®] Core™ i7-1360P Processor Max. 5.0GHz with Intel[®] Turbo Boost Technology - 18 MB Intel[®] Smart Cache

Intel[®] Core™ i7-1370P vPro[®] Processor Max. 5.2GHz with Intel[®] Turbo Boost Technology - 24 MB Intel[®] Smart Cache

VGA Controller

Intel[®] Iris[®] X^e Graphics [†] Intel[®] UHD Graphics Optional: NVIDIA[®] GeForce[®] GTX 1650 4GB discrete graphics controller ^{II, III, IV}

Display 14" TFT LCD HD (1366 x 768)

Protection film 1,000 nits display with Getac sunlight readable technology Optional: 14" TFT LCD HD (1366 x 768)

1000 nits display with Getac sunlight readable technology and capacitive multi-touch screen

Optional: 14" Wide Viewing Angle TFT LCD FHD (1920 x 1000 nits display with Getac sunlight readable technology

Optional: 14" Wide Viewing Angle TFT LCD FHD (1920 x

1080) 1000 nits display with Getac sunlight readable technology and capacitive multi-touch screen

Storage & Memory 8GB DDR5 Optional: 16GB / 32GB / 64GB DDR5

256GB PCIe NVMe SSD Optional: 512GB / 1TB / 2TB PCIe NVMe SSD

Optional: Multimedia bay 2nd storage: 512GB / 1TB SATA SSD

Keyboard

LED backlit membrane keyboard

Pointing Device

Fouchscreen • Optional: Capacitive multi-touch screen Touchpad - Glide touchpad with multi-touch

Expansion Slots

Optional: Smart card reader x 1

Multimedia Bay

Weight saver Optional: 1D/2D imager barcode reader ^{III} Optional: DVD super multi drive ^{III, v} Optional: Multimedia bay battery ^{III, v} Optional: Blu-Ray super multi drive ^{III, v} Optional: 2nd storage ^{III, v}

I/O Interface

Audio in/out combo x 1 DC in Jack x 1 UC IN Jack X 1 USB 3.2 Gen 1 Type-A X 1 USB 3.2 Gen 2 Type-A X 2 ThunderboltTM 4 Type-C X 1 Optional: MicroSD X 1 LAN (R145) X 1 HDM12.0 X 1 Docking concentration Docking connector x 1 Optional: 5M webcam x 1 Optional: SIM card slot x 1 (Mini-SIM, 2FF) ^{vi} Optional: Windows Hello face-authentication 5M camera (front-facing) x 1 ^{vii} Optional: RF antenna pass-through for GPS, WWAN and WLAN

Configurable I/O options :

1. Serial port (9-pin; D-sub) + VGA port (15-pin; D-sub) + 2nd LAN (RJ45) LAN (RI45) 2. Serial port (9-pin; D-sub) + VGA port (15-pin; D-sub) + PowerShare USB 3.2 Gen 1 Type-A 3. Serial port (9-pin; D-sub) + Display port + 2nd LAN (RJ45) 4. Serial port (9-pin; D-sub) + Display port + PowerShare USB 3.2 Gen 1 Type-A

Communication Interface

10/100/1000 base-T Ethernet Intel® Wi-Fi 6E AX211, 802.11ax Bluetooth (v5.3) ^{viii} Optional: Dedicated L1/L5 GPS ^{ix} Optional: 4G LTE mobile broadband with integrated GPS ^{vi.}

Optional: 5G Sub-6 with integrated L1/L5 GPS $^{\rm vi,\,ix,\,x,\,xi}$ Dual SIM (Mini-SIM 2FF and e-SIM) $^{\rm xii}$

Security Features TPM 2.0 Kensington lock Optional: Intel[®] VPro[®] Technology Optional: Fingerprint reader Optional: Fingerprint reader Optional: Smart card reader Optional: Smart card reader Optional: Windows Hello face-authentication 5M camera (front-facing)

Power

AC adapter (90W, 100-240VAC, 50/60Hz) Li-ion battery (10.8V, typical 6900mAh; min. 6600mAh) Optional: AC adapter (120W, 100-240VAC, 50/60Hz) ^{III} Optional: Multimedia bay battery (11.1V, typical 4200mAh; min. 3980mAh)^{III} Optional: 2nd battery (10.8V, typical 6900mAh; min. 6600mAh)

Dimension (W x D x H) & Weight 350 x 293 x 38.5mm (13.8" x 11.5" x 1.5" 2.38kg (5.25lbs) ^{xv}

Rugged Features MIL-STD-810H certified IP53 certified

Splash resistant keyboard Vibration & 3ft (0.9m) drop resistant [™] Sealed ports and connectors Shock-protected removable SSD

Environmental Specifications

- Operating: -29°C to 63°C / -20°F to 145°F ^{xvii} - Storage: -51°C to 71°C / -60°F to 160°F Humidity: - 95% RH, non-condensing

Pre-installed Software

Getac Utility Getac Geolocation Getac Barcode Manager ^{xviii} Optional: Absolute Persistence®

Optional software

Getac Driving Safety Utility Getac Device Monitoring System (GDMS) Getac VGPS Utility ^{xx}

	Vehicle Dock	Office Dock
Serial Port	1	1
External VGA	1	1
Microphone	1	1
Audio Output	1	1
DC in Jack	1	1
USB	4	USB 3.0 x 1 USB 2.0 x 3
LAN	1	1
HDMI 2.0	1	1
RF Antenna Connector	3 (WWAN, WLAN, GPS)	-

S410 SEMI RUGGED NOTEBOOK

Accessories

Battery (10.8V, typical 6900mAh; min. 6600mAh) AC adapter (90W, 100-240VAC, 50/60Hz) Capacitive stylus with tether

Optional:

Carry bag Battery (10.8V, typical 6900mAh; min. 6600mAh) Multimedia 2nd SSD^{III} Multimedia bay battery (11.1V, tpyical 4200mAh; min. 3980mAh) ⁱⁱⁱ Multi-Bay charger (Dual-Bay) Multi-Bay charger (Eight-Bay) AC adapter (120W, 100-240VAC, 50/60Hz) [#] DC-DC vehicle adapter (120W, 11-32VDC) Capacitive stylus with tether Protection film Vehicle cradle ** Vehicle dock Office dock 100W Type-C adapter ^{xxi}

Warranty

vvarranty Nothing says quality like a manufacturer standing behind their product. We've designed the notebook from the inside out to survive drops, shocks, spills, vibration and more. We're confident in our quality and that's why it comes standard with the industry leading 3 years warranty. It's the peace-of-mind protection of knowing you're covered.

Standard

3 years limited warranty

- Units equipped with dual channel memory come with Intel® L.
- П.
- Drills equipped with dual chainer intensity, come that includes the second seco Ш.
- NVEDUA integer barcode reader and 2 storage are mutually exclusive options. NVIDIA[®] GeForce[®] GTX 1650 4GB discrete graphics controller is required to configure with Intel[®] Core[™] iS/i7 processor, Dual battery, FHD LCD display with capacitive multi-touch screen, and 120W AC adapter. Trained user swappable. Units with 4G/5G option come with an embedded SIM card slot. IV
- VI.
- VII VIII
- Units with 4G/5G option come with an embedded SIM card slot. 5M webcam and optional Windows Hello face-authentication camera (front-facing) are mutually exclusive options. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area. Support GP5, GLONASS, Galileo, BelDou and QZ55. Only available in the US, UK, EU, Australia, and New Zealand. Support GP5, GLONASS, Galileo and BeiDou. One physical SIM card slot and one eSIM. Network service may vary depending on local telecommunication providers. 13.56MHz HF RFID/NFC reader (ISO 15693, 14433 A/B, Mifare and FeliCa™ compliant). Weight and dimensions vary from configurations and optional accessories. Drop test results vary from configurations and optional accessories.
- IX. X. XI. XII.
- XIII.
- XIV.
- XV
- accessories. Tested by an independent third-party test lab following MIL-STD-810H. XVI.
- XVII
- STD-810⁴¹. For S410 optional DVD / Blu-Ray super-multi drive, the operating temperature is -10°C to 50°C / 14°F to 122°F. Available when barcode reader option is selected. Models require either embedded or standalone GPS module. Havis vehicle dock is e-mark certified. Do not support the configurations with discrete graphics card. XVIII. XIX. XX. XXI.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

Getac

15495 Sand Canyon Ave. Suite 350 Irvine, CA 92618 Tel : 949-681-2900 GetacSales_US@getac.com I

www.getac.com/us/ Copyright © 2023 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Information provided herewith is for reference only, available specification shall be subjected to quotation by request.