



- X UK BS1363 style sockets
- X High quality, light weight aluminium housing
- X Fully shrouded rocker switch
- X LED indicated unit power
- X Upto 12 sockets per unit

Features

- UK BS1363 style sockets
- Fully shrouded rocker switch
- Upto 12 sockets per unit
- 3 metre input lead terminated with 3 pin 13AMP fused BS1363 plug
- External earth facility
- High quality, light weight aluminium housing
- LED indicated unit power
- Choose from vertical and horizontal mounting options
- 250 volt AC, 50/60Hz Rating
- CE compliant, ROHS compliant
- Each unit is switched as standard


Product Overview

The Excel range of power distribution units are designed for installation and use within 19” networking cabinets and enclosures. Each unit comprises a high quality aluminium extruded housing into which are loaded up to 12 sockets. In this particular range each socket is UK style, manufactured in accordance with the BS1363 standard, the 3 metre input lead is terminated with a 13Amp rated 3 pin BS1363 plug top. The sockets are mounted at a 45° angle on the vertical PDUs and a 90° angle on the horizontal PDUs to aid with cable management.


The range of available units includes 19” horizontally mounted, and higher density vertical mounted options, each unit contains a fully shrouded switch to control input power, and a LED indicator to confirm power to the unit.

Product Drawing

Part number D13-10-EXL, 10 way vertical mounting unit with shrouded rocker switch and LED power indicator.



Images represent product style only. Switched unit shown.



3 Pin BS1363 Socket



3 Pin BS1363 Plug



Shrouded Rocker Switch and LED Indicator

Product Specification - Housing

Property	Value
Socket Type	BS1363 (UK) Style - 90° on horizontal PDU - 45° angle on vertical PDU
Max No of sockets - Switched	6 - Horizontal mounting, 12 - Vertical mounting
Input Lead	3 metre 3 core 1.5mm cable terminated with 3 pin UK BS1363 style
Rated voltage	250 V AC 50/60 Hz
Rated current	13 A
Maximum power	3250 W
Unit Control	LED indicator. On/off rocker switch
Fixing Kit	M6 x 4 fixings, user manual, 6mm earth cable
Safety Mark	CE certified
RoHS Compliance	Yes

Product Dimensions

Model	Overall Dimensions			Case Length	Mounting Centres
	Length	Width	Height		
4 Way - Horizontal	482.6 mm	44.4 mm	62 mm	427 mm	465 mm
5 Way - Horizontal	482.6 mm	44.4 mm	62 mm	427 mm	465 mm
6 Way - Horizontal	482.6 mm	44.4 mm	62 mm	427 mm	465 mm
4 Way - Vertical	482.6 mm	44.4 mm	62 mm	427 mm	465 mm
5 Way - Vertical	482.6 mm	44.4 mm	62 mm	427 mm	465 mm
6 Way - Vertical	590 mm	44.4 mm	62 mm	534 mm	562 mm
8 Way - Vertical	720 mm	44.4 mm	62 mm	664 mm	692 mm
10 Way - Vertical	850 mm	44.4 mm	62 mm	794 mm	822 mm
12 Way - Vertical	980 mm	44.4 mm	62 mm	924 mm	952 mm

Part Number Information - Horizontal Mounting

Part No.	Description
D13-4H-EXL	4 Way 90° Angle UK Socket PDU - UK Plug - Horizontal
D13-5H-EXL	5 Way 90° Angle UK Socket PDU - UK Plug - Horizontal
D13-6H-EXL	6 Way 90° Angle UK Socket PDU - UK Plug - Horizontal

Part Number Information - Vertical Mounting

Part No.	Description
D13-4-EXL	4 Way 45° Angle UK Socket PDU - UK Plug - Vertical
D13-5-EXL	5 Way 45° Angle UK Socket PDU - UK Plug - Vertical
D13-6-EXL	6 Way 45° Angle UK Socket PDU - UK Plug - Vertical
D13-8-EXL	8 Way 45° Angle UK Socket PDU - UK Plug - Vertical
D13-10-EXL	10 Way 45° Angle UK Socket PDU - UK Plug - Vertical
D13-12-EXL	12 Way 45° Angle UK Socket PDU - UK Plug - Vertical

Excel is a world-class premium performing end-to-end infrastructure solution - designed, manufactured, supported and delivered - without compromise.

Contact us at sales@excel-networking.com

excel
without compromise.

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.

www.excel-networking.com