

# Mini Converter UpDownCross HD



Mini Converter UpDownCross HD is a full standards converter that lets you convert any SD or HD video format to any other SD or HD video format! You get both SDI and HDMI inputs and outputs, along with reference input for built in re-sync, high quality Teranex conversion algorithms, automatic audio delay for perfect AV sync, international power supply and more!

**\$155**

## Connections

### SDI Video Inputs

1 x SD, HD or 3G-SDI Video Input and 1 x External Reference Input.

### HDMI Video Output

HDMI type A out. Output supports EDID of the monitor.

### Multi Rate Support

Auto detection of HD or standard definition SDI inputs.

### HDMI Video Input

1 x HDMI type A connector.

### SDI Rates

270Mb, 1.5G, 3G.

### Updates and Configuration

USB

### SDI Video Outputs


1 x loop out and 2 x outputs

### Reference Input

Black burst and Tri-Sync for SD & HD.

### Relocking

Yes



## Standards

### SD Video Standards

525i59.94 NTSC, 625i50 PAL

---

**HD Video Standards**

720p50, 720p59.94, 720p60,  
1080p23.98, 1080p24, 1080p25,  
1080p29.97, 1080p30, 1080p50,  
1080p59.94, 1080p60, 1080PsF23.98,  
1080PsF24, 1080PsF25,  
1080PsF29.97, 1080PsF30, 1080i50,  
1080i59.94, 1080i60

**HDMI Input Video Standards**

720p50, 720p59.94, 720p60,  
1080p23.98, 1080p24, 1080p25,  
1080p29.97, 1080p30, 1080p50,  
1080p59.94, 1080p60, 1080i50,  
1080i59.94, 1080i60

**SDI Compliance**

SMPTE 259M, SMPTE 292M,  
SMPTE 296M, SMPTE 424M-B,  
ITU-R BT.656 and ITU-R BT.601.

**SDI Metadata Support**

Timecode and closed captioning.

**SDI Video Rates**

SDI video connections are switchable  
between standard definition  
and high definition.

**SDI Video Sampling**

4:2:2

**SDI Audio Sampling**

Television standard sample rate of  
48 kHz and 24 bit.

**SDI Color Precision**

4:2:2

**SDI Color Space**

YUV

**SDI Auto Switching**

Automatically detects SD,  
HD or 3G-SDI.

---

## Format Conversion

**Video Conversion**

Convert any SD and HD input to "720p50, 720p59.94, 720p60, 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60, 1080i50, 1080i59.94, 1080i60"

**Computer Scaling**

Scale DVI resolutions 640x480, 800x600, 1024x768 to 525i59.94, 625i50, 720p50, 720p59.94, 720p60, 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60, 1080i50, 1080i59.94, 1080i60

---

## Software

**Internal Software Upgrade**

Via included updater application.

---

## Operating Systems



Mac 10.12 Sierra,  
Mac 10.13 High Sierra or later.



Windows 8.1 or Windows 10.

---

## Settings Control

**Mini Switches**

---

## Power Requirements

### Power Supply

+12V universal power supply included with international socket adapters for all countries.

### Power Consumption

5W

### Operational Voltage Range

6 to 36 Vdc.

---

## Physical Specifications



---

## Environmental Specifications

### Operating Temperature

0° to 40° C (32° to 104° F)

### Storage Temperature

-20° to 45° C (-4° to 113° F)

### Relative Humidity

0% to 90% non-condensing

---

## What's Included

Mini Converter UpDownCross HD

12V universal power supply with international socket adapters

---

## Warranty

3 Year Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2019, all rights reserved.  
All trademarks are property of their respective owners. MSRP excludes sales taxes/duties and shipping costs.  
This website uses remarketing services to advertise on third party websites to previous visitors to our site.  
You can opt out at any time by changing cookie settings. [Privacy Policy](#)

Blackmagic Design Authorized Reseller