ATEN PE6208AV-ATA-G power distribution unit (PDU) 8 AC outlet(s) 1U Black

Brand : ATEN

Product code: PE6208AV-ATA-G



Product name : PE6208AV-ATA-G

- Detachable front panel fits 19" racks with different depths

- Supports RS-232 port and power outlet control (on/off) by outlet group

- Remote and local power outlet control (On/Off, Power Cycle) by individual outlets and outlet groups

- Proactive Overload Protection (POP) - automatically powers off the last outlet that caused the current

overload to protect high-end pro-A/V equipment and servers

8-Outlet eco PDU, Fast Ethernet, Serial, 1U

ATEN PE6208AV-ATA-G. PDU types: Metered, Rack capacity: 1U, Mounting: Horizontal. AC outlets quantity: 8 AC outlet(s), AC outlet types: NEMA 5-20R, Power plug: NEMA L5-20P. Cable length: 3 m, Security algorithms: 128-bit SSL, Certification: FCC, J55032. Supported network protocols: TCP/IP, UDP, HTTP, HTTPS, SSL, DHCP, SMTP, ARP, NTP, DNS, Auto Sense, Ping, Management protocols: SNMP V1, V2, V3, Telnet. Nominal input voltage: 100 - 240 V, Maximum current: 20 A, AC input frequency: 50 - 60 Hz

Design		Management features	
PDU types * Rack capacity * Mounting Product colour	Metered 1U Horizontal Black	Supported network protocols Management protocols	TCP/IP, UDP, HTTP, HTTPS, SSL, DHCP, SMTP, ARP, NTP, DNS, Auto Sense, Ping SNMP V1, V2, V3, Telnet
Ports & interfaces		Power	
AC outlets quantity * Power plug AC outlet types * Serial ports quantity	8 AC outlet(s) NEMA L5-20P NEMA 5-20R 1	Nominal input voltage * AC input frequency Maximum current * Power protection features Weight & dimensions	100 - 240 V 50 - 60 Hz 20 A Overload
Ethernet LAN (RJ-45) ports	1	weight & unitensions	
		Width	432.4 mm
Features LED indicators Cable length Security algorithms	✓ 3 m 128-bit SSI	Width Depth Height Weight	432.4 mm 363.9 mm 44 mm 4.67 kg
LED indicators	✓ 3 m 128-bit SSL	Depth Height	363.9 mm 44 mm
LED indicators Cable length Security algorithms	128-bit SSL	Depth Height Weight	363.9 mm 44 mm
LED indicators Cable length Security algorithms Password protection	128-bit SSL ✓	Depth Height Weight Packaging content	363.9 mm 44 mm 4.67 kg

Operating relative humidity (H-H) 0 - 80%

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.