

Samsung OHB-S OH46B-S Digital signage flat panel 116.8 cm (46") LCD 3500 cd/m² Full HD Black Built-in processor Tizen 6.5 24/7

Brand : Samsung

Product family: OHB-S

Product code:
LH46OHBESGBXEN

Product name : OH46B-S



Samsung OHB-S OH46B-S. Product design: Digital signage flat panel. Display diagonal: 116.8 cm (46"), Display technology: LCD, Display resolution: 1920 x 1080 pixels, Display brightness: 3500 cd/m², HD type: Full HD. Operating hours (hours/days): 24/7. Operating system installed: Tizen 6.5. Product colour: Black

Display		Design	
Panel type	VA	Panel mounting interface	995 x 500 mm
Display diagonal *	116.8 cm (46")	Bezel width (bottom)	2.49 cm
Display technology *	LCD	Bezel width (side)	2.49 cm
Display resolution *	1920 x 1080 pixels	Bezel width (top)	2.49 cm
Display brightness *	3500 cd/m ²	Bezel colour	Black
HD type *	Full HD	Performance	
Touchscreen *	✗	Purpose *	Universal
Response time	6 ms	Operating hours (hours/days)	24/7
Contrast ratio (typical)	6000:1	HDCP	✓
Dynamic contrast ratio marketing name	Mega Contrast	HDCP version	2.2
Viewing angle, horizontal	178°	Power	
Viewing angle, vertical	178°	Power consumption (typical) *	430 W
Pixel pitch	0.53 x 0.53 mm	Power consumption (sleep)	0.5 W
Horizontal scan range	15 - 135 kHz	AC input voltage	100 - 240 V
Vertical scan range	24 - 75 Hz	AC input frequency	50 - 60 Hz
Glass thickness	5 mm	Computer system	
Glass film	AG/AR Film	Computer system *	✓
RGB colour space	NTSC	Computer system type	System on Chip (SoC)
Colour gamut	72%	Built-in processor *	✓
Ports & interfaces		Operating system installed	Tizen 6.5
HDMI ports quantity *	2	Weight & dimensions	
HDMI version	2.0	Display width	1069 mm
DVI port *	✗	Display depth	85 mm
USB port *	✓	Display height	623.6 mm
USB ports quantity	1	Display weight	36 kg
Ethernet LAN *	✓	Packaging data	
Ethernet LAN (RJ-45) ports	2	Package width	1156 mm
Wi-Fi *	✗	Package depth	200 mm
Audio (L/R) out	1	Package height	713 mm
RS-232 interface	✓	Package weight	40.5 kg
Audio		Operational conditions	
Built-in speaker(s) *	✗	Operating temperature (T-T)	-30 - 50 °C
Design		Operating relative humidity (H-H)	10 - 80%
Product design *	Digital signage flat panel	Certificates	
Orientation	Horizontal/Vertical	Certification	Class A 60950-1, 62368-1
Product colour *	Black		
Screen shape	Flat		

Design

VESA mounting *


**Other features**

Flash memory

8000 MB

Glass protection





8806094726541

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.