

DELL P7524QT Interactive flat panel 189.3 cm (74.5") LCD 350 cd/m² 4K Ultra HD Black Touchscreen

Brand : DELL P7524QT

Product name: P7524QT

- 75" 4K UHD 3840 x 2160, IPS
- 8ms, 16:9, 350cd/m², 1200:1

Native refresh rate

60 Hz

- USB, HDMI, VGA, DisplayPort"

75" 4K UHD 3840 x 2160, IPS, 16:9, 350 cd/m² 1.07 Billon, 8 ms, $178^{\circ}/178^{\circ}$, 1200:1

DELL P7524QT Interactive flat panel 189.3 cm (74.5") LCD 350 cd/m² 4K Ultra HD Black Touchscreen:

Bring the team together, whether they are in the room or remote, with this brilliant 75" 4K UHD large format monitor with 20-point touch, palm-rejection and built-in dual 20W speakers. DELL P7524QT. Product design: Interactive flat panel. Display diagonal: 189.3 cm (74.5"), Display technology: LCD, Display resolution: 3840 x 2160 pixels, Display brightness: 350 cd/m², HD type: 4K Ultra HD, Touchscreen. Product colour: Black











Display		Performance	
Panel type	IPS	Purpose *	Corporate
LED backlight	✓	On Screen Display (OSD)	✓
Display diagonal *	189.3 cm (74.5")	HID support	✓
Display technology *	LCD	Power	
Display resolution *	3840 x 2160 pixels	Power consumption (typical) *	140 W
Display brightness *	350 cd/m ²	Power consumption (standby) *	0.5 W
HD type *	4K Ultra HD	Power consumption (off)	0.3 W
Touchscreen *	✓	Power consumption (max)	290 W
Number of simultaneous	20	Energy efficiency class (SDR)	G
touchpoints		Energy efficiency class (HDR)	Not available
Multi-touch	V	Energy consumption (SDR) per 1000	
Native aspect ratio	16:9	hours	140 kWh
Response time	8 ms	AC input voltage	100 - 240 V
Contrast ratio (typical)	1200:1	AC input frequency	50/60 Hz
Viewing angle, horizontal	178°	Heat dissipation	477.7 BTU/h
Viewing angle, vertical	178°	Energy efficiency scale	A to G
Display number of colours	1.07 billion colours	Computer system	
Pixel pitch	0.429 x 0.429 mm	•	
Display diagonal (metric)	189.273 cm	Windows operating systems supported	Windows 7 Professional, Windows 7 Ultimate, Windows 8, Windows 8.1
Horizontal scan range	30 - 140 kHz	• •	Mac OS X 10.10 Yosemite, Mac OS X
Vertical scan range	24 - 75 Hz	Mac operating systems supported	10.11 El Capitan
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1200, 1920 x 1080 (HD 1080), 2048 x 1152, 2560 x 1440, 3840 x 2160	Linux operating systems supported	✓
		Weight & dimensions	
		Display width	1735 mm
		Display depth	79.1 mm
Supported video modes	480p, 576p, 720p, 1080i, 1080p, 2160p	Display height	1017.4 mm
		Display weight	64 kg
Hardness	9H		

Display		Packaging data	
RGB colour space	NTSC	Package weight	76.6 kg
Colour gamut	72%	Packaging content	
Ports & interfaces HDMI ports quantity * 3 HDMI version 2.0 DVI port * *	Remote control included Stylus pen Number of stylus pens Cables included	✓ ✓ 2 AC, DisplayPort, HDMI, USB, VGA	
VGA (D-Sub) input ports	1	Operational conditions	
DisplayPorts quantity * USB port * USB ports quantity USB version USB connector type USB 2.0 Type-B ports quantity	1 7 2.0/3.2 Gen 1 (3.1 Gen 1) Mini-USB A 3	Operating temperature (T-T) Operating relative humidity (H-H) Storage temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C 10 - 80% -20 - 60 °C 5 - 90% 0 - 5000 m 0 - 12192 m
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4	Features	
USB Type-C DisplayPort Alternate Mode	✓	Heat dissipation (max)	989.52 BTU/h
Ethernet LAN *	✓	Technical details	
Ethernet LAN (RJ-45) ports Wi-Fi * Audio (L/R) in Audio (L/R) out	1 X 1 1	Sustainability compliance Sustainability certificates Doesn't contain Compliance certificates	▼ ENERGY STAR Arsenic, Mercury, PVC/BFR RoHS
RS-232 interface	✓	Other features	
Audio Built-in speaker(s) * Number of built-in speakers RMS rated power	✓ 2 40 W	Quick start guide Cable lock slot LED indicators On/off switch	√ √ √
Design		Viewable size diagonal	18.9 cm
Product design * Placement supported * Product colour * Screen shape VESA mounting * Panel mounting interface Bezel width (bottom) Bezel width (side) Bezel width (top) Anti-glare screen	Interactive flat panel Indoor Black Flat 400 x 400 mm 4.67 cm 4.27 cm 4.28 cm	Viewable size, horizontal Viewable size, vertical Power supply type Cable management Response time Plug and Play	165 cm 92.8 cm Internal ✓ 8 s



5397184821558

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.