ASUS EBA63 ExpertWiFi AX3000 Dual-band PoE 2402 Mbit/s White Power over Ethernet (PoE)

Brand : ASUS Product code: 90IG0880-M03C00

Product name: EBA63 ExpertWiFi AX3000 Dual-band

PoE

AX3000 Dual-Band WiFi 6 (802.11ax) PoE Access Point, support up to 5 SSIDs and VLAN, Self-defined Network, support PoE & PoE+, easy management app, AiMesh compatible ASUS EBA63 ExpertWiFi AX3000 Dual-band PoE. Maximum data transfer rate: 2402 Mbit/s, Maximum data transfer rate (2.4 GHz): 574 Mbit/s, Maximum data transfer rate (5 GHz): 2402 Mbit/s. Security algorithms: IPSec, SSH, WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal, WPS. DC voltage range: 12 V, Input current: 1.5 A. Placement: Ceiling, Wall, Product colour: White, LED indicators: Power. Antenna type: Internal





Features		Design	
2.4 GHz * 5 GHz * 6 GHz * Maximum data transfer rate * 2402 Mbit	<i>'</i>	Placement * Product colour * Reset button LED indicators	Ceiling, Wall White V Power
Maximum data transfer rate (2.4 GHz) Maximum data transfer rate (5 GHz)	574 Mbit/s 2402 Mbit/s	Antenna Antenna type *	Internal
Ethernet LAN data rates Frequency band	10,100,1000 Mbit/s 2.4 - 5 GHz	Antennas quantity Performance	4
Networking standards Number of users Spread spectrum method	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n 100 user(s) OFDMA	Built-in processor Processor frequency Flash memory Internal memory	1.7 MHz 256 MB 512 MB
VLAN support	√	Weight & dimensions	
Security Security algorithms *	IPSec, SSH, WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-	Width Depth Height Weight	160 mm 160 mm 42 mm 426 g
MAC address filtering Number of SSID supported	Personal, WPS	Packaging data Package width	262 mm
Management features		Package depth Package height	180 mm 58 mm
Syslog Firmware upgradeable	1	Package weight Package type	750 g Box
Ports & interfaces		Packaging content	
Ethernet LAN (RJ-45) ports * Power Power over Ethernet (PoE) *	1	AC adapter included Cables included Mounting kit	✓ LAN (RJ-45) ✓
DC voltage range	12 V	Quick start guide	✓

	W	

Input current

1.5 A



4711387003442

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.