PHILIPS

Philips V Line 241V8LAB/00 LED display 60.5 cm (23.8") 1920 x 1080 pixels Full HD LCD Black

Brand : Philips Product family: V Line Product code: 241V8LAB/00

Product name: 241V8LAB/00

Monitor 241V8LAB LCD monitor

Philips V Line 241V8LAB/00 LED display 60.5 cm (23.8") 1920 x 1080 pixels Full HD LCD Black:

Philips V line wide-view monitor gives viewing beyond boundaries. Adaptive Sync, a 1 ms MPRT response rate and a 100 Hz refresh rate deliver smooth video display. Features like anti-glare, LowBlue mode and flicker-free make it easy on the eyes.

Philips V Line 241V8LAB/00. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). VESA mounting. Product colour: Black







Display		Ergonomics	
Display diagonal *	60.5 cm (23.8")	VESA mounting *	✓
Display resolution *	1920 x 1080 pixels	Panel mounting interface	100 x 100 mm
HD type *	Full HD	Cable lock slot *	✓
Native aspect ratio *	16:9	Cable lock slot type	Kensington
Display technology *	LCD	Height adjustment *	×
Panel type *	VA	Tilt adjustment	✓
Backlight type	W-LED	Tilt angle range	-5 - 20°
Touchscreen *	×	On Screen Display (OSD)	✓
Display brightness (typical)	250 cd/m²		Simplified Chinese, Traditional
Anti-glare screen	✓	On Screen Display (OSD) languages	Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian
Screen shape *	Flat		
Contrast ratio (typical) *	4000:1		
Dynamic contrast ratio marketing name	Mega Infinity DCR	Number of OSD languages	Swedish, Turkish, Ukrainian 20
Maximum refresh rate *	100 Hz	Plug and Play	✓
Viewing angle, horizontal	178°	LED indicators	Operation, Stand-by
Viewing angle, vertical	178°	Power	
Display number of colours *	16.7 million colours	Power consumption (typical) *	26.83 W
Pixel pitch	0.2745 x 0.2745 mm	Power consumption (typical) *	0.5 W
Pixel density	92.56 ppi	Power consumption (standay)	0.3 W
Horizontal scan range	30 - 115 kHz	AC input voltage	100 - 240 V
Vertical scan range	48 - 100 Hz	AC input voitage AC input frequency	50/60 Hz
Viewable size, horizontal	52.7 cm	Power supply type	Internal
Viewable size, vertical	29.6 cm	> 2.	incernal
Sync-on-green (SOG)	✓	Operational conditions	
Display diagonal (metric)	60.5 cm	Operating temperature (T-T)	0 - 40 °C
DDC/CI	✓	Storage temperature (T-T)	-20 - 60 °C
Haze rate	25%	Operating relative humidity (H-H)	20 - 80%
Surface hardness	3H	Operating altitude	0 - 3658 m
Colour depth	8 bit	Non-operating altitude	3658 - 12192 m

Display		Packaging content	
	sRGB	Stand included	,
Colour gamut standard	SKGB ✓	Cables included	✓ AC, HDMI
Display sRGB	~	Manual	AC, HDMI ✓
Performance			4
NVIDIA G-SYNC *	×	Weight & dimensions	
AMD FreeSync *	×	Width (with stand)	540 mm
VESA Adaptive Sync support	✓	Depth (with stand)	220 mm
Component video sync	Separate sync, Sync-on-green (SOG)	Height (with stand) Weight (with stand)	416 mm 3 kg
Flicker-free technology	✓	Width (without stand)	540 mm
Low Blue Light technology	✓	Depth (without stand)	51 mm
Compatible operating systems	Mac OS X Windows 11 / 10 / 8.1 / 8	Height (without stand)	322 mm
Multimedia		Weight (without stand)	2.61 kg
Built-in speaker(s) *	✓	Packaging data	
Built-in camera *	×	Package width	607 mm
Number of speakers	2	Package depth	121 mm
RMS rated power	4 W	Package height	415 mm
Design		Package weight	4.85 kg
Market positioning *	Home	Sustainability	
Product colour *	Black	Sustainability compliance	✓
Heavy metals free	Hg (mercury)	Sustainability certificates	China Energy Label (CEL), ENERGY STAR
Ports & interfaces		Doesn't contain	Mercury, PVC/BFR
Built-in USB hub *	×		Mercury, PVC/BITK
VGA (D-Sub) ports quantity	1	Other features	
HDMI *	✓	Exterior finish type	Textured
HDMI ports quantity	1	Picture enhancement	SmartImage
HDMI version	1.4	Recyclable packaging material	100%
Audio output	✓	Dogulaton, Approvals	CECP; CCC; CEL; CB; CE Mark; EAC;
PC Audio in	✓	Regulatory Approvals	FCC; ICES-003; PSB; TUV Ergo; TUV/GS
HDCP	✓	EasyRead mode	√
HDCP version	1.4	LowBlue mode	· •
		Mean time between failures (MTBF)	30000 h
		,	



8712581804329

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.